

## **Caution**

Millions of men and women reload ammunition as a hobby or because the cost savings allow them to do more shooting. In order to become or to continue as a safe reloader, **you must be cautious and careful**. You are the production department and the quality control department. Later, when you shoot the ammunition that only you produced and checked, you are the person closest to the gun if it malfunctions because of faulty ammunition — yours.

**Remember—you are dealing with an explosive material. You become a “miniature” manufacturer working with powders and primers that can, if misused, explode or burn, causing serious personal injury (including death) and property damage.**

**Read and study one or more good books that describe reloading techniques in detail. When using smokeless powders, use only the exact type and quantity recommended herein. Store and use smokeless powders—your powders—according to the safety rules listed in this booklet. Reload for quality, so that the safest and most accurate loads on the shooting line will be yours.**

## **Ballistics**

The ballistic data shown in this booklet were obtained in the laboratory under strictly controlled conditions. **You must load only those exact combinations that are listed.** Even then, different reloading techniques, plus industrial tolerances of each component, likely will cause your ammunition, or ammunition loaded by other competent laboratories, to yield slightly different ballistic data. Therefore, **charge recommendations in this booklet must never be exceeded.** Smart shooters and hunters know that accuracy, not maximum power, is their key to success.

## **Disclaimer**

Alliant disclaims any warranties with respect to this product, the safety or suitability thereof, or the results obtained, whether express or implied, including, without limitation, any implied warranty of merchantability or fitness for a particular purpose and/or any other warranty. Buyers and users assume all risk, responsibility, and liability whatsoever for any and all injuries (including death), losses, or damages to persons or property arising from the use of this product, whether or not occasioned by seller's negligence or based on strict product liability or principles of indemnity or contribution. Alliant neither assumes nor authorizes any person to assume for it any liability in connection with the use of this product.

## **Powder Warnings**

- **NEVER** substitute smokeless powder for black powder, or for Pyrodex, or for any other smokeless powder.
- **NEVER** mix together any two powders, regardless of type, brand, style, or source.
- **NEVER** use the data in this *Reloaders' Guide* for any other powders, even if advertised “similar to Bullseye” or “burns the same as Red Dot,” etc.

*Violation of any of the above could result in severe personal injury (including death) or gun damage.*

## Table of Contents

	Page
Smokeless Powders for Reloading	4
Packaging	4
Powder Information	
Dram Equivalent	4
<b>Important Safety and Health Precautions</b>	5
Reference Tables	5–6
Ballistic Data	6
Special Notes Regarding Components	6
Black Powder	6
1996 Powder Bushing Charts	7
<b>Properties and Storage of Smokeless Powder</b>	8–9
10-Gauge Loads	10
12-Gauge Loads	
3½-Inch Shells	11
Federal 2¾- and 3-Inch Shells	12–18
Remington-Peters 2¾- and 3-Inch Shells	19–23
Additional 7/8-Ounce Target Loads	23
Winchester-Western 2¾- and 3-Inch Shells	24–27
Activ 2¾- and 3-Inch Shells	28–29
Fiocchi 2¾- and 3-Inch Shells	30–31
Additional 2¾-Inch 1-Ounce Target Loads	32
28-Gram International Target Loads	33
16-Gauge Loads	34–35
20-Gauge Loads	35–40
28-Gauge Loads	40–41
.410-Bore Loads	41
Buckshot and Rifled Slug Loads	42–43
Pistol and Revolver Loads	44–46
Silhouette Loads	47
Centerfire Rifle Loads	48–55
<b>Pistol and Revolver Cartridges—Special Reloading Precautions</b>	56
Physical Effect of Gun Recoil	56
<b>Handloading Precautions</b>	57
Crusher/Piezo Pressure Tabulation	57
Some Publications on Reloading	Inside Back Cover

**WARNING: The shotgun shell loading data in this booklet are for lead shot only. Steel shot cannot be substituted. Also, do not use buffers or fillers of any kind.**



## Smokeless Powders for Reloading

We currently offer 14 powders for use in reloading. These are listed in the order of decreasing burning rates. Each powder listed is "slower" than those preceding it and "faster" than those following it. Among these Alliant smokeless powders, for example, Red Dot® burns more slowly than Bullseye®, but faster than Green Dot®.

Powder	Principal Use <sup>1</sup>	Can Also be Used In <sup>1</sup>
Bullseye®	Handgun Loads	12-Gauge Light Target Loads
Red Dot®	Light and Standard Shotshell Loads, 12-, 16-, and 20-Gauge	Handgun Loads
American Select™	12-Gauge Target Loads	Handgun Loads
Green Dot®	Standard and Medium Shotshell Loads, 12-, 16-, and 20-Gauge	Handgun Loads
Unique®	All-Around Shotshell Powder, 12-, 16-, 20-, and 28-Gauge	Handgun Loads
<b>POWER PISTOL™</b>	High performance pistol loads such as the 9mm, .40 S&W, and 10mm	Moderate pressure pistol cartridges like the .38 Special, .380 Auto, and .45 ACP
Herco®	Heavy Shotshell Loads, 10-, 12-, 16-, 20-, and 28-Gauge	Heavy Handgun Loads
Blue Dot®	Magnum Shotshell Loads, 10-, 12-, 16-, 20-, and 28-Gauge	Magnum Handgun Loads
2400®	Magnum Handgun Loads	Some Rifle and Shotshell Loads
Reloder® 7	Light Rifle Loads	Silhouette Loads
Reloder® 12	Medium Rifle Loads	Silhouette Loads
Reloder® 15	Medium Rifle Loads	Silhouette Loads
Reloder® 19	Magnum Rifle Loads	Target and hunting rifle loads
Reloder® 22	Magnum Rifle Loads	Maximum hunting loads

<sup>1</sup>Use only in the loads printed in this Guide.

## Packaging

Powder	1-lb Canister	4-lb Canister	5-lb Canister	8-lb Keg
Bullseye, Red Dot, American Select, Green Dot, Unique, Herco, 2400	x	x		x
Power Pistol™	x	x		
Blue Dot	x		x	
Reloder Series	x		x	

All 14 powders are always in stock at distributors' magazines throughout the U.S.A., and in most countries where reloading is legally permitted and popular. Any reloader unable to purchase any of the 14 powders at retail stores that handle powders should write to the address on the back cover. We cannot ship directly, but we will endeavor to correct supply shortages in your area.

## Powder Information

Smokeless sporting propellants are of two basic types – single-base and double-base. Single-base propellants derive their energy from nitrocellulose and double-base from a combination of nitrocellulose and nitroglycerin. Alliant propellants range from the "near" single-base American Select (2% nitroglycerin) to the high nitroglycerin (40%) double-base Bullseye. In addition, our propellants contain stabilizers for long storage life and various other ballistic modifiers which reduce flash, improve combustion efficiency, and promote clean burning.

Some of our propellants also have a chemical coating on the surface to control the burning rate. This creates a progressive burn for achieving higher velocities at lower pressures. All of our propellants have a graphite glaze, which ensures smooth, consistent metering of charges through volumetric reloaders.

Alliant propellants are extruded and cut into circular flakes or cylinders by precision dies and cutting equipment. Granule size tolerances are very tight and uniform to prevent separation of different size granules and to ensure consistent ballistic performance, load after load.

By utilizing a precise combination of chemical formulation, granule size, and chemical coatings, we are able to tailor the burning characteristics of our propellants to achieve the best overall performance in a wide range of loads.

Because each of our propellants is specifically engineered to have different burn rates and performance characteristics, **NEVER BLEND OR MIX DIFFERENT POWDERS, AND USE ONLY THE GRADE AND QUANTITY RECOMMENDED IN THIS RELOADER'S GUIDE.**

All powders burn with great precision and rapidity inside the gun chamber, generating the hot, high-pressure gas that accelerates the bullet (or shot) and drives it toward the target. It is critically important for safety that the powder used is matched to the bullet (or shot) weight and other factors; otherwise, the gun parts may be deformed or may even burst and cause serious personal injury (including death). Shot-to-shot accuracy can also be degraded by deviations from recommended loads. Even after 80 years of producing and testing powders, ballisticians are unable to calculate and predict exact ballistic results; we must test-fire our powders with each set of components and record the results. Therefore, the ballistic values and recommended combinations listed in this booklet must be followed without deviation.

**Working up charges.** For shotgun loads, use the charge weight shown. However, for all rifle and pistol loads, first load and fire a few cartridges at 10% less charge than is shown, watching for any sign of excessive pressure (difficult extraction, flattened or blown primers, unusual recoil).

**Handgun loads.** Many pistol and revolver loads require only small amounts of fast-burning powders; therefore: (1) guard against accidental double charges, and even multiple charges, whether loading with handtools or with progressive loading devices; (2) be sure that each bullet is positioned in the case so that the minimum overall length is not violated.

## Dram Equivalent

Prior to the commercialization of smokeless powder, shotgun shells were loaded with black powder. The weight measurement system used for black powder was "drams." Compared with black powder, smokeless powder is more dense and MUCH more energetic, so it cannot safely be measured and used like black powder. Indeed, a different weight system was selected for smokeless powder: "grains," wherein 7,000 grains equal one pound.

Since many shooters still wanted to be able to compare their smokeless powder loads with the original black powder loads, the term "dram equivalent" evolved. Simply stated, the dram equivalent is an indicator of the velocity of a particular shot load. But note that the charge and weight of smokeless powder must not be calculated from the dram equivalent.

## Notice

We have inserted information on the properties and storage of smokeless powder for your understanding, so that you can avoid unnecessary risks when using it. This information, on pages 8 and 9, was published initially by the Sporting Arms and Ammunition Manufacturers' Institute, Inc., several years ago in the interest of safety. You must read these pages carefully and comply with the precautions listed. If you have questions, please call or write to us at the address on the back cover.

# Important Safety and Health Precautions

To perform in a gun, powders must ignite easily and burn rapidly. These characteristics require use of common sense to avoid accidents. **YOU MUST OBSERVE THESE PRECAUTIONS:**

1. DO NOT smoke when reloading.
2. DO NOT use spark-producing tools.
3. DO NOT mix powders of different kinds.
4. DO NOT leave powder where children can get it.
5. DO NOT try to load when distracted.
6. Avoid an open fire or working near spark-producing machinery.
7. Pour out only the amount of powder needed for immediate work.
8. Check the powder measure each time it is used. Make sure the settings have not been accidentally changed. Check-weigh "thrown charges" frequently.
9. Clean up any spilled powders. Use a brush and dustpan; do not use a vacuum cleaner. Dispose of spilled powder as described in the SAAMI pages of this Guide.
10. Store powder only in its original container, which was carefully designed for this usage. DO NOT REPACKAGE. Do not purchase or accept any Alliant powder not in its original, FACTORY-SEALED container.
11. Be sure the powder container is completely empty before discarding. Do not use the container to store other powders or materials, or for any other purpose.
12. Always keep in mind that smokeless powder is an explosive material and highly flammable. It should always be stored and handled in such a way as to avoid impact, friction, heat, sparks, or flame.
13. Wear safety glasses when reloading.
14. This material contains nitroglycerin. Inhalation, skin contact, or ingestion may cause severe headache, nausea, and lowering of blood pressure. **THEREFORE, THE FOLLOWING PRECAUTIONS MUST BE OBSERVED WHEN HANDLING POWDERS:**
  - A. Do not take internally. In case of ingestion, cause vomiting. Call a physician.
  - B. Avoid contamination of food, beverages, or smoking materials.
  - C. Avoid breathing dust. Ensure adequate ventilation during handling.
  - D. Wash thoroughly after handling and before eating, drinking, or smoking.
  - E. Do not carry powder in clothing.

You must also always remember:

1. Establish a routine for reloading. It will result in more uniform loads and less chance of error.
2. Some primers are more powerful than others (they produce more gas at a higher temperature). Use only the primers specified herein.
3. Shotshell wads differ in their sealing ability. Use only the load combinations specified herein.
4. If you use cast bullets, their diameter, hardness, lubrication, and crimp will affect the ballistics.
5. **The shotshell loads in this booklet are for use with LEAD SHOT ONLY!**
6. Use only the brands of powder and components shown in our tables. Do not substitute other types.
7. Discharging firearms in poorly ventilated areas, cleaning firearms, or handling ammunition may result in exposure to lead, a substance known to cause birth defects, reproductive harm, and other serious physical injury. Have adequate ventilation at all times. Wash hands and face thoroughly after handling and before coming in contact with food, chewing materials, and smoking material.







## Reference Tables

### Approximate Number of Pellets in Specific Weights of Lead Shot (Sizes 2 Through 9)

Weight, oz	No. 2	No. 4	No. 5	No. 6	No. 7½	No. 8	No. 8½	No. 9
½	45	67	85	112	175	205	242	292
¾	67	101	127	168	262	308	363	439
⅞	79	118	149	197	306	359	425	512
1	90	135	170	225	350	410	485	585
1½	101	152	191	253	393	461	545	658
1¼	112	169	213	281	437	513	605	731
1¾	124	186	234	309	481	564	665	804
1½	135	202	255	337	525	615	730	877

### Space Occupied by One Ounce of Shot in Various Gauges

(Values are Inches)



### Internal Diameter of the Barrel in Several Shotgun Gauges

- 10-Gauge—0.775-Inch  
12-Gauge—0.729-Inch  
16-Gauge—0.662-Inch  
20-Gauge—0.615-Inch  
28-Gauge—0.550-Inch  
.410-Bore—0.410-Inch

## Reference Tables (continued)

### Number of Shells That Can Be Loaded with One Pound of Powder at Various Grains Per Load

(The term grain is a measure of weight: 7,000 grains equal one pound)

Grains/ Load	Loads/ Pound										
12	583	23	304	34	205	45	156	56	125	67	104
13	538	24	291	35	200	46	152	57	123	68	103
14	500	25	280	36	194	47	149	58	121	69	101
15	466	26	269	37	189	48	146	59	119	70	100
16	437	27	259	38	184	49	143	60	117	71	99
17	411	28	250	39	179	50	140	61	115	72	97
18	388	29	241	40	175	51	137	62	113	73	96
19	368	30	233	41	170	52	135	63	111	74	95
20	350	31	225	42	166	53	132	64	109	75	93
21	333	32	218	43	162	54	130	65	108	76	92
22	318	33	212	44	159	55	127	66	106	77	91

### Typical Percentage of Pellets in a 30-Inch Circle at 40 Yards (Pattern) for Various Choke Sizes

(Choke is a Constriction at the Muzzle of a Shotgun Barrel)

Full Choke—70%

Improved Cylinder—50%

Improved Modified Choke—65 to 70%

True Cylinder—40%

Modified Choke—55%

## Ballistic Data

The velocity and pressure obtained with the specific combinations of shell, wad, primer, bullet or shot weight, powder, and powder weight provided in this booklet were obtained in a laboratory, where considerable effort is made to control the load and test conditions. Velocity was measured with a chronograph (electric stopwatch). Pressure was measured either by compressing copper cylinders, or electronically, by use of a piezoelectric transducer.

Guns are designed to take a considerable amount of internal pressure, but if this is exceeded, they burst violently. Be alert to signs of excess pressure, such as heavy recoil, flattened primers, or blown primers. Don't make changes in the suggested loads.

Tone variations (shaded areas) used in the reloading tables are for ease of reading and do not represent preferred loads.

Each shotshell table lists DRAM EQUIVALENT in the first column. This number is not used in any way during reloading. The quantity of powder to use is listed in GRAINS, which are a measure of weight, under each powder column.

Every reloader needs a good-quality scale for weighing each powder charge, or for checking the weight of powder thrown by volumetric loaders.

### Special Notes Regarding Components Other Than Powder

A. **Shotgun Shells.** Manufacturers may sell ammunition under different brand names that are identical for reloading purposes. Following are popular variations. When in doubt, consult the ammunition producer.

- Federal Hi Power Plastic same as Duck and Pheasant, Field, Game, and Dove and Squirrel or Top Gun.
- Federal Premium (Integral Base Wad)
- Remington-Peters. Same as Mohawk brand shells.
- Winchester AA-Type (Compression-Formed) same as AA Target, Upland and Super Double X.
- Winchester Polyformed Type (Reifenhauser Tube) same as Duck and Pheasant, Dove and Squirrel, and Sears Brand.

B. **Primers**

- CCI 109 and CCI 209 are ballistically identical and can be interchanged.
- CCI 209M (Magnum) is "hotter" and cannot be substituted for CCI 109 or 209. Use 209M only as listed.
- Rem. 209 is "hotter" and cannot be substituted for Rem. 97★ or Rem. 209P primer.
- Rem. 209P is interchangeable with Rem. 97★ primer.
- Federal 209A is "hotter" and cannot be substituted for Federal 209.

C. **Wads.** Card wads and fiber wads are used for certain slug and buckshot loads and a few light shotshell loads. **Do not interchange wads.**

D. **Shot.** Use only clean lead shot. **DO NOT USE STEEL SHOT IN SHOTSHELL LOADS LISTED IN THIS GUIDE.**

E. **Shot Buffers.** Do not add any buffers or fillers of any kind to shotshell loads listed in this Guide.

F. **Cards and Fillers.** For revolver, pistol, and rifle cartridge reloading, do not add any cards, kapok, or fillers of any kind to loads listed in this Guide.

### Black Powder

Black powder is entirely different from smokeless powder. NEVER substitute one for the other. Smokeless powders have much more energy than black powder. NEVER attempt to use smokeless powder in black powder guns or saluting cannon; they may blow up and cause serious personal injury (including death).

# 1996 Powder Bushing Charts

A reloading scale is *required* to check the nominal weight of a powder charge.

Powder bushings can vary in the charge weight they drop and could vary as much as several grains under certain conditions.

Powder density, moisture content, and loading technique can cause a variation from the bushing weights listed on the charts. Also, the loading machine vibration affects charge weights. A complete loading cycle should be completed to *assure* an average powder charge weight.

The information in these tables has been supplied by the reloading machine manufacturers and *is not a reloading recommendation* or a result of Alliant's testing.

## Lee Powder Bushing Chart (Units shown in grains)

Bushing #	.095	.100	.105	.110	.116	.122	.128	.134	.141	.148	.151*	.155	.163	.171	.180	.189	.198
Red Dot	11.0	11.6	12.2	12.8	13.5	14.2	14.8	15.5	16.4	17.2	17.5	18.0	18.9	19.8	20.9	21.9	23.0
Green Dot	12.3	13.0	13.6	14.3	15.1	15.8	16.6	17.4	18.3	19.2	19.6	20.1	21.2	22.2	23.4	24.5	25.7
Unique	14.3	15.0	15.8	16.5	17.4	18.3	19.2	20.1	21.2	22.2	22.7	23.3	24.5	25.7	27.0	28.4	29.7
Herco	13.9	14.6	15.3	16.1	16.9	17.8	18.7	19.6	20.6	21.6	22.0	22.6	23.8	25.0	26.3	27.6	28.9
Blue Dot	18.0	19.0	19.9	20.8	22.0	23.1	24.3	25.4	26.7	28.0	28.6	29.4	30.9	32.4	34.1	35.8	37.5
2400	21.0	22.1	23.2	24.3	25.6	27.0	28.3	29.6	31.2	32.7	33.4	34.3	36.0	37.8	39.8	41.8	43.8

\*NOTE: Only available with Lee Load-Fast.

## Hornady Powder Bushing Chart for 366 Auto and Apex 91 (Units shown in grains)

Grains	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44		
Red Dot	384	393	405	423	438	453	468	480	489	498	510	519																									
American Select								417	423	432	447	456	468	477	483																						
Green Dot	363	378	390	405	420	435	447	456	468	480	492	501	513	522	534	—	549	558																			
Unique	342	354	369	381	393	405	414	423	435	444	453	465	474	483	492	501	—	510																			
Herco	357	369	381	393	405	414	426	438	450	462	471	477	489	498	—	513	522	531	—	549	558	564	573	—	588	594											
Blue Dot										366	372	381	390	396	408	414	423	435	441	447	459	468	474	483	489	495	501	510	516	522	531	534	543	549	555	561	
2400	256	266	—	291	300	312	324	330	339																												

## Ponsness/Warren Powder Bushing Chart (Units shown in grains)

Bushing #	1A	2A	3A	A	B	C	C1	D	D1	E	E1	E2	F	F1	F2	G	G1	H	I	J	J1	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z	AA							
Bullseye										16.2	16.8	17.7	18.7	19.4																															
Red Dot										11.6	12.2	12.9	13.4	13.7	14.5	14.7	15.7	16.5	16.8	17.3	17.6	18.5	19.4	20.7	20.9	21.3	21.9	22.9																	
American Select																16.4	17.5	18.2	18.8	19.4	19.9	20.6	22.0																						
Green Dot																11.7	12.3	13.1	13.6	13.8	14.7	14.9	15.9	16.7	17.0	17.5	17.9	18.8	19.6	21.1	21.3	21.8	22.3	23.2	23.6	25.3	26.5								
Unique																12.6	14.2	14.8	15.6	16.5	17.2	17.5	18.7	19.0	20.2	21.2	21.7	22.3	22.7	24.0	25.0	26.8	27.1	27.6											
Herco																12.3	13.8	14.4	15.1	16.0	16.6	16.9	18.0	18.3	19.5	20.5	20.9	21.5	21.9	23.0	24.0	25.7	26.0	26.5	27.1	28.1	28.8	30.7	32.1	33.1	34.9	35.4	37.2		
Blue Dot																16.4	18.4	19.2	20.1	21.3	22.2	22.6	23.9	24.3	25.9	27.2	27.7	28.5	29.1	30.6	31.9	34.2	34.5	35.2	36.0	37.5	38.1	40.7	42.5	43.8	46.5	47.2	49.5	55.7	
2400	12.3	13.2	15.2	16.1	16.8	17.6	18.3	19.0	21.3	22.2	23.3	24.7	25.7	26.1	27.7	28.2	30.0	31.5	32.2	33.1	33.7	35.5	37.1	39.8	40.2	41.1	42.0	43.8	44.5	47.5	49.8														

## MEC Powder Bushing Chart (Units shown in grains)

Bushing #	10	11	12	12A	13	13A	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31						
Bullseye	8.6	9.1	9.6	10.1	10.6	11.2	11.7	12.3	12.9	13.5	14.1	14.8	15.4	16.1	16.8	17.5	18.2	18.9	19.6	20.4	21.2	21.9	22.8	23.7						
Red Dot	6.3	6.7	7.1	7.5	7.9	8.3	8.7	9.2	9.6	10.1	10.6	11.1	11.6	12.1	12.6	13.1	13.7	14.2	14.9	15.7	16.4	17.1	17.8	18.5						
American Select	6.9	7.3	7.7	8.2	8.6	9.1	9.6	10.1	10.6	11.1	11.7	12.2	12.8	13.3	13.9	14.5	15.1	15.7	16.4	17.0	17.7	18.3	19.0	19.7						
Green Dot	6.7	7.2	7.6	8.0	8.4	8.9	9.3	9.8	10.3	10.8	11.3	11.8	12.4	12.9	13.5	14.0	14.6	15.2	15.8	16.4	17.0	17.7	18.3	19.0						
Unique	7.5	7.9	8.4	8.9	9.4	9.9	10.4	10.9	11.4	12.0	12.6	13.1	13.7	14.5	15.1	15.8	16.4	17.1	17.7	18.4	19.1	19.8	20.5	21.1						
Herco	7.9	8.3	8.8	9.3	9.8	10.4	10.9	11.4	12.0	12.6	13.2	13.8	14.4	15.0	15.7	16.3	17.0	17.7	18.4	19.1	19.8	20.6	21.3	22.1						
Blue Dot	10.8	11.3	11.9	12.5	13.1	13.7	14.4	15.0	15.7	16.3	17.0	17.7	18.4	19.2	20.1	21.0	21.9	22.8	23.7	24.6	25.5	26.4	27.3	28.2						
2400	11.8	12.5	13.3	14.0	14.8	15.6	16.4	17.2	18.1	18.9	19.8	20.7	21.7	22.6	23.6	24.6	25.6	26.6	27.7	28.8	29.9	31.0	32.1	33.3						

## MEC Powder Bushing Chart continued (Units shown in grains)

Bushing #	32	33	34	35	36	37	38	38A	39	39A	40	40A	41	41A	42	42A	43	43A	44	44A	45	45A	46
Bullseye	24.6	25.5	26.4	27.3	28.2	29.1	30.1	31.0	31.9	32.8	33.7	34.7	35.7	36.9	38.1	39.4	40.7	42.0	43.3	44.6	46.0	47.4	48.8
Red Dot	19.2	19.9	20.6	21.3	21.9	22.7	23.3	24.1	24.7	25.2	25.9	26.6	27.3	27.9	28.4	29.3	29.9	30.8	31.5	32.1	32.7	33.4	34.1
American Select	20.4	21.1	21.8	22.6	23.3	24.1	24.9	25.7	26.5	27.3	28.1	28.9	29.8	30.7	31.5	32.4	33.3	34.2	35.2	36.4	37.0	38.0	39.0
Green Dot	19.6	20.3	21.0	21.7	22.4	23.2	23.9	24.7	25.4	26.2	27.0	27.8	28.6	29.4	30.3	31.1	32.0	32.8	33.7	34.6	35.5	36.4	37.4
Unique	21.7	22.5	23.2	24.0	24.8	25.6	26.5	27.3	28.2	29.0	29.9	30.8	31.7	32.6	33.5	34.5	35.4	36.4	37.4	38.4	39.4	40.4	41.4
Herco	22.9	23.7	24.5	25.3	26.2	27.0	27.9	28.8	29.7	30.6	31.5	32.4	33.4	34.3	35.3	36.3	37.3</						

# S A A M I

SPORTING ARMS AND AMMUNITION MANUFACTURERS' INSTITUTE, INC.

Flintlock Ridge Office Center, 11 Mile Hill Road, Newtown, CT 06470-2359

## Properties and Storage of Smokeless Powder

Ammunition handloading has become increasingly popular in recent years. This information discusses properties of smokeless powder and offers recommendations for its storage.

This information is intended to increase the knowledge of all concerned individuals and groups regarding smokeless powder. The statements and recommendations made are not intended to supersede local, state, or Federal regulations. Proper authorities should be consulted on regulations for storage and use of smokeless powder in each specific community. A leaflet entitled "Sporting Ammunition Primers: Properties, Handling, & Storage for Hand Loading" supplements this information on smokeless powder.

### Properties of Smokeless Powder

Smokeless powders, or propellants, are essentially mixtures of chemicals designed to burn under controlled conditions at the proper rate to propel a projectile from a gun.

Smokeless powders are made in three forms:

1. Thin, circular flakes or wafers
2. Small cylinders
3. Small spheres

Single-base smokeless powders derive their main source of energy from nitrocellulose.

The energy released from double-base smokeless powders is derived from both nitrocellulose and nitroglycerin.

All smokeless powders are extremely flammable; by design, they are intended to burn rapidly and vigorously when ignited.

Oxygen from the air is not necessary for the combustion of smokeless powders since they contain sufficient built-in oxygen to burn completely, even in an enclosed space such as the chamber of a firearm.

In effect, ignition occurs when the powder granules are heated above their ignition temperature. This can occur by exposing powder to:

1. A flame such as a match or primer flash.
- 2 An electrical spark or the sparks from welding, grinding, etc.
3. Heat from an electric hot plate or a fire directed against or near a closed container even if the powder itself is not exposed to the flame.

When smokeless powder burns, a great deal of gas at high temperature is formed. If the powder is confined, this gas will create pressure in the surrounding structure. The rate of gas generation is such, however, that the pressure can be kept at a low level if sufficient space is available or if the gas can escape.

In this respect smokeless powder differs from blasting agents or high explosives such as dynamite or blasting gelatin, although smokeless powder may contain chemical ingredients common to some of these products.

High explosives such as dynamite are made to detonate, that is, to change from solid state to gaseous state with evolution of intense heat at such a rapid rate that shock waves are propagated through any medium in contact with them. Such shock waves exert pressure on anything they contact, and, as a matter of practical consideration, it is almost impossible to satisfactorily vent away from the effects of a detonation involving any appreciable quantity of dynamite.

Smokeless powder differs considerably in its burning characteristics from common "black powder."

Black powder burns essentially at the same rate out in the open (unconfined) as when in a gun.

When ignited in an unconfined state, smokeless powder burns inefficiently with an orange-colored flame. It produces a considerable amount of light brown noxious smelling smoke. It leaves a residue of ash and partially burned powder. The flame is hot enough to cause severe burns.

The opposite is true when it burns under pressure as in a cartridge fired in a gun. Then it produces very little smoke, a small glow, and leaves very little or no residue. The burning rate of smokeless powder increases with increased pressure.

If burning smokeless powder is confined, gas pressure will rise and eventually can cause the container to burst. Under such circumstances, the bursting of a strong container creates effects similar to an explosion.

For this reason, the Department of Transportation (formerly Interstate Commerce Commission) sets specifications for shipping containers for propellants and requires tests of loaded containers — under actual fire conditions — before approving them for use.

When smokeless powder in D.O.T. approved containers is ignited during such tests, container seams split open or lids pop off — to release gases and powder from confinement at low pressure.

### How to Check Smokeless Powder for Deterioration

Although modern smokeless powders are basically free from deterioration under proper storage conditions, safe practices require a recognition of the signs of deterioration and its possible effects.

Powder deterioration can be checked by opening the cap on the container and smelling the contents. Powder undergoing deterioration has an irritating acidic odor. (Don't confuse this with common solvent odors such as alcohol, ether and acetone.)

Check to make certain that powder is not exposed to extreme heat as this may cause deterioration. Such exposure produces an acidity which accelerates further reaction and has been known, because of the heat generated by the reaction, to cause spontaneous combustion.

Never salvage powder from old cartridges and do not attempt to blend salvaged powder with new powder. Don't accumulate old powder stocks.

The best way to dispose of deteriorated smokeless powder is to burn it out in the open at an isolated location in small shallow piles (not over 1" deep). The quantity burned in any one pile should never exceed one pound. Use an ignition train of slow burning combustible material so that the person may retreat to a safe distance before powder is ignited.

### Considerations for Storage of Smokeless Powder

Smokeless powder is intended to function by burning, so it must be protected against accidental exposure to flame, sparks or high temperatures.

For these reasons, it is desirable that storage enclosures be made of insulating materials to protect the powder from external heat sources.



Once smokeless powder begins to burn, it will normally continue to burn (and generate gas pressure) until it is consumed.

D.O.T. approved containers are constructed to open up at low internal pressures to avoid the effects normally produced by the rupture or bursting of a strong container.

Storage enclosures for smokeless powder should be constructed in a similar manner:

1. Of fire-resistant and heat-insulating materials to protect contents from external heat.
2. Sufficiently large to satisfactorily vent the gaseous products of combustion, which would result if the quantity of smokeless powder within the enclosure accidentally ignited.

If a small, tightly enclosed storage enclosure is loaded to capacity with containers of smokeless powder, the walls of the enclosure will expand or move outwards to release the gas pressure — if the powder in storage is accidentally ignited.

Under such conditions, the effects of the release of gas pressure are similar or identical to the effects produced by an explosion.

Hence only the smallest practical quantities of smokeless powder should be kept in storage, and then in strict compliance with all applicable regulations and recommendations of the National Fire Protection Association (reprinted at end of leaflet).

## Recommendations for Storage of Smokeless Powder

**STORE IN A COOL, DRY PLACE.** Be sure the storage area selected is free from any possible sources of excess heat and is isolated from open flame, furnaces, hot water heaters, etc. Do not store smokeless powder where it will be exposed to the sun's rays. Avoid storage in areas where mechanical or electrical equipment is in operation. Restrict from the storage areas heat or sparks which may result from improper, defective or overloaded electrical circuits.

**DO NOT STORE SMOKELESS POWDER IN THE SAME AREA WITH SOLVENTS, FLAMMABLE GASES, OR HIGHLY COMBUSTIBLE MATERIALS.**

**STORE ONLY IN DEPARTMENT OF TRANSPORTATION APPROVED CONTAINERS.**

Do not transfer the powder from an approved container into one which is not approved.

**DO NOT SMOKE IN AREAS WHERE POWDER IS STORED OR USED. PLACE APPROPRIATE "NO SMOKING" SIGNS IN THESE AREAS.**

**DO NOT SUBJECT THE STORAGE CABINETS TO CLOSE CONFINEMENT.**

**STORAGE CABINETS SHOULD BE CONSTRUCTED OF INSULATING MATERIALS AND WITH A WEAK WALL, SEAMS OR JOINTS TO PROVIDE AN EASY MEANS OF SELF-VENTING.**

**DO NOT KEEP OLD OR SALVAGED POWDERS.** Check old powders for deterioration regularly. Destroy deteriorated powders immediately.

**OBEY ALL REGULATIONS REGARDING QUANTITY AND METHODS OF STORING.** Do not store all your powders in one place. If you can, maintain separate storage locations. Many small containers are safer than one or more large containers.

**KEEP YOUR STORAGE AND USE AREA CLEAN.** Clean up spilled powder promptly. Make sure the surrounding area is free of trash or other readily combustible materials.

## 10-3 Smokeless Propellants.

**10-3.1** Quantities of smokeless propellants not exceeding 25 lb (11.3 kg) in shipping containers approved by the U.S. Department of Transportation, may be transported in a private vehicle.

**10-3.2** Quantities of smokeless propellants exceeding 25 lb (11.3 kg) but not exceeding 50 lb (22.7 kg), transported in a private vehicle, shall be transported in a portable magazine having wood walls of at least 1-in. (25.4-mm) nominal thickness.

**10-3.3** Transportation of more than 50 lb (22.7 kg) of smokeless propellants in a private vehicle is prohibited.

**10-3.4** Commercial shipments of smokeless propellants in quantities not exceeding 100 lb (45.4 kg) are classified for transportation purposes as flammable solids when packaged according to U.S. Department of Transportation Hazardous Materials Regulations (Title 49, Code of Federal Regulations, Part 173.197a), and shall be transported accordingly.

**10-3.5** Commercial shipments of smokeless propellants exceeding 100 lb (45.4 kg) or not packaged in accordance with the regulations cited in 10-3.4 shall be transported according to U.S. Department of Transportation regulations for Class B propellant explosives.

**10-3.6** Smokeless propellants shall be stored in shipping containers specified by U.S. Department of Transportation Hazardous Materials Regulations.

**10-3.7** Smokeless propellants intended for personal use in quantities not exceeding 20 lb (9.1 kg) may be stored in original containers in residences. Quantities exceeding 20 lb (9.1 kg), but not exceeding 50 lb (22.7 kg), may be stored in residences if kept in a wooden box or cabinet having walls of at least 1-in. (25.4-mm) nominal thickness.

**10-3.8** Not more than 20 lb (9.1 kg) of smokeless propellants, in containers of 1-lb (0.45-kg) maximum capacity, shall be displayed in commercial establishments.

**10-3.9** Commercial stocks of smokeless propellants shall be stored as follows:

(a) Quantities exceeding 20 lb (9.1 kg), but not exceeding 100 lb (45.4 kg), shall be stored in portable wooden boxes having walls of at least 1-in. (25.4 mm) thickness.

(b) Quantities exceeding 100 lb (45.4 kg), but not exceeding 800 lb (363 kg), shall be stored in nonportable storage cabinets having walls of at least 1-in. (25.4-mm) thickness. Not more than 400 lb (181 kg) may be stored in any one cabinet and cabinets shall be separated by a distance of at least 25 ft. (7.63 m) or by a fire partition having a fire resistance of at least 1 hour.

(c) Quantities exceeding 800 lb (363 kg), but not exceeding 5,000 lb (2268 kg), may be stored in a building if the following requirements are met:

1. The warehouse or storage room shall not be accessible to unauthorized personnel.

2. Smokeless propellant shall be stored in nonportable storage cabinets having wood walls at least 1 in. (25.4-mm) thick and having shelves with no more than 3 ft (0.92 m) separation between shelves.

3. No more than 400 lb (181 kg) shall be stored in any one cabinet.

4. Cabinets shall be located against walls of the storage room or warehouse with at least 40 ft (12.2 m) between cabinets.

5. Separation between cabinets may be reduced to 20 ft. (6.1 m) if barricades twice the height of the cabinets are attached to the wall, midway between each cabinet. The barricades shall extend at least 10 ft (3 m) outward, shall be firmly attached to the wall, and shall be constructed of  $\frac{1}{4}$ -in. (6.4-mm) boiler plate, 2-in. (51-mm) thick wood, brick, or concrete block.

6. Smokeless propellant shall be separated from materials classified by the U.S. Department of Transportation as flammable liquids, flammable solids, and oxidizing materials by a distance of 25 ft (7.63 m) or by a fire partition having a fire resistance of at least 1 hour.

7. The building shall be protected by an automatic sprinkler system installed according to NFPA 13, Standard for the Installation of Sprinkler Systems.

(d) Smokeless propellants not stored according to (a), (b) and (c) above shall be stored in a Type 4 magazine constructed and located according to Chapter 6.

*Reprinted with permission from NFPA495-85, Standard for the Manufacture, Transportation, Storage and Use of Explosive Materials, © 1985, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the NFPA on the referenced subject, which is represented by the Standard in its entirety.*



## 10-Gauge, 3½-in. Federal Plastic with Paper Wad Base

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Green Dot Grains	Unique Grains	Herco Grains	Blue Dot Grains
					Approx. psi	Approx. psi	Approx. psi	Approx. psi	Approx. psi
4	1¼	1,265	CCI 209M Win. 209	Rem. SP10 (see Note 6) Rem. SP10 (see Note 6)		29.5 29.0	8,300 8,800		
4½	1⅝	1,285	CCI 209M Win. 209	Rem. SP10 (see Note 4) Rem. SP10 (see Note 4)				36.0	10,300
4½	1⅞	1,270	CCI 209M Win. 209	Rem. SP10 (see Note 3) Rem. SP10 (see Note 3)					45.0 45.5
4½	2	1,210	CCI 209M Win. 209	Rem. SP10 (see Note 2) Rem. SP10 (see Note 2)					9,900 8,300
4½	2¼	1,165	CCI 209M Win. 209	Rem. SP10 (see Note 1) Rem. SP10 (see Note 1)					43.5 44.0

## 10-Gauge, 3½-in. Remington SP Shell

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Green Dot Grains	Unique Grains	Herco Grains	Blue Dot Grains
					Approx. psi	Approx. psi	Approx. psi	Approx. psi	Approx. psi
4	1¼	1,265	CCI 209M Win. 209	Rem. SP10 (see Note 6) Rem. SP10 (see Note 6)		28.5 29.0	8,800 8,800	31.0 31.0	7,500 7,600
4½	1⅝	1,285	CCI 209M Win. 209	Rem. SP10 (see Note 4) Rem. SP10 (see Note 4)					43.5 44.0
4½	1⅞	1,270	CCI 209M Win. 209	Rem. SP10 (see Note 3) Rem. SP10 (see Note 3)					9,800 9,100
4½	2	1,210	CCI 209M Win. 209	Rem. SP10 (see Note 2) Rem. SP10 (see Note 2)					10,400 10,100
4½	2¼	1,165	CCI 209M Win. 209	Rem. SP10 Rem. SP10					10,400 10,500

## 10-Gauge, 3½-in. Winchester Polyformed with Plastic Base Wad

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Green Dot Grains	Unique Grains	Herco Grains	Blue Dot Grains
					Approx. psi	Approx. psi	Approx. psi	Approx. psi	Approx. psi
4	1¼	1,265	Win. 209 CCI 209M	Rem. SP10 (see Note 5) Rem. SP10 (see Note 5)		28.5 28.0	8,600 8,500		
4½	1⅝	1,285	Win. 209 CCI 209M	Rem. SP10 (see Note 3) Rem. SP10 (see Note 3)				35.5	10,400
4½	1⅞	1,270	Win. 209 CCI 209M	Rem. SP10 (see Note 2) Rem. SP10 (see Note 2)					10,200 9,800
4½	2	1,210	Win. 209 CCI 209M	Rem. SP10 (see Note 1) Rem. SP10 (see Note 1)					9,500 9,400
4½	2¼	1,165	Win. 209 CCI 209M	Rem. SP10 Rem. SP10					10,500 10,500

- NOTES:**
1. Add one 20-gauge, 0.135-in. thick card wad to the inside bottom of the shot cup.
  2. Add two 20-gauge, 0.135-in. thick card wads to the inside bottom of the shot cup.
  3. Add three 20-gauge, 0.135-in. thick card wads to the inside bottom of the shot cup.
  4. Add four 20-gauge, 0.135-in. thick card wads to the inside bottom of the shot cup.
  5. Add five 20-gauge, 0.135-in. thick card wads to the inside bottom of the shot cup.
  6. Add six 20-gauge, 0.135-in. thick card wads to the inside bottom of the shot cup.



## 12-Gauge, 3½-in. Federal Unibody Plastic Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Red Dot Approx. psi	Green Dot Grains	Green Dot Approx. psi	Unique Grains	Unique Approx. psi	Herco Grains	Herco Approx. psi	Blue Dot Grains	Blue Dot Approx. psi
4	1 1/8	1,200	CCI 209M	Fed. 12SO (see Note 1) Win. WAA12SL (see Note 1) Rem. R12L (see Note 2) Win. 209 Fed. 12SO (see Note 1)									41.0	9,100
													41.0	8,900
													40.5	9,600
													40.0	9,000
4 1/4	1 1/8	1,255	CCI 209M	Fed. 12SO Win. WAA12SL Rem. R12L (see Note 1) Win. 209 Fed. 12SO									43.0	9,800
													43.0	9,500
													42.5	10,100
													42.5	10,100
4 1/4	2	1,220	CCI 209M	Fed. 12SO Win. WAA12SL Rem. R12L Win. 209 Fed. 12SO									42.5	10,000
													42.5	9,800
													42.0	10,000
													41.0	9,900
4 1/4	2 1/4	1,150	CCI 209M	Fed. 12S4 Win. WAA12F114 Rem. SP12 Win. 209 Fed. 12S4									38.5	11,100
													38.5	11,100
													39.5	11,200
													38.0	10,900

## 12-Gauge, 3½-in. Remington Plastic SP

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Red Dot Approx. psi	Green Dot Grains	Green Dot Approx. psi	Unique Grains	Unique Approx. psi	Herco Grains	Herco Approx. psi	Blue Dot Grains	Blue Dot Approx. psi
4	1 1/8	1,200	CCI 209M	Rem. R12L (see Note 1) Fed. 12SO (see Note 1) Win. WAA12SL (see Note 1) Win. 209 Rem. R12L (see Note 1)									38.0	10,300
													38.0	10,100
													38.0	10,000
													37.5	10,500
4 1/4	1 1/8	1,255	CCI 209M	Rem. R12L (see Note 1) Fed. 12SO (see Note 1) Win. WAA12SL (see Note 1) Win. 209 Rem. R12L (see Note 1)									39.0	10,900
													39.0	10,600
													39.0	10,400
													38.5	11,000
4 1/4	2	1,220	CCI 209M	Rem. R12L Fed. 12SO Win. WAA12SL Win. 209 Rem. R12L									39.5	11,100
													39.5	10,800
													39.0	10,700
													39.0	11,200
4 1/4	2 1/4	1,150	CCI 209M	Rem. SP12 Fed. 12S4 Win. 209 Rem. SP12									38.0	11,100
													37.0	11,100
													38.0	11,500

## 12-Gauge, 3½-in. Winchester Plastic Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Red Dot Approx. psi	Green Dot Grains	Green Dot Approx. psi	Unique Grains	Unique Approx. psi	Herco Grains	Herco Approx. psi	Blue Dot Grains	Blue Dot Approx. psi
4	1 1/8	1,200	Win 209	Win. WAA12SL Fed. 12SO Rem. R12L (see Note 1)									38.5	10,000
			CCI 209M	Win. WAA12SL									38.5	10,600
													38.5	10,300
													38.0	10,100
4 1/4	1 1/8	1,255	Win. 209	Win. WAA12SL Fed. 12SO Rem. R12L (see Note 1)									40.0	10,800
			CCI 209M	Win. WAA12SL									40.5	10,700
													40.0	10,700
													39.5	10,500
4 1/4	2	1,220	Win. 209	Win. WAA12SL Fed. 12SO Rem. R12L									40.0	11,200
			CCI 209M	Win. WAA12SL									40.5	11,000
													39.0	10,600
													39.0	11,200
4 1/4	2 1/4	1,150	Win. 209	Rem. SP12									37.0	11,200

NOTES: 1. Add one 20-gauge, 0.135-in. thick card wad to the inside bottom of the shot cup.  
2. Add two 20-gauge, 0.135-in. thick card wads to the inside bottom of the shot cup.

# 12-Gauge, 2¾-in. Federal Paper Target Shells



Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	American Select Grains	Green Dot Grains	Unique Grains	Herco Grains	Blue Dot Grains		
					Approx. psi	Approx. psi	Approx. psi	Approx. psi	Approx. psi	Approx. psi		
3½	1	1,290	Fed. 209A	Rem. R12L	20.0	9,300		21.5	8,800			
				Fed. 12S3	20.5	9,000		23.5	9,400			
				Fed. 12SO	20.5	10,400		22.5	9,200			
				CCI 209M	Fed. 12S3	21.0	8,700	23.0	7,800			
2¾	1⅓	1,145	Fed 209A	Fed. 12C1	18.0	8,500		19.0	8,200			
				Fed. 12S3	18.0	8,700	19.0	8,200	19.5	7,400		
				Rem. R12L	18.5	9,300		19.0	8,000			
				Rem. RXP12	18.0	8,900		18.5	8,100			
				Win. WAA12 (White)	18.0	8,600	19.0	8,400	18.5	8,000		
				Fiocchi FTW1	18.5	9,000		20.0	7,900			
				Red PC	18.0	8,300		20.0	7,600			
				Lage Uniwad	18.0	8,500		19.0	8,400			
				Hornady Versalite	18.0	8,800	19.0	7,900	19.5	6,900		
				Windjammer	18.5	8,200	19.5	7,100	20.5	6,600		
				Rem. Fig. 8			19.0	7,600				
				Win. WT12 (Orange)			19.0	8,100				
				Claybuster			19.0	7,600				
			Rem. 209P	Fed. 12C1	18.5	8,300		20.0	7,000			
				Fed. 12S3		19.0	8,500					
3	1⅓	1,200	Fed. 209A	Win. 209	Fed. 12C1	18.5	8,600	19.5	7,500			
				Fed. 12S3		19.0	8,900					
				CCI 109	Fed. 12C1	18.5	8,500	19.0	7,800			
				CCI 209M	Fed. 12C1	18.5	7,900	20.0	7,400			
				CCI 209SC	Fed. 12S3		19.0	8,600				
				Fed. 12C1	19.0	9,300		20.0	8,600	22.0	8,200	
				Fed. 12S3	19.0	9,800	20.5	10,400	21.0	7,800	22.0	7,200
				Rem. R12L	19.5	9,500		20.0	8,600	22.0	7,800	
				Rem. R12H	19.0	9,200		19.5	8,800			
				Rem. RXP12	19.0	9,900		20.0	8,600	21.0	8,000	
				Win. WAA12 (White)	19.0	10,500	20.5	10,400	19.5	9,000	21.0	8,600
				Fiocchi FTW1	19.5	9,500		21.0	8,200			
				Red PC	19.0	10,300		21.0	8,800	22.5	8,400	
				Lage Uniwad	18.5	9,400		20.0	8,800	22.0	8,000	
3¼	1⅓	1,255	Fed. 209A	Hornady Versalite	19.0	8,900	20.0	10,100	21.0	8,300	22.0	7,900
				Windjammer	19.0	8,700	20.0	9,100	22.0	7,700	23.5	7,600
				Rem. Fig. 8			20.0	9,800				
				Win. WT12 (Orange)			20.5	10,200				
				Claybuster			20.5	9,300				
				Rem. 209P	Fed. 12C1	20.0	9,200		22.0	7,800	24.0	7,000
				Fed. 12S3		21.0	9,700					
				Win. 209	Fed. 12C1	19.5	9,800		21.0	8,100	23.0	7,600
				Fed. 12S3		20.5	9,700					
				CCI 109	Fed. 12C1	19.0	9,200		20.5	8,200	22.0	7,500
				CCI 209M	Fed. 12C1	20.0	8,700		21.5	7,700	24.0	7,200
				CCI 209SC	Fed. 12S3		20.5	9,800				
3½	1⅓	1,310	Fed 209A	Fed. 12C1	21.0	10,200		21.5	7,900	22.5	8,900	
				Fed. 12S3	21.0	9,400		23.0	9,100	23.0	8,300	
				Rem. R12H				21.5	9,900	22.5	9,000	
				Rem. RXP12	21.0	10,000		21.5	9,300	22.0	8,500	
				Win. WAA12 (White)				21.5	10,500	22.0	9,500	
				Red PC	20.5	10,700		22.5	9,600	24.5	8,500	
				Hornady Versalite	20.5	9,900		22.5	8,500	23.0	8,700	
Rem. 209P	Fed. 12C1	Win. 209	CCI 209M	Fed. 12C1	21.5	10,700		23.5	7,500	26.0	7,500	
				Fed. 12C1	21.0	10,300		22.5	9,000	24.5	8,300	
				Fed. 12C1	21.0	10,500		22.5	8,500	24.5	8,400	
				Fed. 12C1								
				Fed. 12C1								
2¾	1⅓	1,255	Fed. 209A	Fed. 12C1				24.5	9,900	26.5	9,000	
				Fed. 12S3					26.5	9,700		
				Rem. RXP12				24.5	9,800	26.5	8,600	
				Win. WAA12 (White)				24.5	9,700	26.5	9,100	
Rem. 209P	Fed. 12C1	Win. 209	CCI 209M	Fed. 12C1				25.5	9,300	27.5	8,300	
				Fed. 12C1						26.5	9,200	
				Fed. 12C1						26.5	9,400	

continued on next page

## 12-Gauge, 2¾-in. Federal Paper Target Shells (continued)

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	American Select Grains	Green Dot Grains	Unique Grains	Herco Grains	Blue Dot Grains
					Approx. psi	Approx. psi	Approx. psi	Approx. psi	Approx. psi	Approx. psi
3¼	1¼	1,220	Fed. 209A	Fed. 12C1			21.0	10,600	22.5	9,500
				Fed. 12S4			23.0	10,500	24.0	9,800
				Rem. SP12			21.0	9,600	22.0	9,600
				Win. WAA12 (White)			21.0	10,500	22.0	10,000
				Win. WAA12F114			23.0	9,900	23.5	9,500
				Hornady Versalite			23.0	9,600	23.0	8,800
				Rem. 209P	Fed. 12S4		23.0	9,900	25.5	9,100
				Win. 209	Fed. 12S4				24.5	10,600
				CCI 209M	Fed. 12S4		23.0	10,500	25.5	9,700
3¾	1¼	1,330	Fed. 209A	Fed. 12S4					29.0	9,400
				Rem. RP12					29.5	9,300
				Rem. SP12					29.5	9,200
				Win. WAA12F114						
				Win. 209	Fed. 12S4					
3½	1¾	1,240	Fed. 209A	CCI 209M	Fed. 12S4		28.0	10,700	29.5	9,900
				Rem. 209P	Rem. SP12					
				Win. 209	Rem. SP12					
				CCI 209M	Rem. SP12					
3¾	1¾	1,295	Fed. 209A	Rem. SP12						34.0
				Win. WAA12F114						9,900
				Rem. 209P	Rem. SP12					33.0
				Win. 209	Rem. SP12					10,200
4	1¾	1,350	Fed. 209A	CCI 209M	Rem. SP12					
				Rem. RP12						
				Fed. 209A	Rem. SP12					
				Activ T42						
3¼	1½	1,150	Fed. 209A	Rem. RP12					25.0	10,200
				Win. 209	Activ T42					
				Rem. 209P	Activ T42					
				CCI 209M	Activ T42					
				Fio. 616	Activ T42					
3½	1½	1,205	Fed. 209A	Rem. RP12						
				Rem. 209P	Rem. RP12					
				Win. 209	Rem. RP12					
				CCI 209M	Rem. RP12					

PC: Pattern Control

# 12-Gauge, 2¾-in. Federal Gold Medal Plastic Target Shells



Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	American Select Grains	Green Dot Grains	Unique Grains	Herco Grains	Blue Dot Grains
					Approx. psi	Approx. psi	Approx. psi	Approx. psi	Approx. psi	Approx. psi
—	7/8	1,200	Fed. 209A	Fed. 12SO	17.5	7,600				
				Rem. TGT 12	17.5*	7,100				
				Win. WAA12SL	17.0*	7,300				
				Purple PC	17.0*	6,400				
—	7/8	1,250	Fed. 209A	Fed. 12SO	19.0	7,900				
				Rem. TGT 12	18.5*	7,800				
				Win. WAA12SL	18.0*	8,000				
				Purple PC	18.5*	7,300				
—	7/8	1,300	Fed. 209A	Fed. 12SO	19.5	8,400	21.0	7,300		
				Rem. TGT 12	19.5*	8,500	21.0	7,400		
				Win. WAA12SL	19.0*	8,400				
				Purple PC	19.5*	7,900	21.5	6,900		
2½	1	1,200	Fed. 209A	Claybuster			21.5	6,900		
				Fed. 12SO	18.0	8,300	19.5	7,100		
				Rem. TGT 12	18.0	7,900	19.5	7,500		
				Win. WAA12SL	18.0	8,700	19.5	7,200		
				Purple PC	18.0*	7,400				
3	1	1,255	Fed. 209A	Claybuster			20.0	7,300		
				Fed. 12SO	19.5	9,300	21.0	7,700		
				Rem. TGT 12	19.0	8,700	20.5	8,100		
				Win. WAA12SL	18.5	9,100	21.0	8,400		
				Purple PC	19.5*	8,700				
3¼	1	1,290	Fed. 209A	Claybuster			21.0	7,600		
				Fed. 12SO	20.5	10,300	22.0	8,500		
				Rem. TGT 12	20.0	9,100	21.5	8,800		
				Win. WAA12SL	20.0	10,300	21.5	8,800		
				Purple PC	20.5	9,300				
2½ Extra Lite	1⅓	1,090	Fed. 209A	Claybuster			21.5	8,000		
				Fed. 12S3	17.0	8,400	17.5	7,100		
				Rem. Fig. 8	17.0	7,700	17.5*	8,000		
				Win. WAA12SL	17.0	8,100				
				Win. WAA12 (White)	16.5*	8,500	17.5*	7,400		
				Win. WT12 (Orange)			18.0*	7,700		
				Fiocchi FTW1	16.5*	8,500				
				Hornady Versalite	17.0*	8,600	17.0*	8,100		
				Windjammer	17.5	7,600				
				Claybuster			17.5	7,100		
2¾	1⅓	1,145	Fed. 209A	Win. 209	17.0	8,400				
				CCI 209M	17.0	8,300				
				Fio. 616	17.5	8,200				
				Fed. 12S3						
				Rem. Fig. 8	18.0	8,800	19.0	7,600	19.5	8,100
				Rem. RXP12	18.0	8,800	19.0	9,000	19.0	7,700
				Win. WAA12SL	18.0	9,400			19.0	8,000
				Win. WAA12 (White)	17.5*	9,400	19.0*	9,600	19.0*	8,200
				Win. WT12 (Orange)	18.5*	9,300	19.0*	9,300	20.0*	8,400
				Fiocchi FTW1	18.0*	9,600			19.5	8,600
2½	1⅓	1,145	Fed. 209A	Hornady Versalite	18.0*	9,400	18.5*	9,600	19.0	8,000
				Windjammer	18.5	8,200	19.0	8,700	19.5	7,700
				Claybuster			19.0	8,200		
				Rem. 209P	18.5	8,200	19.5	7,800	20.5	6,800
				Win. 209	17.5	9,600	19.5	8,100	19.5	8,000
				CCI 209	18.0	8,200			19.0	7,800
				CCI 209M	18.0	8,600			19.5	7,500
2½	1⅓	1,145	Fed. 209A	CCI 209SC	19.0	9,800	18.5	8,500	20.5	8,600
				Win. WAA12 (White)	18.5	10,200			20.5	9,000
				Rem. Fig. 8	19.5	9,500			21.0	8,300

continued on next page

PC: Pattern Control

NOTES: \*For each asterisk (\*), add one 20-gauge, 0.135-in. thick card wad to the inside bottom of the shot cup.

Auto-loading shotguns may not function with loads having pressures less than 7,000 psi. It is important to have tight crimps to prevent load efficiencies (pressures) from dropping. The efficiency may also drop when these loads are fired at low temperatures.

Nitro cards may be obtained from: Ballistic Products, Inc., 20015 75th Avenue North, Corcoran, MN 55340. Phone: (612) 494-9237.

## 12-Gauge, 2¾-in. Federal Gold Medal Plastic Target Shells (continued)

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Approx. psi	American Select Grains	Approx. psi	Green Dot Grains	Approx. psi	Unique Grains	Approx. psi	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi
3	1⅓	1,200	Fed. 209A	Fed. 12S3 Rem. Fig. 8 Rem. RXP12 Win. WAA12SL Win. WAA12 (White) Fiocchi FTW1 Hornady Versalite Windjammer Win. WT12 (Orange) Claybuster Rem. 209P	19.5 19.0 19.0 19.0 19.0* 19.0 19.0 19.5 20.0* 20.5	10,000 9,500 9,900 10,000 10,400 10,500 10,100 9,600 10,400 9,600	20.5 20.0* 20.5* 20.0 20.5* 20.5 20.0* 20.5* 20.5* 20.5	9,200 10,300 8,800 8,800 9,400 9,300 10,900 9,800 10,400 9,600	20.0 20.0 20.5 20.5 20.0 20.5 20.5 21.0 21.5*	9,000 8,600 8,800 8,800 9,200 9,300 9,400 8,200 8,800 8,800	22.5 22.5 22.5 22.5 22.5 22.5 22.5 22.5 23.5*	7,300 7,300 7,800 8,100 8,100 8,000 8,000 6,900 8,300				
			Win. 209	Fed. 12S3	19.5	9,300	21.5	9,000	21.5	7,900	24.0	6,900				
			CCI 209	Fed. 12S3	19.0	10,500	20.5	9,900	20.5	9,000	23.0	8,600				
			CCI 209M	Fed. 12S3	20.0	9,800			22.0	9,200	24.0	8,300				
			CCI 209SC	Fed. 12S3	19.0	8,900			21.0	8,600	23.5	8,000				
				Win. WAA12 (White)	20.5	10,700	20.5	10,000	22.5	8,900						
				Rem. Fig. 8	20.0	10,500	20.0	10,200	22.0	9,200						
					21.0	9,800			23.0	9,200						
Heavy	1⅓	1,250	Fed. 209A	Fed. 12S3 Rem. Fig. 8 Rem. RXP12 Win. WAA12 (White) Hornady Versalite Windjammer Claybuster Rem. 209P	20.0 20.0 20.0 20.0 20.0 20.5	9,500 10,100 10,700 9,500	22.0 21.0 21.0 21.5*	10,100 10,900 10,700 10,600	21.5 21.5 21.5 22.5	9,500 9,700 9,400 8,400	23.5 23.5 23.0 24.0	8,100 7,800 8,400 8,300	26.0	8,000		
			Win. 209	Fed. 12S3					23.0	8,800	25.0	7,600				
			CCI 209M	Fed. 12S3					22.5	10,500	24.0	9,800				
3½	1⅓	1,310	Fed. 209A	Rem. RXP12 Win. WAA12 (White) Hornady Versalite Windjammer					22.5	9,800	24.0	9,100				
3¼	1¼	1,220	Fed. 209A	Fed. 12S4 Rem. SP12 Win. WAA12F114 Rem. 209P							24.0	10,500	25.0	10,200		
			Win. 209	Fed. 12S4							24.0	10,400	26.0	9,700		
			CCI 209M	Fed. 12S4							24.0	10,600	25.0	10,100		
3½	1¼	1,275	Fed. 209A	Fed. 12S4 Rem. SP12 Win. WAA12F114 Rem. 209P									27.0	10,100	34.0	8,900
			Win. 209	Fed. 12S4									27.0	10,500		
			CCI 209M	Fed. 12S4									27.5	9,200		
3¾	1¼	1,330	Fed. 209A	Rem. SP12 Win. 209 CCI 209M											35.0	8,700
			Rem. 209P	Fed. 12S4											35.0	9,100
3½	1¾	1,240	Fed. 209A	Rem. RP12 Win. WAA12F114 Win. 209 CCI 209M											35.0	10,500
			Rem. RP12	Rem. RP12											37.0	9,000
			Rem. RP12	Rem. RP12											37.5	8,300
3¾	1¾	1,295	Fed. 209A	Rem. RP12 Rem. 209P Win. 209 CCI 209M											34.0	9,900
			Rem. RP12	Rem. RP12											33.0	10,100
			Rem. RP12	Rem. RP12											34.5	8,600
			Rem. 209P	Rem. RP12											35.0	8,600
			Rem. 209P	Rem. RP12											36.0	7,800
3½	1½	1,150	Fed. 209A	Rem. RP12 Win. 209 Rem. 209P CCI 209M									25.5	10,100	33.5	8,300
			Activ T42	Activ T42											32.5	9,200
			Activ T42	Activ T42											32.5	9,300
			Activ T42	Activ T42											32.5	9,400
			Fio. 616	Activ T42											32.0	9,700
3½	1½	1,205	Fed. 209A	Rem. RP12 Rem. 209P CCI 209M											34.0	9,700
			Rem. RP12	Rem. RP12											35.5	8,100
			CCI 209M	Rem. RP12											34.0	9,400
			Win. 209	Rem. RP12											34.5	9,900

# 12-Gauge, 2¾-in. Federal Hi Power Plastic Shells with Rolled Paper Base Wad



Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot		Green Dot		Unique		Herco		Blue Dot		
					Grains	Approx. psi	Grains	Approx. psi	Grains	Approx. psi	Grains	Approx. psi	Grains	Approx. psi	
3½	1	1,290	Fed. 209A	Fed. 12S3 Rem. R12L	21.0 20.5	9,400 8,500	23.0 22.5	7,500 7,400							
2¾	1⅓	1,145	Fed. 209A	Fed. 12S3 Rem. RXP12 Win. WAA12 (White) Hornady Versalite Rem. 209P Fed. 12S3 Win. 209 CCI 209M	18.5 18.5 18.5 18.5 18.5 18.5 18.5 18.5	7,300 8,700 9,600 8,300 8,400 9,100 8,600	20.0 19.0 18.5 19.5	7,200 8,700 9,100 7,100 6,700 8,200 7,600							
3	1⅓	1,200	Fed. 209A	Fed. 12C1 Fed. 12S3 Rem. RXP12 Win. WAA12 (White) Hornady Versalite Rem. 209P Fed. 12S3 Win. 209 CCI 209M	19.0 19.5 19.0 19.5 19.0 20.0 19.5 20.0	9,300 9,300 9,800 9,000 9,400 9,200 9,500 9,300	21.0 20.5 20.0 20.0 19.800 22.0 21.5 21.5	8,000 9,100 9,300 8,800 7,600 8,900 8,600 8,600	23.0 22.0 21.0 22.5	7,700 8,100 7,700 8,000					
3½	1⅓	1,255	Fed. 209A	Fed. 12C1 Fed. 12S3 Rem. RXP12 Win. WAA12 (White) Hornady Versalite Rem. 209P Fed. 12S3 Win. 209 CCI 209M	21.0 21.5 21.0 20.5 22.0 21.5 21.5	10,200 10,100 9,800 9,700 10,300 10,700 10,100	22.0 22.0 22.5 23.5 23.0 23.0 22.0	10,100 9,000 10,000 8,600 8,500 9,400 9,600	24.0 23.0 23.0 23.5	8,100 8,100 8,600 8,200					
3¼	1¼	1,220	Fed. 209A	Fed. 12C1 Fed. 12S4 Rem. R12H Rem. RXP12 Win. WAA12 (White) Win. WAA12F114 Hornady Versalite Rem. 209P Fed. 12S4 Win. 209 CCI 209M			23.0 22.0 22.0 21.5 23.0 23.0 23.0	9,800 10,500 9,600 9,500 9,900 9,700	23.0 23.0 23.0 23.5	9,000 9,500 8,300 9,600 9,400 8,800 9,000 9,500 10,000					
3¾	1¼	1,330	Fed. 209A	Fed. 12C1 Fed. 12S4 Rem. SP12 Win. WAA12 (White) Win. WAA12F114 Win. 209 CCI 209M					25.5 25.5 25.5	10,200 10,200 10,200	28.5 29.0 28.5 29.0 30.0	9,800 10,200 9,900 10,500 10,200 9,500			
3¾	1⅓	1,295	Fed. 209A	Rem. RP12 Rem. SP12 Win. WAA12 (White) Win. WAA12F114 Rem. 209P Win. 209 CCI 209M									38.5 38.0 37.5 37.5	8,600 9,000 8,500 9,100	
4	1⅓	1,350	Fed. 209A	Rem. RP12 Win. 209 CCI 209M									39.0 39.0 39.0	8,400 9,400 8,500	
3½	1½	1,150	Fed. 209A	Rem. SP12 Activ T42 Rem. RP12 Win. 209 Rem. 209P CCI 209M							26.5	8,900	32.5 33.5	9,100 8,400	
3½	1½	1,205	Fed. 209A	Rem. RP12 CCI 209M Win. 209									34.5 35.0 34.5	8,500 8,700 8,600	
3¾	1½	1,260	Fed. 209A	Rem. RP12 Rem. SP12 Win. 209 CCI 209M									36.0 37.0 37.0 37.0	9,500 9,600 9,900 9,500	



## 12-Gauge, 2¾-in. Federal One-Piece Plastic Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Green Dot		Unique		Herco		Blue Dot	
					Grains	Approx. psi	Grains	Approx. psi	Grains	Approx. psi	Grains	Approx. psi
3½	1¼	1,220	Fed. 209A	Fed. 12S4			25.0	9,100	26.0	8,400		
			Rem. SP12	Win. WAA12F114			25.5	8,700	26.5	7,800		
			Rem. 209	Fed. 12S4			25.5	8,700	26.0	8,000		
			Win. 209	Fed. 12S4			25.0	8,800	26.5	9,100		
			CCI 209M	Fed. 12S4			25.0	9,200	26.0	8,500		
							25.5	9,200	26.0	8,900		
3¾	1¼	1,275	Fed. 209A	Fed. 12S4					28.0	9,500		
			Rem. SP12	Win. WAA12F114					27.5	8,200		
			Rem. 209	Fed. 12S4					27.5	8,700		
			Win. 209	Fed. 12S4					28.5	9,400		
			CCI 209M	Fed. 12S4					27.5	9,000		
									27.5	9,500		
3½	1¾	1,330	Fed. 209A	Fed. 12S4							38.5	8,500
			Win. WAA12F114								39.0	7,700
			Win. 209	Fed. 12S4							39.0	8,400
			CCI 209M	Fed. 12S4							37.5	9,000
3½	1⅓	1,240	Fed. 209A	Rem. SP12							37.0	8,100
			Win. WAA12F114								38.0	7,900
			Win. 209	Rem. SP12							37.5	7,700
			CCI 209M	Rem. SP12							37.5	8,300
3¾	1⅓	1,295	Fed. 209A	Rem. RP12							38.5	8,700
			Rem. 209	Rem. RP12							38.5	9,500
			Win. 209	Rem. RP12							38.5	9,300
			CCI 209M	Rem. RP12							38.0	9,200
3½	1½	1,150	Fed. 209A	Fed. 12S4					27.0	9,200		
			Rem. SP12	Win. WAA12F114					27.0	8,600		
			Activ T35						26.5	8,700		
			Win. 209	Fed. 12S4					26.5	8,500		
			Rem. 209P	Fed. 12S4					26.5	10,100		
			CCI 209M	Fed. 12S4					26.5	10,000		
3½	1½	1,205	Fed. 209A	Fed. 12S4					26.0	10,100		
			Rem. 209	Rem. RP12					36.0	8,800		
			Win. 209	Rem. RP12					36.0	8,100		
			CCI 209M	Rem. RP12							37.0	8,500
			Fed. 209A	Rem. RP12							36.0	8,500
											38.0	9,900
3¾	1½	1,260	Rem. 209	Rem. RP12							38.0	8,700
			Win. 209	Rem. RP12							38.0	9,100
			CCI 209M	Rem. RP12							38.0	10,000
3½	1⅓	1,115	Fed. 209A	Rem. SP12					26.5	10,000		
			Win. 209	Rem. SP12					26.5	9,800		
			Rem. 209P	Rem. SP12					26.5	9,500		
			CCI 209M	Rem. SP12					26.5	10,000		
			Fio. 616	Rem. SP12					26.0	10,300		



## 12-Gauge, 3-in. Federal Hi Power Plastic Shells with Rolled Paper Base Wad

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Herco		Blue Dot	
					Grains	Approx. psi	Grains	Approx. psi
3 3/4	1 3/8	1,295	Fed. 209A	Fed. 12S3 Rem. RXP12 Win. WAA12 (White)	30.5 30.5 30.5	10,000 9,300 9,700	38.0 38.0	9,000 8,800
4	1 3/8	1,350	Fed. 209A	Fed. 12S4 Rem. SP12 Win. WAA12F114			40.0 40.0 40.0	9,400 8,900 9,800
4	1 1/2	1,315	Fed. 209A	Fed. 12S3 Rem. RXP12 Win. WAA12 (White) Activ TG30			38.0 38.5 37.5 38.0	9,700 9,600 9,800 9,400
4	1 5/8	1,280	Fed. 209A	Rem. SP12			39.0	10,400
4	1 3/4	1,245	Fed. 209A	Rem. RP12			39.0	10,500
3 3/4	1 7/8	1,155	Fed. 209A	Rem. SP12 Rem. RP12 Activ T35			36.0 34.0 34.5	10,300 10,500 10,100

## 12-Gauge, 3-in. Federal One-Piece Plastic Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Green Dot		Unique		Herco		Blue Dot	
					Grains	Approx. psi	Grains	Approx. psi	Grains	Approx. psi	Grains	Approx. psi
3 3/4	1 3/8	1,295	Fed. 209A	Fed. 12S3 Rem. RXP12 Win. WAA12 (White)					31.0 32.0	10,500 10,100	40.5 38.0	7,900 9,800
4	1 3/8	1,350	Fed. 209A	Rem. RXP12 Win. WAA12 (White)							42.0 44.0	8,000 9,900
4	1 1/2	1,315	Fed. 209A	Fed. 12S4 Rem. SP12 Win. WAA12F114							40.0 40.0 42.0	9,700 9,000 9,800
4	1 5/8	1,280	Fed. 209A	Fed. 12S4 Rem. SP12 Win. WAA12F114							40.0 40.0 40.0	10,100 9,400 10,000
4	1 3/4	1,245	Fed. 209A	Rem. RP12							39.0	10,500
3 3/4	1 7/8	1,155	Fed. 209A	Rem. SP12 Activ T35							36.5 35.5	9,900 9,300

# 12-Gauge, 2¾-in. Remington Premier Plastic Target Shells



Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Approx. psi	American Select Grains	Approx. psi	Green Dot Grains	Approx. psi	Unique Grains	Approx. psi	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi	
—	7/8	1,200	Rem. 209P	Rem. TGT 12 Fed. 12SO Win. WAA12SL Purple PC	17.0*	6,800											
—	7/8	1,250	Rem. 209P	Rem. TGT 12 Fed. 12SO Win. WAA12SL Purple PC	18.5*	7,100											
—	7/8	1,300	Rem. 209P	Rem. TGT 12 Fed. 12SO Win. WAA12SL Purple PC Claybuster	20.5	8,200	20.5	7,000	22.0	7,100							
2 3/4	1	1,200	Rem. 209P	Rem. TGT 12 Fed. 12SO Win. WAA12SL Purple PC Claybuster	18.0	8,700	19.0	7,000	20.0	8,200							
3	1	1,255	Rem. 209P	Rem. TGT 12 Fed. 12SO Win. WAA12SL Purple PC Claybuster	19.0	9,500	20.5	8,000	21.0	8,500							
3 1/4	1	1,290	Rem. 209P	Rem. Fig. 8 Rem. TGT 12 Rem. R12L Win. WAA12F1 Win. WAA12SL Fed. 12SO Purple PC Claybuster	21.5	9,100	22.5	8,700	22.0	8,100							
			Fed. 209	Rem. R12L	21.0	10,700			22.5	8,400							
			Win. 209	Rem. R12L	20.5	9,900			23.0	7,200							
			CCI 209M	Rem. R12L	20.0	10,400	21.5	9,200	22.5	9,000							
					20.5	10,500	21.5	9,900	22.0	8,700							
					20.5	10,100			22.5	8,200							
					20.0	10,300			22.0	9,100							
2 1/2 Extra Lite	1 1/8	1,090	Rem. 209P	Rem. Fig. 8 Rem. RXP12 Fed. 12S3 Win. WAA12 (White) Win. WT12 (Orange) Fiocchi FTW1 Windjammer Red PC Claybuster	16.5	8,300	17.5	7,100									
			Fed. 209	Rem. Fig. 8	16.0	8,700	17.0	7,500									
			Win. 209	Rem. Fig. 8	16.0	10,300	17.5	8,200									
			CCI 209M	Rem. Fig. 8 Rem. RXP12 Fed. 12S3 Win. WAA12 (White) Fiocchi FTW1 Windjammer Red PC	16.0	9,400			17.0	7,300							
					16.5	8,500											
					16.5	7,900	18.0	6,900									
					16.5	8,700	17.5	7,000									
					16.5	9,200	17.5	6,900									
			Fio. 616	Rem. Fig. 8	16.0	9,800											
					16.5	8,900											
2 3/4	1 1/8	1,145	Rem. 209P	Rem. Fig. 8 Fed. 12S3 Rem. RXP12 Win. WAA12 (White) Win. WT12 (Orange) Fiocchi FTW1 Windjammer Red PC Lage Uniwad Hornady Versalite Claybuster	18.0	9,200	19.0	7,600	19.0	7,300							
					18.0	10,100	18.5	9,100	19.0	8,800							
					17.5	8,900	18.5	8,300	19.0	7,700							
					17.0	10,100			19.0	6,700							
					18.5*	8,800	18.5*	8,900	19.5*	7,900							
					17.5	9,700			19.5	8,800							
					17.5	8,900	19.0	7,900	19.5	7,800							
					17.5	9,000	19.0	8,200	19.0	7,600							
					17.5	9,900			19.0	8,000							
					17.5	9,000			19.0	8,000							

NOTE: \*For each asterisk (\*), add one 20-gauge, 0.135 in. thick card wad to the inside bottom of the shot cup.

continued on next page

## 12-Gauge, 2¾-in. Remington Premier Plastic Target Shells (continued)

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Red Dot Approx. psi	American Select Grains	American Select Approx. psi	Green Dot Grains	Green Dot Approx. psi	Unique Grains	Unique Approx. psi	Herco Grains	Herco Approx. psi	Blue Dot Grains	Blue Dot Approx. psi				
2½	1⅓	1,145	Fed. 209A	Rem. Fig. 8 Rem. RXP12 Fed. S3 Red PC Windjammer	16.5 16.0 16.5 17.0 17.5	10,300 10,600 10,100 10,700 10,500	18.5	9,200	19.5 19.5 19.0 19.5 20.0	10,100 10,500 9,900 10,000 9,600										
			Win. 209 CCI 209M	Rem. Fig. 8 Rem. Fig. 8 Rem. RXP12 Fed. 12S3 Win. WAA12 (White) Fiocchi FTW1 Windjammer Red PC Hornady Versalite	18.0 17.5 17.0 17.5 16.5 17.0 17.0 17.0 17.0	9,500 9,300 9,600 10,600 10,200 9,900 9,000 9,400 9,100	18.5	9,000	19.0 19.0 19.0 19.0 19.0 19.5 19.5 19.0 19.0	8,100 8,800 9,100 8,900 9,400 9,300 7,900 7,700 8,000										
			CCI 209 CCI 209SC	Rem. Fig. 8 Rem. Fig. 8 Fed. 12S3 Win. WAA12 (White) Windjammer	17.5 18.0 18.5	8,600 10,400 10,400	18.5	8,900	19.5 20.5 19.5 20.0	7,100 9,900 9,500 10,600										
			Fio. 616	Rem. Fig. 8	17.5	8,900			19.0	7,800										
3	1⅓	1,200	Rem. 209P	Rem. Fig. 8 Rem. RXP12 Fed. 12S3 Win. WAA12 (White) Win. WT12 (Orange) Fiocchi FTW1 Windjammer Red PC Hornady Versalite Claybuster	19.0 19.0 19.0 19.5*	10,100 10,000 10,600 10,700 10,700 9,400 9,400 10,100 9,500	20.5 20.5 20.0	9,100 10,200 10,600	21.0 20.5 20.5 21.0 20.5 20.5 20.5 20.0	8,800 8,700 9,700 8,900 9,900 8,200 8,500 8,700	22.5 22.5 22.0 22.0 23.5*	8,200 8,300 9,100 8,900 8,300 7,000 7,800 7,900								
			Fed. 209A	Rem. Fig. 8 Rem. RXP12	17.0 17.0	10,400 10,100	20.0	10,700	20.5 21.0	10,500 10,400	23.0 22.0	9,200 9,100								
			Win. 209 CCI 209M	Rem. Fig. 8 Rem. Fig. 8 Rem. RXP12 Fed. 12S3 Win. WAA12 (White) Fiocchi FTW1 Windjammer Red PC Hornady Versalite	19.0 18.5 18.5	10,400 10,400 10,500	20.0	10,200	20.0 20.0 20.5 21.0 20.5 20.5 20.0	8,600 9,300 9,200 10,200 9,600 9,700 9,200	22.5 22.5 22.5 22.0 22.0 22.0 22.0	8,400 9,500 9,500 9,700 9,300 9,700 8,800								
			CCI 209 CCI 209SC	Rem. Fig. 8 Rem. Fig. 8 Fed. 12S3 Windjammer	19.5 19.0	9,900 10,400 10,600	20.0	10,300	21.0 21.0 20.0	8,700 10,600 10,600	22.5 22.5	8,500 8,500								
			Fio. 616	Rem. Fig. 8	19.5	10,600			20.0	8,700	23.0	8,500								
Heavy	1⅔	1,250	Fed. 209	Rem. RXP12					22.0	10,500	24.0	10,100								
			Win. 209	Rem. RXP12					22.0	9,400	24.5	8,800								
			CCI 209M	Rem. RXP12 Fed. 12S3 Win. WAA12 (White) Windjammer Red PC Hornady Versalite					22.0 21.5 22.5 22.0 22.0 21.5	9,600 10,600 10,700 9,400 9,600 10,200	24.0 23.5 24.0 25.0 24.0 23.5	10,400 10,200 10,300 9,300 9,400 10,400	24.5 24.5 24.5 25.0 25.0 24.5	9,800 9,900 10,400 9,400 9,500 9,900						
			Fio. 616	Rem. RXP12					22.0	9,100	23.5	9,100								
			Rem. 209P	Rem. RXP12 Rem. Fig. 8 Claybuster			21.0 21.5 21.5	10,500 9,900 10,600												
3½	1⅓	1,310	Rem. 209P	Rem. RXP12 Win. WAA12 (White) Windjammer Hornady Versalite Activ T32							24.5 25.0 26.5 25.5 25.0	9,700 10,500 8,600 9,900 9,900	27.5 27.0 28.5 27.0 27.0	8,400 8,800 8,600 9,700 9,600						
			Fed. 209	Rem. RXP12											27.0	9,200				
			Win. 209	Rem. RXP12											27.0	9,500				
			CCI 209M	Rem. RXP12											26.5	9,700				
			Fio. 616	Rem. RXP12											26.0	9,900	27.5	9,300		

NOTE: \*For each asterisk(\*), add one 20-gauge, 0.135 in. thick card wad to the inside bottom of the shot cup.

continued on next page

## 12-Gauge, 2¾-in. Remington Premier Plastic Target Shells (continued)

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Red Dot Approx. psi	American Select Grains	American Select Approx. psi	Green Dot Grains	Green Dot Approx. psi	Unique Grains	Unique Approx. psi	Herco Grains	Herco Approx. psi	Blue Dot Grains	Blue Dot Approx. psi
3½	1¼	1,220	Rem. 209P	Rem. SP12 Fed. 12S4 Win. WAA12F114 Hornady Versalite Activ T32					23.5	9,300	25.0	9,600				
			Fed. 209	Rem. SP12					23.0	10,700	25.0	10,400				
			Win. 209	Rem. SP12					24.0	10,100	24.5	9,300				
			CCI 209M	Rem. SP12					23.5	9,400	25.0	8,400				
			Fio. 616	Rem. SP12					23.5	9,400	25.0	8,800				
									23.0	9,900	25.0	9,800				
									23.5	10,000	24.5	9,600				
									23.5	10,300	24.5	10,000				
									23.0	9,600	24.5	9,300				
3½	1¼	1,275	Rem. 209P	Rem. SP12 Fed. 12S4 Win. WAA12F114 Activ T35										34.5	8,600	
			Fed. 209	Rem. SP12							26.5	10,500			34.0	10,100
			Win. 209	Rem. SP12							27.0	9,900			35.0	8,500
			CCI 209M	Rem. SP12										35.0	9,100	
			Fio. 616	Rem. SP12										26.0	10,600	
														35.5	9,100	
														34.5	9,800	
														35.5	9,300	
3¾	1¼	1,330	Rem. 209P	Rem. SP12											37.5	9,700
			Fed. 209	Rem. SP12										36.5	9,700	
			Win. 209	Rem. SP12										36.5	9,900	
			CCI 209M	Rem. SP12										35.5	10,300	
			Fio. 616	Rem. SP12										35.5	9,900	
3½	1¾	1,240	Rem. 209P	Rem. SP12 Activ T35											35.0	9,300
			Fed. 209	Rem. SP12										34.0	9,300	
			Win. 209	Rem. SP12										35.0	9,100	
			CCI 209M	Rem. SP12										35.0	9,100	
			Fio. 616	Rem. SP12										34.0	9,400	
														34.0	9,100	
3¾	1¾	1,295	Rem. 209P	Rem. SP12											37.5	10,300
			Rem. RP12											36.5	9,900	
			Fed. 209	Rem. RP12										35.5	10,500	
			Win. 209	Rem. RP12										35.5	10,500	
			CCI 209M	Rem. RP12										35.5	10,400	
			Fio. 616	Rem. RP12										35.5	10,000	
3½	1½	1,150	Rem. 209P	Rem. RP12 Activ T42											31.0	9,900
			Fed. 209	Rem. RP12										30.5	10,400	
			Win. 209	Rem. RP12										31.0	9,900	
			CCI 209M	Rem. RP12										31.5	10,100	
			Fio. 616	Rem. RP12										31.0	9,900	
														31.0	9,800	
3½	1½	1,205	Rem. 209P	Rem. RP12 Activ T42											33.0	10,200
			Fed. 209	Rem. RP12										31.5	10,600	
			Win. 209	Rem. RP12										33.0	10,300	
			CCI 209M	Rem. RP12										33.0	10,200	
			Fio. 616	Rem. RP12										33.0	10,100	
														33.0	10,100	

PC: Pattern Control

# 12-Gauge, 2¾-in. Remington-Peters Unibody SP Plastic Shells



Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Approx. psi	Green Dot Grains	Approx. psi	Unique Grains	Approx. psi	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi
3½	1	1,290	Rem. 209	Rem. R12L Rem. RXP12 Win. WAA12F1			22.0	9,200						
			CCI 209	Rem. R12L	21.0	9,700	21.5	9,900						
			CCI 209M	Rem. R12L	20.0	10,600	21.0	9,900						
			Fed. 209	Rem. R12L	19.5	10,400	22.5	8,100						
			Win. 209	Rem. R12L	20.0	10,700	22.0	9,600						
							21.5	8,800						
2¾	1⅓	1,145	Rem. 209	Rem. RXP12 Rem. R12H Fed. 12S3 Win. WAA12 (White) Hornady Versalite	17.5	9,300	19.0	8,800						
			CCI 209	Rem. RXP12	17.0	10,100	19.0	8,500						
			CCI 209M	Rem. RXP12	17.0	10,200	19.0	9,200						
			Fed. 209	Rem. RXP12	17.5	10,500	17.5	10,000						
			Win. 209	Rem. RXP12	17.0	10,500	18.0	8,500						
							18.0	9,200						
3	1⅓	1,200	Rem. 209	Rem. RXP12 Rem. R12H Fed. 12S3 Win. WAA12 (White) Hornady Versalite Windjammer	18.0	10,500	20.0	9,800	22.0	9,100				
					18.0	10,000	19.5	9,400	21.5	8,300				
							19.5	10,000	21.5	8,400				
							18.0	9,900	21.0	8,200				
							18.5	9,600	20.5	8,300	22.0	7,700		
			Fed. 209	Rem. RXP12	18.0	10,100	20.0	9,200	22.0	8,100				
			CCI 209	Rem. RXP12			21.0	8,800	23.0	8,300				
			CCI 209M	Rem. RXP12			20.0	10,000	22.0	8,800				
			Win. 209	Rem. RXP12			20.5	9,800	22.0	8,900				
3¼	1⅓	1,255	Rem. 209	Rem. RXP12 Rem. R12H Fed. 12S3 Win. WAA12 (White)			20.5	10,300	22.5	9,200				
							21.0	10,400	22.5	8,300				
									22.5	9,800				
									22.5	9,200				
			Rem. 97★	Rem. RXP12 Rem. R12H			21.0	10,600						
							21.0	10,100						
			Fed. 209	Rem. RXP12			20.5	10,200	23.0	10,000				
			CCI 209	Rem. RXP12			22.5	10,500	23.0	8,800				
			CCI 209M	Rem. RXP12			21.0	10,100	23.0	9,700				
			Win. 209	Rem. RXP12			21.5	10,700	23.5	9,800				
3½	1⅓	1,310	Rem. 209	Rem. RXP12 Rem. R12H Win. WAA12 (White)					24.0	10,000	25.5	10,200		
									24.5	10,100	25.5	10,100		
			Fed. 209	Rem. R12H					24.0	10,300	24.5	10,200		
			CCI 209	Rem. R12H							25.5	10,700		
			CCI 209M	Rem. R12H					25.5	9,600	27.0	9,300		
			Win. 209	Rem. R12H					25.0	10,700	26.5	10,300		
									25.0	10,700	26.5	10,700		
3¼	1¼	1,220	Rem. 209	Rem. SP12 Win. WAA12F114					22.5	9,700	23.5	9,400		
			Fed. 209	Rem. SP12					22.5	10,700	23.5	10,400		
			CCI 209	Rem. SP12					24.5	9,600	25.5	9,100		
			CCI 209M	Rem. SP12									32.0	8,500
			Win. 209	Rem. SP12					23.0	10,100	24.5	10,500	33.0	9,000
3½	1¼	1,275	Rem. 209	Rem. SP12 Win. WAA12F114									32.0	10,200
			Fed. 209	Rem. SP12									32.0	10,000
			CCI 209	Rem. SP12									32.5	10,600
			CCI 209M	Rem. SP12									35.5	8,900
			Win. 209	Rem. SP12									33.5	9,800
													35.0	10,300
3¾	1¼	1,330	CCI 209	Rem. RP12									37.5	9,700
			CCI 209M	Rem. RP12									35.5	10,400
3½	1⅓	1,240	CCI 209	Rem. RP12									36.0	10,100
			CCI 209M	Rem. RP12									32.5	10,500
3¼	1½	1,150	Rem. 209P	Rem. RP12 Activ T42									32.5	8,000
			Fed. 209	Rem. RP12									31.5	9,600
			Win. 209	Rem. RP12									31.5	9,100
			CCI 209M	Rem. RP12									32.0	8,300
			Fio. 616	Rem. RP12									32.0	8,400
													31.5	9,200
3¼	1⅓	1,115	Rem. 209P	Activ T42									29.5	10,500
			Fed. 209A	Activ T42									29.0	10,400
			Win. 209	Activ T42									29.5	10,400
			CCI 209M	Activ T42									29.5	10,300
			Fio. 616	Activ T42									29.5	10,400

## 12-Gauge, 3-in. Remington-Peters SP Plastic Shells with Separate Plastic Base Wad



Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Red Dot Approx. psi	Green Dot Grains	Green Dot Approx. psi	Unique Grains	Unique Approx. psi	Herco Grains	Herco Approx. psi	Blue Dot Grains	Blue Dot Approx. psi
3 3/4	1 3/8	1,295	CCI 209M	Rem. RXP12* Fed. 12S3 Win. WAA12 (White)*							30.0	9,200		
											29.5	10,000		
											30.0	10,000		
4	1 3/8	1,350	CCI 209M	Rem. RXP12 Fed. 12S3 Win. WAA12 (White)									42.5	8,000
													42.0	8,400
													42.0	8,500
4	1 1/2	1,315	CCI 209M	Rem. SP12* Fed. 12S4* Win. WAA12F114*									40.0	9,400
													39.5	9,800
													39.5	9,800
4	1 5/8	1,280	CCI 209M	Rem. SP12 Fed. 12S4 Win. WAA12F114									39.0	9,800
													38.5	10,200
													38.5	10,500
4	1 3/4	1,245	CCI 209M	Rem. RP12 Activ T35									38.5	10,700
													37.5	10,400
3 3/4	1 7/8	1,155	CCI 209M	Rem. RP12 Activ T35									34.0	10,300
													34.0	10,100

NOTE: \*For each asterisk (\*), add one 20-gauge, 0.135-in. thick card wad to the inside bottom of the shot cup.

## 12-Gauge, 3-in. Remington-Peters Unibody SP Plastic Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Herco Grains	Herco Approx. psi	Blue Dot Grains	Blue Dot Approx. psi	2400 Grains	2400 Approx. psi
3 3/4	1 3/8	1,295	Win. 209	Rem. RXP12 Fed. 12S3 Win. WAA12SL Win. WAA12 (White) Activ TG30					37.5	9,200
									37.0	9,300
									35.5	10,100
									36.5	9,400
									36.5	9,200
4	1 3/8	1,350	Win. 209	Rem. RXP12 Fed. 12S4 Win. WAA12F114 Activ T32					38.5	9,900
									38.0	10,200
									38.0	10,500
									38.5	9,800
4	1 1/2	1,315	CCI 209M	Rem. SP12					37.5	10,700

## Additional 12-Gauge, 2 3/4-in., 7/8-oz. Target Loads‡

Shell	Velocity (fps)	Primer	Wad	Bullseye Grains	Bullseye Approx. psi	Red Dot Grains	Red Dot Approx. psi	American Select Grains	American Select Approx. psi	Green Dot Grains	Green Dot Approx. psi
Federal Paper Target	1,200	Fed. 209	Fed. 12SO Win. WAA12F1 Rem. PT12	17.5 17.5* 17.5*	4,500 4,600 5,100	17.5 17.5 17.5	5,700 4,800 5,000				
Federal Gold Medal	1,200	Fed. 209	Fed. 12SO Win. WAA12F1 Rem. PT12	17.0** 17.0** 17.5**	6,300 5,800 5,500	18.0 18.0* 18.0*	6,200 5,700 6,400				
Win. Western AA-Type	1,200	Win. 209	Win. WAA12F1 Fed. 12SO Rem. PT12	16.5* 16.5 16.5*	6,700 7,400 7,100	16.5 16.0* 16.5*	7,300 8,000 7,300				

NOTES: \*For each asterisk (\*), add one 20-gauge, 0.135-in. thick card wad to the inside bottom of the shot cup.

‡Auto-loading shotguns may not function with loads having pressures less than 7,000 psi.

It is important to have tight crimps to prevent load efficiencies (pressures) from dropping. The efficiency may also drop when these loads are fired at low temperatures.



## 12-Gauge, 2¾-in. Winchester Plastic AA Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Red Dot Approx. psi	American Select Grains	American Select Approx. psi	Green Dot Grains	Green Dot Approx. psi	Unique Grains	Herco Grains	Herco Approx. psi	Blue Dot Grains	Blue Dot Approx. psi		
—	7/8	1,200	Win. 209	Win. WAA12SL Win. WAAL (Gray) Fed. 12SO Rem. TGT 12 Purple PC	16.5* 16.5 16.0* 16.5* 17.0*	7,300 7,900 8,000 7,300 7,500											
—	7/8	1,250	Win. 209	Win. WAA12SL Win. WAAL (Gray) Fed. 12SO Rem. TGT 12 Purple PC	18.0* 17.5 17.5 18.0* 18.0*	9,300 8,600 9,000 8,400 8,400	18.5	7,200									
—	7/8	1,300	Win. 209	Win. WAA12SL Win. WAAL (Gray) Fed. 12SO Rem. TGT 12 Purple PC Claybuster	19.0 18.5 19.0 19.0* 19.5*	10,300 9,300 9,400 9,300 9,000	20.5 19.5 21.0 20.5 20.5	8,400 8,000 8,300 7,600 7,200	20.5 20.0 21.0 21.0 21.5*	8,800 8,300 8,900 8,400 7,900							
—	7/8	1,400	Win. 209	Win. WAAL (Gray)			22.0	10,200									
2 3/4	1	1,200	Win. 209	Win. WAA12SL Win. WT12 (Orange) Fed. 12SO Rem. TGT 12 Purple PC Claybuster	18.0 17.5 18.0 18.0 18.0	10,200 10,600 9,600 9,200 8,900	19.0 19.0 19.0 19.0 19.0	8,200 8,700 8,000 7,400	19.5 19.5 19.5 19.5	8,500 8,400 7,900 7,000							
3	1	1,255	Win. 209	Win. WAA12SL Rem. TGT 12 Purple PC Fed. 12SO Claybuster	19.0 19.5 19.0	10,500 9,800 9,700	20.0 20.0 20.0 20.5	9,500 9,100 10,000 8,800	21.0 21.0 21.5	9,200 8,800 8,700							
3 1/4	1	1,290	Win. 209	Win. WAA12SL Win. WAA12 (White) Fed. 12C1 Fed. 12S3 Fed. 12SO Rem. RXP12 Rem. TGT 12 Purple PC Claybuster	19.0 19.0 20.0 20.0 20.0 20.0 20.0	10,500 10,500 10,200 9,900 10,100 10,400	21.5 20.5	10,300 10,200	21.5 21.0 22.5	9,500 8,800 9,700							
Extra Lite	1 1/8	1,090	Win. 209	CCI 209M Win. WAA12 (White)	18.5	10,400			21.5	9,900							
				Win. WAA12SL Win. WAA12 (White) Win. WT12 (Orange) Rem. Fig. 8 Rem. RXP12 Fed. 12S3 Hornady Versalite Red PC Claybuster	16.0 16.0 16.0 16.0 16.5 17.0 16.5 16.0	9,300 9,500 9,000 8,300 9,000 10,400 9,000 9,100	17.0	9,000	18.0 17.5 16.5 17.5 17.0 17.0 17.5 17.0	8,000 8,100 9,000 8,100 7,400 7,600 7,800 7,300							
				Fed. 209 Win. WAA12 (White) Fed. 209A Win. WAA12 (White) Rem. 209P Win. WAA12 (White) CCI 209M Win. WAA12 (White) CCI 209SC Win. WAA12 (White) Fio. 616 Win. WAA12 (White)	16.0 16.0 17.0 17.0 17.0 16.0	9,900 9,900 8,100 9,800 7,900	17.0 17.0 17.0 17.0 17.0	8,700 8,000 8,000									
									17.0	7,900							
2 3/4	1 1/8	1,145	Win. 209	Win. WAA12SL Win. WAA12 (White) Win. WT12 (Orange) Rem. Fig. 8 Rem. RXP12 Fed. 12C1 Fiocchi FTW1 Hornady Versalite Windjammer Red PC Claybuster	17.0 17.0 16.5 17.5 17.5 17.5 17.5 18.0 17.5 17.5	10,000 10,000 10,700 9,900 8,400 9,400 10,100 9,500 9,300 9,500	18.0 18.5 18.5 19.0 19.0 18.5 19.5 19.5 18.0 18.5	9,400 9,600 9,400 9,400 9,400 8,100 9,600 8,000 8,400 9,000	19.0 18.0 18.0 19.0 18.0 18.5 19.5 19.5 18.0 19.0	9,400 8,500 9,400 8,600 8,100 8,100 9,600 8,000 8,400 8,300							

*continued on next page*

## 12-Gauge, 2¾-in. Winchester Plastic AA Shells (continued)

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Red Dot Approx. psi	American Select Grains	American Select Approx. psi	Green Dot Grains	Green Dot Approx. psi	Unique Grains	Unique Approx. psi	Herco Grains	Herco Approx. psi	Blue Dot Grains	Blue Dot Approx. psi	
2¾	1⅓	1,145	Fed. 209A	Win. WAA12 (White) Rem. Fig. 8 Hornady Versalite Windjammer Red PC Claybuster	17.0	10,600	18.5	9,800	18.0	9,300							
				Rem. 209P	17.5	8,700	19.0	8,700	18.5	8,600							
			CCI 109	Win. WAA12 (White)	17.0	9,200			18.0	8,200							
			CCI 209M	Win. WAA12 (White)	17.5	10,400			18.5	10,100							
			CCI 209SC	Win. WAA12 (White) Rem. Fig. 8 Windjammer	17.5	10,600	18.5	9,600	19.5	10,300							
				18.0	10,500			20.5	9,700								
				18.0	9,900			20.5	9,500								
			Fio. 616	Win. WAA12 (White)	17.0	10,200			18.5	9,400							
3	1⅓	1,200	Win. 209	Win. WAA12SL Win. WAA12 (White) Win. WT12 (Orange) Rem. Fig. 8 Rem. RXP12 Fed. 12C1 Fiocchi FTW1 Hornady Versalite Windjammer Red PC Claybuster	18.0	10,400	19.5	10,300	19.5	9,300	22.5	9,100					
				17.0	10,700	19.5	10,700	19.0	10,100	21.5	9,000						
				18.5	10,700	20.0	9,800	20.5	9,500	22.5	8,300						
				18.5	9,800	20.5	10,700	19.5	8,900	22.0	8,700						
				18.5	9,700			19.5	9,000	22.0	8,900						
				18.5	10,700			20.0	9,900	22.5	8,800						
				19.0	9,700			21.0	9,000	21.0	8,200						
				18.5	9,900			21.0	9,000	22.5	8,200						
				18.5	10,500	20.0	10,100	20.5	9,800	23.5	9,500						
					19.5	10,200											
			Fed. 209A	Win. WAA12 (White) Rem. Fig. 8 Hornady Versalite Windjammer Red PC Claybuster	18.5	10,200	19.5	10,800	19.0	10,200							
				18.0	10,700			19.5	9,400								
				18.0	10,000			20.0	9,200								
				18.0	10,000			19.5	10,500								
				18.5	10,500			19.5	9,300								
				19.0	9,500	21.0	9,600	20.0	9,800	23.0	7,500						
				18.0	10,400			19.0	9,300								
				18.5	10,500			20.0	10,400	21.5	10,300						
					18.5	10,400	19.5	10,100	20.5	10,700							
					18.5	10,400			22.0	10,400							
					18.5	10,200			22.0	10,200							
				Fio. 616	Win. WAA12 (White)	18.0	10,500			20.0	9,500	21.5	9,100				
Heavy	1⅓	1,250	Win. 209	Win. WAA12SL Win. WAA12 (White) Win. WT12 (Orange) Rem. Fig. 8 Rem. RXP12 Fed. 12C1 Hornady Versalite Red PC Claybuster					21.5	10,500	24.0	9,900					
									19.0	9,900	23.5	9,400	25.0	9,500			
									22.0	10,300	22.5	9,500	23.5	9,400			
									21.0	10,800	24.0	9,000	25.0	9,100			
									21.0	9,500	23.0	9,200	25.0	9,200			
									21.0	10,200	23.0	9,500	25.0	9,400			
									22.0	9,900	24.0	9,400	24.5	9,200			
									22.0	10,300	24.5	10,000	25.0	9,100			
				Win. 209	Activ T32	21.5	9,600			23.0	8,800						
				Fed. 209	Win. WAA12 (White)							24.0	10,100				
				Rem. 209P	Win. WAA12 (White)							24.0	9,300				
					Rem. Fig. 8												
				Fio. 616	Win. WAA12 (White)	22.0	10,500			23.5	10,100						
3½	1⅓	1,310	Win. 209	Rem. RXP12 Win. WAA12 (White) Red PC Hornady Versalite							24.0	9,800	26.5	9,100			
			Fed. 209	Win. WAA12 (White)							25.5	10,000	26.5	9,300			
			Rem. 209P	Win. WAA12 (White)							25.0	9,100					
											25.0	10,300	26.5	9,900			
				CCI 209M	Win. WAA12 (White)						24.5	10,600					
											26.0	9,700	27.0	8,100			
											25.5	9,700					

continued on next page

## 12-Gauge, 2¾-in. Winchester Plastic AA Shells (continued)

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Red Dot Approx. psi	AmericanSelect Grains	AmericanSelect Approx. psi	Green Dot Grains	Green Dot Approx. psi	Unique Grains	Unique Approx. psi	Herco Grains	Herco Approx. psi	Blue Dot Grains	Blue Dot Approx. psi
3½	1¼	1,220	Win. 209	Fed. 12S4 Rem. RP12 Win. WAA12F114 Hornady Versalite  Win. 209 Activ T35 Fed. 209 Win. WAA12F114 Rem. 209P Win. WAA12F114 CCI 209M Win. WAA12F114 Fio. 616 Win. WAA12F114					23.5 22.5 23.5 24.0	10,400 9,500 9,900 9,800	25.0 25.0 25.5 25.5	9,300 8,400 8,500				
3½	1¼	1,275	Win. 209	Win. WAA12F114 Rem. SP12 Fed. 12S4 Activ T35  Fed. 209 Win. WAA12F114 Rem. 209P Win. WAA12F114 CCI 209M Win. WAA12F114 Fio. 616 Win. WAA12F114							26.5 26.0 26.0 26.0 27.0	10,700 10,700 10,700 10,700 9,400	24.5 24.0 25.5 24.0 23.5	10,400 10,100 8,300 9,100 10,300	34.5 35.0 34.0 34.5 32.0	9,900 8,200 10,500 9,000 9,500
3¾	1¼	1,330	Win. 209	Rem. RP12 Rem. SP12 Win. WAA12F114 Activ T35  Fed. 209 Win. WAA12F114 CCI 209M Win. WAA12F114											38.0 37.0 37.0 36.5 33.5	10,200 10,300 10,600 9,700 10,500
3½	1⅓	1,240	Win. 209	Win. WAA12F114 Rem. SP12 Fed. 12S4  Fed. 209 Win. WAA12F114 CCI 209M Win. WAA12F114											34.0 33.0 33.0 32.0 33.5	10,500 10,600 10,400 10,100 8,300
3½	1½	1,150	Win. 209	Rem. RP12 Activ T42  Rem. 209P Activ T42 CCI 209M Activ T42											31.0 30.0 30.0 30.0	9,400 10,000 10,400 10,400

PC: Pattern Control

NOTES: \*For each asterisk(\*), add one 20-gauge, 0.135-in. thick card wad to the inside bottom of the shot cup.

Auto-loading shotguns may not function with loads having pressures less than 7,000 psi. It is important to have tight crimps to prevent load efficiencies (pressures) from dropping. The efficiency may also drop when these loads are fired at low temperatures.



## 12-Gauge, 2¾-in. Winchester Polyformed with Plastic Wad

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Approx. psi	Green Dot Grains	Approx. psi	Unique Grains	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi
3½	1	1,290	Win. 209	Win. WAA12F1	22.0	7,600	23.5	7,000					
				Fed. 12SO	21.0	9,600							
				Rem. Fig. 8	21.5	8,500	23.0	7,800					
				Purple PC	21.5	7,900	24.0	6,800					
				Rem. 209P	21.5	7,800							
			Fed. 209	Win. WAA12F1	21.0	8,200							
				CCI 209M	Win. WAA12F1	21.0	8,400	23.0	7,500				
				Fio. 616	Win. WAA12F1	21.5	7,900	23.0	7,400				
Extra Lite	1½	1,090	Win. 209	Win. WAA12 (White)	16.5	7,800							
				Fed. 12S3	17.5	7,800							
				Rem. Fig. 8	17.0	6,900	18.5	6,700					
				Hornady Versalite	16.5	7,900	18.5	6,700					
				Red PC	17.0	7,500							
			Rem. 209P	Win. WAA12 (White)	16.5	6,700							
				Fed. 209	16.5	7,900	18.5	7,000					
				CCI 209M	Win. WAA12 (White)	17.0	8,000	18.5	7,000				
				Fio. 616	Win. WAA12 (White)	17.0	7,600	18.5	7,100				
2¾	1½	1,145	Win. 209	Win. WAA12 (White)	18.0	8,500	20.5	7,300					
				Fed. 12S3	18.0	8,900							
				Rem. Fig. 8	18.0	8,000	19.5	7,000					
				Hornady Versalite	18.0	8,600	20.0	7,200					
				Red PC	18.5	7,800	20.5	6,800					
			Fed. 209	Win. WAA12 (White)	18.0	8,700	20.0	7,000					
				CCI 209M	Win. WAA12 (White)	18.0	9,000	20.0	7,400				
				Fio. 616	Win. WAA12 (White)	18.5	8,300	20.0	6,800				
				Rem. 209P	Win. WAA12 (White)	18.5	8,100						
3	1½	1,200	Win. 209	Win. WAA12 (White)	19.5	8,900	22.0	8,700	23.0	7,600			
				Fed. 12S3	19.0	9,600	21.5	8,300	23.5	8,300			
				Rem. Fig. 8	19.0	8,700	21.5	8,200	23.0	7,400			
				Hornady Versalite	19.0	9,400	21.5	7,700	23.0	7,700			
				Red PC	19.5	8,400	22.0	7,600	23.5	7,600			
			Rem. 209P	Win. WAA12 (White)	19.5	9,000			23.5	7,900			
				Fed. 209	19.0	9,900	21.5	7,700	23.5	7,900			
				Fio. 616	Win. WAA12 (White)	19.5	9,300	21.5	7,600	23.5	7,200		
3½	1½	1,255	Win. 209	Win. WAA12 (White)	21.0	9,400	23.5	8,800	25.0	8,500			
				Fed. 12S3			23.5	8,600	25.0	8,400			
				Hornady Versalite	21.5	9,700	24.0	8,300	25.0	8,000			
				Red PC	21.0	9,900	23.5	8,000	25.0	7,900			
				Activ T32	21.0	10,100	23.5	8,800	25.0	8,300			
			Rem. 209P	Win. WAA12 (White)	21.5	9,500			25.5	7,700			
				Fed. 209	20.5	10,200	23.5	8,800	25.0	8,400			
				CCI 209M	Win. WAA12 (White)	21.5	10,000	23.0	8,800	25.0	8,500		
				Fio. 616	Win. WAA12 (White)	21.5	10,100	23.0	8,600	25.0	8,000		
3½	1½	1,310	Win. 209	Win. WAA12 (White)			25.5	8,900	26.5	8,600			
				Fed. 12S3			24.5	9,900	26.0	9,400			
				Hornady Versalite	22.5	10,300	25.0	8,900	26.5	9,000			
				Red PC	22.5	10,200	25.5	8,700	26.5	8,600			
				Activ T32			24.5	9,500	26.5	9,000			
			Rem. 209P	Win. WAA12 (White)	22.5	10,200	25.0	8,800	27.0	9,000			
				Fed. 209			24.5	9,400	27.0	8,500			
				CCI 209M	Win. WAA12 (White)	22.0	9,400	25.0	9,000	26.0	8,500		
				Fio. 616	Win. WAA12 (White)	22.5	10,600	24.5	8,900	27.5	9,200		

PC: Pattern Control

## 12-Gauge, 3-in. Winchester-Western Plastic AA-Type Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi	2400 Grains	Approx. psi	
3¾	1¾	1,295	Win. 209	Fed. 12S3			37.5	10,300			
				Rem. RXP12			38.0	9,400			
				Win. WAA12 (White)			37.5	10,000			
4	1¾	1,350		Fed. 12S4			40.0	10,500			
				Rem. SP12			40.5	9,300			
				Win. WAA12F114			39.0	9,900			
4	1½	1,315	Rem. SP12				38.5	10,300			
									50.0	10,000	
4¼	1¾	1,335	Rem. RP12							45.0	9,900
4	1¾	1,245	Rem. RP12								



## 12-Gauge, 2¾-in. Activ Plastic Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Red Dot Approx. psi	American Select Grains	American Select Approx. psi	Green Dot Grains	Green Dot Approx. psi	Unique Grains	Unique Approx. psi	Herco Grains	Herco Approx. psi	Blue Dot Grains	Blue Dot Approx. psi		
2¾	1⅛	1,145	CCI 209	Fed. 12S3	18.5	7,800												
			CCI 209M	Fed. 12S3	17.5	8,100												
			Fed. 209	Fed. 12S3	18.0	8,700												
			CCI 209SC	Claybuster Activ TG30			19.0	7,000										
			Rem. 209P	Claybuster Activ TG30			19.5	8,100										
			Win. 209	Fed. 12S3	18.0	8,500												
				Rem. PT12	17.5	8,300												
				Win. WAA12F1	18.5	7,700												
				Purple PC	18.5	7,400												
				Claybuster Activ TG30			19.0	7,300										
			Fed. 209A	Claybuster Activ TG30			19.5	8,100										
							19.0	8,700										
							19.5	8,500										
3	1⅛	1,200	CCI 209	Fed. 12S3	20.0	8,200												
			CCI 209M	Fed. 12S3	19.5	10,000												
			CCI 209SC	Claybuster Activ TG30			20.5	9,100										
			Fed. 209	Fed. 12S3	19.5	9,600												
			Fed. 209A	Claybuster Activ TG30			20.5	10,100										
			Rem. 209P	Claybuster (Red) Activ TG30			20.5	9,600										
			Win. 209	Fed. 12S3	19.5	10,300												
				Rem. PT12	19.5	9,400												
				Win. WAA12F1	19.5	8,700												
				Purple PC	20.0	8,400												
				Claybuster Activ TG30			20.5	8,600										
							21.0	9,200										
Heavy	1⅛	1,250	Rem. 209P	Activ TG30			22.5	8,900										
				Claybuster (Red)			22.5	10,000										
			Win. 209	Activ TG30			22.0	10,100										
				Claybuster			22.0	9,700										
			CCI 209SC	Activ TG30			22.5	10,600										
3¼	1⅛	1,255		Claybuster			22.0	10,500										
			Fed. 209A	Activ TG30			21.0	9,000										
				Claybuster			21.5	10,800										
3¼	1¼	1,220	CCI 209M	Fed. 12S3					22.0	9,400								
				Win. WAA12 (White)					23.0	8,800								
			CCI 209	Activ T32						23.0	9,300	25.5	8,100					
				Win. WAA12 (White)						23.5	9,000	25.5	8,400					
			CCI 209M	Activ T32							22.0	9,600	24.5	9,000				
3¾	1¼	1,330		Win. WAA12 (White)							22.5	10,000	24.5	9,000				
			Fed. 209	Activ T32							22.5	10,000	24.5	9,200				
				Win. WAA12 (White)							22.5	9,800	24.5	9,500				
			Win. 209	Activ T32							23.0	9,700	24.5	9,000				
				Fed. 12C1								24.5	8,900					
				Rem. RXP12							22.0	9,900	24.5	9,200				
				Win. WAA12 (White)								22.0	10,200	24.0	9,200			
			CCI 209	Fed. 12S4										30.5	9,800	39.5	9,300	
				Activ T32										29.0	10,200			
			Fed. 209	Activ T32										29.5	10,300	37.0	10,100	
				Fed. 12S4														
			Win. 209	Activ T32										27.5	10,200	29.0	9,700	
				Fed. 12S4												39.5	9,000	
				Rem. SP12											28.5	9,800	39.0	8,700
				Win. WAA12F114											28.5	10,300	40.0	8,800

continued on next page

## 12-Gauge, 2¾-in. Activ Plastic Shells (continued)

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	American Select Grains	Green Dot Grains	Unique Grains	Herco Grains	Blue Dot Grains
					Approx. psi	Approx. psi	Approx. psi	Approx. psi	Approx. psi	Approx. psi
3¾	1⅓	1,295	CCI 209	Activ T35 Rem. RP12					30.5	10,300
			CCI 209M	Activ T35 Rem. RP12					29.5	10,500
			Fed. 209	Activ T35 Rem. RP12						40.0
			Win. 209	Activ T35 Rem. RP12						8,500
			Fed. 209	Activ T35						38.5
4	1⅓	1,350	Win. 209	Activ T35						38.0
			Fed. 209	Activ T35						9,700
3½	1½	1,150	CCI 209M	Activ T42 Rem. RP12						37.0
			Fed. 209	Activ T42						10,200
			Rem. 209P	Activ T42						39.0
			Win. 209	Activ T42						9,100
			Fio. 616	Activ T42						38.0
3¾	1½	1,260	CCI 209	Activ T42						9,500
			CCI 209M	Activ T42 Rem. RP12						40.0
			Win. 209	Activ T42 Rem. RP12						10,100
			Fed. 209	Activ T42						39.5
3¼	1⅔	1,115	CCI 209M	Activ T42						10,100
			Fed. 209	Activ T42						34.0
			Win. 209	Activ T42						7,700
			Rem. 209P	Activ T42						34.5
			Fio. 616	Activ T42						8,600

## 12-Gauge, 3-in. Activ Plastic Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Green Dot Grains	Unique Grains	Herco Grains	Blue Dot Grains
					Approx. psi	Approx. psi	Approx. psi	Approx. psi	Approx. psi
3¾	1⅓	1,295	CCI 209M	Fed. 12S3 Rem. RXP12 Win. WAA12 (White)				31.5	10,400
4	1⅓	1,350	CCI 209M	Activ T32 Rem. RXP12 Win. WAA12 (White) Fed. 12S3				31.5	10,000
4	1½	1,315	CCI 209M	Activ T35 Fed. 12S4 Rem. R12H Win. WAA12F114				31.5	10,100
4	1⅔	1,280	CCI 209M	Activ T35 Fed. 12S4 Rem. SP12 Win. WAA12F114				33.5	10,700
4	1⅔	1,245	CCI 209M	Activ T35 Rem. SP12				33.0	10,400
3¾	1⅔	1,155	CCI 209M	Activ T35 Rem. SP12					42.5
3¾	2	1,120	CCI 209M	Rem. RP12					7,900
									40.5
									8,700
									41.5
									8,600
									41.0
									9,200
									40.5
									8,500
									40.0
									9,800
									39.0
									10,000
									39.5
									10,600
									41.5
									10,100
									40.0
									9,900
									40.0
									10,400
									40.0
									10,700
									36.5
									10,000
									37.0
									10,200
									35.0
									10,600

# 12-Gauge, 2¾-in. Fiocchi Plastic Target Shells



Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	American Select Grains	Green Dot Grains	Unique Grains	Herco Grains	Blue Dot Grains				
					Approx. psi	Approx. psi	Approx. psi	Approx. psi	Approx. psi	Approx. psi				
—	7/8	1,200	Fio. 616	Rem. TGT 12 Fed. 12SO Win. WAA12SL Purple PC	17.0* 17.5 17.0* 17.5*	6,900 6,700 6,700 6,400								
—	7/8	1,250	Fio. 616	Rem. TGT 12 Fed. 12SO Win. WAA12SL Purple PC	18.5 19.0 18.5 19.0*	7,000 6,900 6,800 6,700								
—	7/8	1,300	Fio. 616	Fed. 12SO Rem. TGT 12 Win. WAA12SL Purple PC	19.5 20.0 20.0 20.0*	8,800 7,900 8,100 8,600	22.0 22.0 22.5	7,600 7,900 7,700						
2 3/4	1	1,200	Fio. 616	Fed. 12SO Rem. TGT 12 Win. WAA12SL Purple PC	18.0 18.0 18.0 18.0	9,100 8,500 8,500 8,100		20.0 20.0 20.0	8,100 7,400 7,900					
3	1	1,255	Fio. 616	Rem. TGT 12 Win. WAA12SL Purple PC	19.0 19.0 19.0	9,300 9,500 9,500		21.0 21.0 21.0	8,400 8,100 8,200					
3 1/4	1	1,290	Fio. 616	Rem. TGT 12 Win. WAA12SL Purple PC	20.5 20.5 21.0	10,100 10,300 9,800		22.5 22.5 23.0	8,600 9,400 8,400					
Extra Lite	1 1/8	1,090	Fio. 616	Fiocchi FTW1 Fiocchi TL1 Fed. 12S3 Fed. 12C1 Win. WAA12 (White) Win. WAA12SL Rem. Fig. 8 Rem. RXP12 Hornady Versalite Claybuster (Red)	16.5 16.0 17.0 17.0 17.0 17.0 16.0 16.5 16.5	8,100 8,400 7,600 7,300 8,000 8,700 8,100	18.0 17.5	7,400 7,400	18.5 18.5 18.5 18.5 18.5 18.5 18.0	6,800 7,200 6,800 7,000 6,500 6,700 7,100				
2 3/4	1 1/8	1,145	Fio. 616	Fiocchi FTW1 Fiocchi TL1 Fed. 12S3 Fed. 12C1 Rem. Fig. 8 Rem. RXP12 Win. WAA12 (White) Win. WAA12SL Hornady Versalite Windjammer Claybuster (Red)	17.5 18.0 18.0 18.0 18.0 18.0 18.0 17.5 18.5	8,800 9,200 8,800 8,400 8,700 9,000 8,300 9,000 7,400	19.5 19.0	8,500 8,700	20.0 20.0 19.5 20.0 20.0 20.0	7,300 7,500 7,500 7,100 7,200 7,600				
3	1 1/8	1,200	Fio. 616	Fiocchi FTW1 Fiocchi TL1 Fed. 12S3 Fed. 12C1 Rem. Fig. 8 Rem. RXP12 Win. WAA12 (White) Hornady Versalite Windjammer Claybuster (Red)	19.0 19.0 19.0 19.0 19.5 19.5 19.5 18.5 20.0	9,300 9,700 9,500 9,600 9,600 9,700 9,400 9,500 8,600	20.5 20.5	9,200 9,400	21.0 21.5 21.5 21.5 21.5 21.0 21.0 21.0 21.0	7,800 8,400 8,500 8,500 7,900 8,100 8,200 8,200 7,700	23.5 23.5 23.5 23.5 22.5 23.5 24.0 24.0 24.0	7,400 6,900 7,000 7,200 7,200 6,800 7,100 7,100 6,400		
Heavy	1 1/8	1,250	Fio. 616	Fiocchi FTW1 Fiocchi TL1 Fed. 12S3 Fed. 12C1 Rem. Fig. 8 Rem. RXP12 Win. WAA12 (White) Hornady Versalite Windjammer Claybuster (Red)	21.0 20.5 20.5 21.0	10,500 10,700 10,200 9,400	22.0 22.0	10,200 10,300	23.0 22.5 23.0 23.0 22.5	9,200 9,300 8,800 9,200 9,300	24.5 24.5 24.5 23.5 25.5	8,200 8,000 7,600 8,200 7,800	26.0 26.0 26.0 26.0 25.5	8,300 7,500 7,300 7,500 7,700
3 1/2	1 1/8	1,310	Fio. 616	Fed. 12S3 Fed. 12S3 CCI 209M Win. 209					25.0 24.5 24.0 25.0	9,600 10,300 10,000 8,700	27.0 27.0 26.5 26.5	8,600 9,200 8,400 8,300		
3 1/4	1 1/4	1,220	Fio. 616	Fed. 12S4 Fed. 12S4 CCI 209M Win. 209					23.0 23.0 24.5 23.0	9,700 10,000 8,000 10,000	25.0 24.5 25.0 25.0	8,800 9,500 8,400 8,700		

continued on next page

## 12-Gauge, 2¾-in. Fiocchi Plastic Target Shells (continued)

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Approx. psi	American Select Grains	Approx. psi	Green Dot Grains	Approx. psi	Unique Grains	Approx. psi	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi
3½	1¼	1,275	Fio. 616 Fed. 209 CCI 209M Win. 209	Fed. 12S4 Fed. 12S4 Rem. SP12 Win. WAA12F114					27.0	10,300	28.0	9,500				
									26.0	10,100	27.5	9,800				
									27.0	10,000	28.0	8,300				
											28.0	8,400				
3¾	1¼	1,300	Fio. 616  Fed. 209 CCI 209M Win. 209	Fed. 12S4 Rem. SP12 Win. WAA12F114 Fed. 12S4 Rem. SP12 Win. WAA12F114							30.0	9,500	40.0	8,300		
											30.5	8,600	41.0	7,700		
											30.0	9,200	39.5	7,500		
											30.0	10,300	37.0	8,800		
											30.0	9,200	41.0	7,600		
											30.0	10,100	38.5	8,300		
3¾	1⅓	1,295	Fio. 616 Fed. 209 CCI 209M Win. 209	Rem. RP12 Rem. RP12 Rem. RP12 Rem. RP12									38.0	9,100		
													36.0	10,100		
													37.0	9,600		
													38.0	9,500		
4	1⅓	1,350	Fio. 616 Fed. 209 CCI 209M Win. 209	Rem. RP12 Rem. RP12 Rem. RP12 Rem. RP12									41.5	9,400		
													39.0	10,200		
													40.0	10,100		
													40.0	9,900		
3¼	1½	1,150	Fio. 616  Fed. 209 Rem. 209P Win. 209 CCI 209M	Activ T42 Activ T42 Activ T42 Activ T42 Activ T42									32.5	9,000		
													32.5	8,700		
													32.5	8,100		
													33.5	8,300		
													33.5	8,700		
													34.0	8,500		
3½	1½	1,205	Fio. 616 Fed. 209 CCI 209M Win. 209	Rem. RP12 Rem. RP12 Rem. RP12 Rem. RP12									36.5	9,000		
													34.5	8,500		
													33.0	9,500		
													35.5	8,600		
3¾	1½	1,260	Fio. 616 CCI 209M Win. 209	Rem. RP12 Rem. RP12 Rem. RP12									37.5	9,600		
													36.5	10,600		
													36.5	10,300		
3¼	1⅓	1,115	Fio. 616 Fed. 209 Win. 209 Rem. 209P CCI 209M	Activ T42 Activ T42 Activ T42 Activ T42 Activ T42									31.0	9,600		
													31.0	9,300		
													31.0	9,000		
													31.5	8,600		
													31.5	8,900		

PC: Pattern Control

NOTES: \*For each asterisk (\*), add one 20-gauge, 0.135-in. thick card wad to the inside bottom of the shot cup.

Auto-loading shotguns may not function with loads having pressures less than 7,000 psi. It is important to have tight crimps to prevent load efficiencies (pressures) from dropping. The efficiency may also drop when these loads are fired at low temperatures.

## 12-Gauge, 3-in. Fiocchi Plastic Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Green Dot Grains	Approx. psi	Unique Grains	Approx. psi	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi		
3¾	1⅓	1,295	Fio. 616  Win. 209 CCI 209M	Fed. 12S3 Rem. RXP12 Win. WAA12 (White) Fiocchi FTW1 Fed. 12S3 Fed. 12S3					31.5	9,100				
									32.5	8,600				
									31.5	8,900				
									31.0	9,200				
4	1⅓	1,350	Fio. 616  Win. 209 CCI 209M	Fed. 12S4 Rem. SP12 Win. WAA12F114 Activ T32 Fed. 12S4 Fed. 12S4					32.0	10,700				
									32.5	10,100				
									32.5	10,700				
									32.5	10,300				
4	1½	1,315	Fio. 616  Win. 209 CCI 209M	Fed. 12S4 Rem. SP12 Win. WAA12F114 Activ T35 Fed. 12S4 Fed. 12S4							38.5	10,100		
											38.0	10,400		
4	1½	1,315	Fio. 616  Win. 209 CCI 209M	Fed. 12S4 Rem. SP12 Win. WAA12F114 Activ T35 Fed. 12S4 Fed. 12S4							39.0	10,300		
											39.0	9,700		
											39.0	9,400		
											39.0	9,000		
4	1⅓	1,280	Fio. 616  CCI 209M	Fed. 12S4 Rem. SP12 Win. WAA12F114 Activ T35							39.0	10,600		
											38.0	10,400		
4	1¾	1,245	Fio. 616	Activ T35							39.0	10,700		
3¾	1⅓	1,155	Fio. 616	Rem. RP12 Activ T35							39.5	9,700		
											38.5	10,500		
											39.0	10,500		
											37.5	10,300		
											34.5	10,700		
											34.5	10,300		



## Additional 12-Gauge 2 3/4-in., 1-oz. Target Loads

Shell	Dram Equiv.	Velocity (fps)	Primer	Wad	Bullseye		Red Dot		Green Dot		
					Grains	Approx. psi	Grains	Approx. psi	Grains	Approx. psi	
Federal Paper Target	2 3/4	1,200	Fed. 209A	Fed. 12SO	18.5	7,800	19.0	8,000			
				Fed. 12S3	18.5*	8,500	18.5	7,400			
				Rem. PT12	18.0	6,200	18.0	7,500			
				Rem. R12L	18.5*	7,800	18.5	7,100			
				Rem. RXP12	18.5*	7,600	19.0	7,200			
				Win. WAA12F1	18.0*	7,500	18.5*	8,100			
				Win. WAA12 (White)	18.5*	8,700	18.5	7,800			
				Pacific Versalite	18.5*	8,500	18.0	7,300			
				Lage Uniwad	19.0*	8,600	19.0	7,100			
				Windjammer	19.0*	7,300	19.0*	7,400			
				Purple PC	19.0	6,400	19.0	7,100			
			CCI 209	Fed. 12SO	18.5	7,600	19.0	7,600			
			CCI 209M	Purple PC	18.0	6,900	18.5	6,600			
			Rem. 209	Purple PC	18.5	6,200	18.0	7,800			
			Win. 209	Purple PC	19.0	7,100	19.0	7,200			
Federal Gold Medal	2 3/4	1,200	Fed. 209A	Fed. 12SO	18.0	7,600	18.0	7,900	21.0	7,100	
				Rem. PT12			18.5	7,500	21.0	6,100	
				Rem. RXP12	17.5*	9,000	18.0*	8,700	20.0	7,600	
				Win. WAA12 (White)	17.5**	9,500	18.0*	8,500	20.0*	8,200	
				Win. WAA12F1	18.5*	7,600	18.0*	8,400	21.0	7,200	
				Purple PC	19.0	5,700	18.5	6,900			
			CCI 209	Fed. 12SO	19.0	8,400	19.0	7,600			
			CCI 209M	Purple PC			18.0	6,900			
			Rem. 209	Purple PC	18.5	5,600	18.5	7,200	20.5	6,100	
			Win. 209	Purple PC			18.5	6,700			
Rem. Premier Plastic Target	2 3/4	1,200	Rem. 209P	Rem. Fig. 8	17.0	7,100	18.0	8,400	20.0	6,500	
				Fed. 12SO	17.5	7,800	18.0	8,800	19.5	7,200	
				Win. WAA12F1	17.5	6,900	18.0	7,800	19.0	6,200	
				Purple PC	18.0	6,900	18.5	7,700	20.5	6,200	
				Pacific Versalite	17.0	7,500	17.5	8,600	20.0	6,600	
				CCI 209M	Rem. Fig. 8	17.0	8,300	17.5	8,900	18.5	7,700
				Fed. 209	Rem. Fig. 8	17.5	7,500	18.0	8,400	20.0	7,200
				Win. 209	Rem. Fig. 8	17.5	7,900	18.0	7,100	20.0	7,100
Peters Target (Blue Magic)	2 3/4	1,200	Rem. 209	Purple PC	17.5	7,200	17.5	8,300	19.0	7,300	
				Fed. 12SO	18.0	10,300	18.0	9,400			
				Fed. 12S3	18.5*	8,500	18.0*	8,600	19.5	7,300	
				Rem. R12L	17.5*	8,300	18.0*	8,000	20.0	7,100	
				Rem. RXP12	17.5*	8,800	18.0*	8,400	20.0	7,500	
				Win. WAA12 (White)	17.5*	9,900	18.0*	9,100	19.5	7,500	
				Win. WAA12F1	18.0	8,700	18.0	8,500	21.0	7,500	
				Lage Uniwad	18.0*	9,600	18.0*	8,600	20.5	6,700	
				Windjammer	18.0*	8,700	19.0*	8,300			
				CCI 209M	Rem. R12L	17.5	9,000	18.0	8,800		
				Purple PC	17.0	7,400	17.5	8,000	19.5	7,000	
				Fed. 209	Purple PC	18.0	6,300	18.5	8,400	20.0	6,400
				Win. 209	Purple PC	18.0	6,800	18.0	7,700		
Winchester-Western AA	2 3/4	1,200	Win. 209	Fed. 12SO	18.0	9,600	18.0	9,600	19.5	8,400	
				Fed. 12S3	17.5*	8,700	18.0	8,400			
				Rem. R12L	18.0*	8,800	18.0	7,600	20.0	7,100	
				Rem. RXP12	17.5	8,800	18.0	8,300	20.0	7,100	
				Win. WAA12 (White)	17.5*	9,900	18.0	8,800	19.5	7,500	
				Win. WAA12F1	18.0**	9,500	18.0	9,000	20.0	7,600	
				Lage Uniwad	17.5*	8,900	18.0	8,000	20.5	7,400	
				Windjammer	18.0**	9,500	18.0*	9,100	20.0	7,600	
				Purple PC	17.5	7,300	17.5	8,800	19.5	6,900	
				CCI 209	Purple PC	18.0	7,300	18.5	7,800	21.0	6,300
CCI 209M	2 3/4	1,200	Win. 209	Win. WAA12 (White)			17.5	9,900			
				Purple PC	17.5	7,900	17.5	8,500	19.0	6,600	
				Fed. 209	Purple PC	17.5	7,600	17.5	8,900	19.0	7,200
				Rem. 209	Purple PC	17.5	7,400	17.5	8,600	19.0	7,700

PC: Pattern Control

NOTE: \*For each asterisk (\*), add one 20-gauge, 0.135-in. thick card wad to the inside bottom of the shot cup.



## 28-Gram International Target Loads with 12-Gauge, 2¾-in. Federal Gold Medal Plastic Target Shells

Dram Equiv.	Velocity (fps)	Primer	Wad	Red Dot Grains	Red Dot Approx. psi	Green Dot Grains	Green Dot Approx. psi	Unique Grains	Unique Approx. psi	Herco Grains	Herco Approx. psi	Blue Dot Grains	Blue Dot Approx. psi
3½	1,345	Fed. 209A	Fed. 12SO Rem. Fig. 8 Win. WAA12SL Purple PC	23.0 22.5 22.5 23.0	9,900 9,500 9,600 8,800	24.5 25.0 24.5 25.0	9,100 8,400 8,400 8,200	27.5	7,400				

PC: Pattern Control

## 28-Gram International Target Loads with 12-Gauge, 2¾-in. Remington Premier Plastic Target Shells

Dram Equiv.	Velocity (fps)	Primer	Wad	Red Dot Grains	Red Dot Approx. psi	Green Dot Grains	Green Dot Approx. psi	Unique Grains	Unique Approx. psi	Herco Grains	Herco Approx. psi	Blue Dot Grains	Blue Dot Approx. psi
3½	1,345	Rem. 209P	Rem. Fig. 8 Fed. 12S3 Win. WAA12SL Purple PC	21.5 21.5	10,600 10,600	23.0 23.0 23.0 24.0	9,700 10,300 10,100 9,900	26.0 27.0 27.0 27.0	8,300 8,500 8,500 7,800				

PC: Pattern Control

## 28-Gram International Target Loads with 12-Gauge, 2¾ Winchester-Western Plastic AA-Type Shells

Dram Equiv.	Velocity (fps)	Primer	Wad	Red Dot Grains	Red Dot Approx. psi	Green Dot Grains	Green Dot Approx. psi	Unique Grains	Unique Approx. psi	Herco Grains	Herco Approx. psi	Blue Dot Grains	Blue Dot Approx. psi
3½	1,345	Win. 209	Win. WAA12SL Rem. Fig. 8 Fed. 12S3 Purple PC			22.5 23.0	10,600 9,500	25.5 25.0 25.5 26.5	10,200 9,600 9,500 8,700				

PC: Pattern Control

## 28-Gram International Target Loads with 12-Gauge, 2¾ Fiocchi Plastic Target Shells

Dram Equiv.	Velocity (fps)	Primer	Wad	Red Dot Grains	Red Dot Approx. psi	Green Dot Grains	Green Dot Approx. psi	Unique Grains	Unique Approx. psi	Herco Grains	Herco Approx. psi	Blue Dot Grains	Blue Dot Approx. psi
3½	1,345	Fio. 616	Fed. 12S3 Rem. Fig. 8 Win. WAA12SL Purple PC	22.0 21.5 21.5 22.5	9,600 9,700 10,400 9,500	24.0 24.0 24.0 24.0	8,800 8,800 8,800 8,800	26.5 27.0	7,500 7,700				

PC: Pattern Control



## 16-Gauge, 2¾-in. Federal Plastic Hi Power Shells with Paper Base Wad

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Approx. psi	Green Dot Grains	Approx. psi	Unique Grains	Approx. psi	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi
2¾	1	1,220	Fed. 209A	Win. WAA16 Activ G28			19.0	9,800	21.0	8,400	21.5	8,100		
							18.5	9,300	21.5	8,200	21.5	8,000		
3	1	1,275	Fed. 209A	Win. WAA16 Activ G28					23.0	8,800	23.5	8,700		
									23.0	9,000	23.5	8,500		
2¾	1⅓	1,185	Fed. 209A	Rem. SP16 Win. WAA16			19.0	10,600	21.5	8,900	22.0	9,100		
							18.5	10,200	21.0	8,700	22.0	9,100		
3	1⅓	1,240	Fed. 209A	Rem. SP16 Win. WAA16					22.5	9,600	23.5	10,100		
									22.0	10,200	24.0	10,200		
3¼	1⅓	1,295	Fed. 209A	Rem. SP16							24.5	10,300	32.0	8,600
3¼	1¼	1,260	Fed. 209A	Rem. SP16									30.5	10,200

## 16-Gauge, 2¾-in. Remington-Peters SP Plastic Shells with Plastic Base Wad

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Approx. psi	Green Dot Grains	Approx. psi	Unique Grains	Approx. psi	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi
2½	1	1,165	Rem. 209P	Win. WAA16 Activ G28			16.5	10,200	19.0	8,600				
							17.5	9,700	19.5	8,400				
2¾	1	1,220	Rem. 209P	Win. WAA16 Activ G28					20.0	9,400	21.0	9,700		
									20.5	8,600	21.0	8,900		
3	1	1,275	Rem. 209P	Win. WAA16 Activ G28					21.0	10,200	22.0	9,600		
									21.0	10,200	22.0	9,800		
2¾	1⅓	1,185	Rem. 209P	Win. WAA16 Activ G28					20.0	10,300	21.0	10,600		
									20.5	10,700	21.0	10,500		
3	1⅓	1,240	Rem. 209P	Rem. SP16									27.0	9,900

## 16-Gauge, 2¾-in. Winchester AA-Type Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Approx. psi	Green Dot Grains	Approx. psi	Unique Grains	Approx. psi	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi
2½	1	1,165	Win. 209	Win. WAA16 Activ G28			17.5	10,300	19.0	9,200				
									19.0	9,100				
2¾	1	1,220	Win. 209	Win. WAA16 Activ G28					19.5	10,500	20.0	10,200		
									20.0	10,100				
3	1	1,275	Win. 209	Rem. SP16									29.0	9,300
2¾	1⅓	1,185	Win. 209	Rem. SP16									27.0	10,000

## 16-Gauge 2¾-in. Fiocchi Plastic Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Approx. psi	Green Dot Grains	Approx. psi	Unique Grains	Approx. psi	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi
2½	1	1,165	Fio. 616	Win. WAA16 Activ G28	15.5	10,400	17.5	9,400	19.0	8,100				
					17.0	10,000	18.0	8,200	19.5	7,900				
2¾	1	1,220	Fio. 616	Activ G28 Win. WAA16			18.0	10,500	20.0	9,000	21.0	8,500		
									20.5	8,800	21.0	8,900		
3	1	1,275	Fio. 616	Activ G28 Win. WAA16					21.5	9,600	22.0	9,000		
									21.0	9,900	22.0	9,600		
2¾	1⅓	1,185	Fio. 616	Win. WAA16 Rem. SP16					19.5	10,600	21.0	10,200		
									20.5	9,900				
3	1⅓	1,240	Fio. 616	Rem. SP16							23.5	10,700	31.0	8,900
3¼	1⅓	1,295	Fio. 616	Rem. SP16									32.5	9,200



## 16-Gauge 2¾-in. Activ All-Plastic Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Approx. psi	Green Dot Grains	Approx. psi	Unique Grains	Approx. psi	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi
2½	1	1,165	CCI 209	Activ G28	16.5	10,100	18.0	9,200	20.0	7,900				
2¾	1	1,220	CCI 209	Activ G28 Win. WAA16			19.5	9,800	21.5	8,700	23.0	8,500		
3	1	1,275	CCI 209	Activ G28 Win. WAA16			19.5	9,700	21.5	8,300	22.5	8,000		
2¾	1½	1,185	CCI 209	Win. WAA16 Rem. SP16					23.0	9,100	24.5	8,700		
3	1½	1,240	CCI 209	Win. WAA16 Rem. SP16					22.5	8,700	24.0	9,000		
3¼	1½	1,295	CCI 209M	Rem. SP16					20.5	9,200	22.0	9,400		
3¼	1¼	1,260	CCI 209M	Rem. SP16					21.5	9,200	22.0	8,800		
									22.0	10,000	23.0	10,200		
									22.5	10,200	24.0	9,400		
													31.0	9,100
													30.0	10,000

## 20-Gauge, 2¾-in. Federal Paper Target Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Approx. psi	Green Dot Grains	Approx. psi	Unique Grains	Approx. psi	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi
2¼	¾	1,200	Fed. 209	Fed. 20S1 Rem. RXP20 Win. WAA20	12.5**	11,400	14.0	9,700	15.5	9,200				
			CCI 109	Fed. 20S1 Rem. RXP20 Win. WAA20	13.5**	10,500	14.0	10,200	16.0	8,100				
					13.0**	10,500	14.0	8,800	15.5	9,200				
						15.0	10,900		17.0	8,900		17.0	6,800	
2½	⅞	1,155	Fed. 209	Fed. 20S1 Rem. RXP20 Win. WAA20	14.0	11,400	15.0	9,900	15.5	9,000				
			CCI 109	Fed. 20S1 Rem. RXP20 Win. WAA20	14.5	10,100	14.5	10,200	15.5	9,200				
					14.0	10,000	14.5	9,500	15.0	8,800				
			CCI 209M	Fed. 20S1	14.5	8,900	15.0	8,700	15.0	8,000				
					14.0	8,400	14.5	8,400	15.0	8,000				
Skeet	⅞	1,200	Fed. 209	Fed. 20S1 Rem. RXP20 Win. WAA20	14.5	9,800	15.0	9,600	15.5	9,400				
			CCI 109	Fed. 20S1 Rem. RXP20 Win. WAA20	15.5	10,900	15.0	9,900	16.5	9,800				
					15.0	9,700	15.5	9,700	16.0	9,200				
			CCI 209M	Fed. 20S1	15.0	9,000	15.5	9,000	17.0	8,400				
					16.0	9,900	16.0	9,900	17.0	8,500				
					15.5	8,800	15.5	8,800	17.0	8,500				
2½	1	1,165	Fed. 209	Rem. RXP20 Rem. SP20 Win. WAA20 Win. WAA20F1	15.0	10,500	15.0	10,500	17.0	9,900	17.0	9,600		
											17.0	11,500		
											16.5	11,500		
											16.0	11,200		
											16.5	11,300		

NOTE: For each asterisk (\*), add one 20-gauge, 0.135-in. thick card wad to the inside bottom of the shot cup.



## 20-Gauge, 2¾-in. Federal Plastic Target Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Approx. psi	Green Dot Grains	Approx. psi	Unique Grains	Approx. psi	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi	
2½	¾	1,200	Fed. 209	Fed. 20S1 Rem. RXP20 Win. WAA20 Windjammer*	13.0*** 13.0*** 13.0*** 14.0	10,100 9,400 10,300 9,300	15.0* 15.0* 15.0* 15.5	9,000 8,600 8,900 8,700	15.0** 16.0** 16.0** 17.0	9,000 8,600 8,200 7,500					
2½	⅞	1,155	Fed. 209	Hornady Versalite Windjammer Lage Uniwad Win. WAA20			15.5 15.0 16.0 14.5	10,000 10,000 10,100 9,700	16.5	8,600					
			CCI 109	Fed. 20S1 Rem. RXP20 Win. WAA20 Lage Uniwad			14.5	8,400 8,000 8,700 9,100	16.0	8,600 8,300 8,700					
			CCI 209M	Fed. 20S1											
Skeet	⅞	1,200	Fed. 209	Windjammer Lage Uniwad Fed. 20S1 Hornady Versalite			16.0 16.5 16.5 16.0	10,900 11,000 10,600 10,500	17.0	10,600	18.5	10,200			
			Fed. 209A	PC 20			16.0	11,200	18.0	9,800	18.0	9,200			
			CCI 109	Fed. 20S1 Rem. RXP20 Win. WAA20 Lage Uniwad			15.5 16.0 15.5 16.0	9,400 9,600 9,100 10,000	17.0 17.0 17.0 18.0	8,500 9,200 8,500 8,800	17.0	9,300 18.0 17.0	9,100		
			CCI 209M	Fed. 20S1			16.5	9,300	17.0	9,100	17.5	7,600			
2½	1	1,165	Fed. 209	SP20 Rem. RXP20 Win. WAA20F1					16.0	10,800	17.0	9,600 17.0	11,300		
									15.5	11,300	16.5	11,100			
2¾	1	1,220	Fed. 209	Rem. SP20 Win. WAA20F1									24.0	10,200	
			CCI 209M	Fed. 20S1									24.0	10,100	
2¾	1⅛	1,175	Fed. 209	Rem. SP20									23.0	10,900	

NOTE: For each asterisk (\*), add one 28-gauge, 0.135-in. thick card wad or one 0.135-in. thick .410 bore card wad to the inside bottom of the shot cup.

## 20-Gauge 3-in. Federal Plastic Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Approx. psi	Green Dot Grains	Approx. psi	Unique Grains	Approx. psi	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi
3	1⅓	1,255	Fed. 209	Win. WAA20 Rem. RXP20									26.5	9,400
													27.0	9,200
3¼	1⅓	1,310	Fed. 209	Rem. RXP20 Win. WAA20 Fed. 20S1									28.0	10,200
													28.5	10,600
													28.0	10,300
3	1⅓	1,230	Fed. 209	Rem. SP20*									26.5	10,300
				Win. WAA20F1									26.0	10,100
3	1¼	1,185	Fed. 209	Rem. SP20*									25.5	10,600
				Win. WAA20F1									25.5	10,400

NOTE: For each asterisk (\*), add one 28-gauge, 0.135-in. thick wad to the inside bottom of the shot cup.



## 20-Gauge, 2¾-in. Remington Premier Plastic Target Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Approx. psi	Green Dot Grains	Approx. psi	Unique Grains	Approx. psi	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi
2¼	¾	1,200	Rem. 209P	Rem. RXP20** Win. WAA20** Fed. 20S1** Hornady Versalite** Windjammer** Lage Uniwad**	13.0 13.0 13.0 13.5 13.0 13.5	10,700 11,500 10,600 11,500 11,200 11,100	14.0 14.0 14.0 14.5 14.0 14.0	10,000 10,500 10,000 10,000 10,300 9,800	15.5 15.5 15.5 16.0 15.5 15.5	8,700 8,900 8,400 8,900 8,900 8,600				
2½	⅞	1,155	Rem. 209P	Rem. RXP20 Fed. 20S1 Win. WAA20 Hornady Versalite Windjammer Lage Uniwad			14.5 14.0 14.0 14.0 14.0 14.0	11,500 11,100 11,500 11,200 11,400	15.5 15.5 15.5 15.5 15.5	10,000 10,000 10,200 9,700 9,900 10,000	16.5 16.0 16.0 16.0 16.0 16.0	10,000 10,000 9,500 9,600 9,500 9,600		
			Fed. 209	Rem. RXP20					15.5	10,700	16.5	10,500		
			Win. 209	Rem. RXP20					15.5	10,300	16.5	10,200		
			Fio. 616	Rem. RXP20					16.0	10,700	16.5	10,100		
			CCI 209M	Rem. RXP20					15.5	11,000	16.5	10,500		
			CCI 209	Rem. RXP20					14.5	10,900	16.0	9,500	16.5	8,900
Skeet	⅞	1,200	Rem. 209P	Rem. RXP20 Fed. 20S1 Win. WAA20 Hornady Versalite Windjammer Lage Uniwad PC 20					16.5 16.5 16.5 16.5 16.5 16.5 14.5	10,700 10,800 10,900 10,200 10,400 10,400 11,200	17.0 17.0 17.0 17.5 17.0 17.5 17.0	10,600 10,500 10,700 10,400 10,100 10,300 10,200		
			Fed. 209	Rem. RXP20					16.5	11,300	17.0	11,000		
			Win. 209	Rem. RXP20					16.5	11,300	17.0	10,600		
			Fio. 616	Rem. RXP20					16.5	11,200	17.0	10,700		
			CCI 209M	Rem. RXP20					16.0	11,300	17.0	10,800		
			CCI 209	Rem. RXP20					16.5	9,900	17.5	9,400		
2½	1	1,155	Rem. 209F	Rem. SP20 Win. WAA20F1							17.5	11,500	21.5	9,000
			Fed. 209	Rem. SP20									21.5	9,000
			Win. 209	Rem. SP20									20.5	11,300
			Fio. 616	Rem. SP20									21.5	10,600
			CCI 209M	Rem. SP20									22.5	9,800
			CCI 209	Rem. SP20									21.5	10,500
2¾	1	1,220	Rem. 209P	Rem. SP20 Win. WAA20F1									22.0	9,500
			Win. 209	Rem. SP20									24.0	11,100
			Fio. 616	Rem. SP20									23.5	10,900
			CCI 209M	Rem. SP20									22.0	11,100
			CCI 209	Rem. SP20									23.5	11,000
2¾	1⅓	1,175	Rem. 209P	Rem. SP20 Win. WAA20F1									22.5	10,900
													23.0	10,300
													22.0	11,300
													22.0	11,500

NOTE: For each asterisk (\*), add one 0.135-in. .410-bore card to the inside bottom of the shot cup.



## 20-Gauge, 2¾-in. Remington-Peters RXP Plastic Target Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Approx. psi	Green Dot Grains	Approx. psi	Unique Grains	Approx. psi	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi
2½	¾	1,200	Rem. 97★	Rem. RXP20 Fed. 20S1 Win. WAA20	12.5** 12.5* 12.5*	11,300 11,400 11,400	13.5* 13.5 13.5	10,400 11,100 10,400	15.5 15.5 15.0	9,900 9,900 9,400				
2½	⅞	1,155	Rem. 97★	Fed. 20S1 Rem. RXP20 Win. WAA20 Lage Uniwad			13.0 14.0 13.5	11,500 11,300 11,400						
			CCI 109	Fed. 20S1 Rem. RXP20 Win. WAA20 Lage Uniwad			13.5 14.0 14.0 14.5	11,100 10,500 10,700 11,300	15.5	10,800				
Skeet	⅞	1,200	Rem. 97★	Fed. 20S1 Rem. RXP20 Win. WAA20 Lage Uniwad					16.0 16.0 16.0 16.0	10,500 9,700 10,700 10,900	17.0 17.0	10,600 10,600		
			CCI 109	Fed. 20S1 Rem. RXP20 Win. WAA20 Lage Uniwad			14.5	10,900	16.0	10,500	17.0 17.0 16.5	11,300 9,900 10,400		
			CCI 209M	Rem. RXP20			15.5	11,400	16.0	10,800 10,400 10,500	16.5	10,400 10,700		
2½	1	1,165	Rem. 97★	Fed. 20S1 Rem. RXP20 Win. WAA20					15.5 16.0 15.5	10,800 10,600 11,200				
2¾	1	1,220	Rem. 97★	Rem. RXP20							18.0	11,000		

\*NOTE: For each asterisk (\*), add one 28-gauge, 0.135-in. thick card wad to the inside bottom of the shot cup.

## 20-Gauge, 2¾-in. Remington-Peters Unibody Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Green Dot Grains	Approx. psi	Unique Grains	Approx. psi	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi	2400 Grains	Approx. psi
Skeet	⅞	1,200	Rem. 209	Rem. RXP20 Win. WAA20 Hornady Versalite			16.5 16.5	10,800 11,200	16.5	10,200				
			Fed. 209	Rem. RXP20			16.0	11,500	16.5	10,700				
			CCI 209M	Rem. RXP20			16.5	10,900	17.5	11,300				
			Win. 209	Rem. RXP20			17.5	10,900						
2½	1	1,165	Rem. 209	Rem. SP20 Win. WAA20F1							21.0 21.5	11,500 11,100		
			Fed. 209	Rem. SP20							21.5	10,500		
			CCI 209M	Rem. SP20							22.0	10,500		
			Win. 209	Rem. SP20							22.0	11,300		
2¾	1	1,220	Fed. 209	Activ W32									29.5	10,500

## 20-Gauge, 2¾-in. Remington SP with Plastic Base Wad

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Approx. psi	Green Dot Grains	Approx. psi	Unique Grains	Approx. psi	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi
Skeet	⅞	1,200	Rem. 209	Rem. RXP20 Win. WAA20					16.5 16.5	9,100 9,800				
2½	1	1,165	Rem. 209	Rem. SP20 Win. WAA20F1							17.5 17.5	11,300 10,700		
2¾	1	1,220	Rem. 209	Rem. SP20 Win. WAA20F1									23.0 24.0	10,300 10,100



## 20-Gauge, 2¾-in. Winchester-Western Plastic Xpert Ranger Shells (Polyformed Shell)

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Approx. psi	Green Dot Grains	Approx. psi	Unique Grains	Approx. psi	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi
2¼	7/8	1,155	Win. 209	Fed. 20S1 Win. WAA20					14.5	9,700				
Skeet	7/8	1,200	Win. 209	Fed. 20S1 Rem. RXP20 Win. WAA20					15.5	10,800				
2½	1	1,165	Win. 209	Rem. RXP20					15.5	9,700				
									15.5	10,700				
									16.0	11,100				

## 20-Gauge, 2¾-in. Winchester-Western Plastic AA-Type Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Approx. psi	Green Dot Grains	Approx. psi	Unique Grains	Approx. psi	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi
2¼	3/4	1,200	Win. 209	Win. WAA20 Fed. 20S1 Rem. RXP20	12.0**	10,900	14.0*	10,800	15.5*	9,100				
2¼	7/8	1,155	Win. 209	Fed. 20S1 Rem. RXP20 Win. WAA20 Lage Uniwad PC20	12.0**	11,100	14.0*	9,900	15.5	9,700				
				CCI 109	12.5**	10,800	14.0*	10,200	15.5*	9,900				
Skeet	7/8	1,200	Win. 209	Fed. 20S1 Rem. RXP20 Win. WAA20 PC20			14.0	10,300	15.0	10,100				
				CCI 109			14.5	9,900	15.0	8,700				
				CCI 209M			14.0	10,300	15.0	9,800				
				CCI 209M			14.0	11,400	15.5	10,500				
				CCI 209M			13.5	11,200						
				Win. WAA20			14.0	9,500	15.5	9,600				
				CCI 209M			14.5	9,300	15.5	7,800				
				Win. WAA20			14.0	10,000	15.5	9,200				
				Lage Uniwad			14.0	10,900	16.0	10,100				
				PC20			15.0	10,900	16.0	10,200				
2½	1	1,165	Win. 209	Rem. RXP20 Rem. SP20 Win. WAA20			14.5	10,300	15.5	10,400	16.5	10,700		
2¾	1	1,220	Win. 209	Rem. RXP20 Rem. SP20 Win. WAA20F1			15.0	10,000	16.0	9,000	16.5	9,000		
				CCI 109			14.5	10,600	16.0	10,500	16.5	9,600		
				CCI 109			14.5	10,500	16.0	10,000	16.5	10,200		
				CCI 209M			15.0	10,000	16.0	9,900	16.5	8,800		
				Win. WAA20			14.5	10,300	16.0	10,700	16.5	10,200		
				CCI 209M			16.5	10,800			17.5	10,000		
				Win. WAA20							16.5	9,600		
				Win. WAA20							16.5	10,000		
				PC20							16.5	10,400		
				Win. WAA20F1							23.0	11,300		
				Win. WAA20							23.5	11,400		
				PC20							23.0	11,500		

## 20-Gauge, 3-in. Winchester-Western Plastic AA-Type Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi	2400 Grains	Approx. psi
3	1 1/16	1,255	Win. 209	Rem. SP20			26.0	10,600		
3	1 1/8	1,230	Win. 209	Win. WAA20F1 Rem. SP20			25.5	11,100		
				Rem. SP20			25.5	11,000		
2 3/4	1 1/4	1,135	Win. 209	Win. WAA20F1 Rem. SP20			23.0	10,200		
				Rem. SP20			24.0	10,900		
3	1 1/4	1,190	Win. 209	Rem. SP20			25.0	11,500		
3 1/4	1 1/4	1,240	Win. 209	Rem. SP20					34.5	9,600



## 20-Gauge, 2¾-in. Activ Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Red Dot Approx. psi	Green Dot Grains	Green Dot Approx. psi	Unique Grains	Unique Approx. psi	Herco Grains	Herco Approx. psi	Blue Dot Grains	Blue Dot Approx. psi
Skeet	7/8	1,200	CCI 209M	Fed. 20S1							18.0	9,500		
				Hornady Versalite							18.0	9,800		
				Win. WAA20							18.0	9,500		
				Rem. RXP20							18.5	9,500		
				Win. 209	Hornady Versalite						18.5	9,300		
	2½	1	1,165	Fed. 209	Hornady Versalite						18.0	9,300		
				Rem. 209	Hornady Versalite						18.0	9,500		
				Hornady Versalite							18.0	9,500		
				Rem. RXP20							16.5	10,000		
				Rem. 209	Activ W28						17.5	10,300		
				Win. 209	Activ W28						18.0	11,300		

## 20-Gauge, 2¾-in. Fiocchi Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Red Dot Approx. psi	Green Dot Grains	Green Dot Approx. psi	Unique Grains	Unique Approx. psi	Herco Grains	Herco Approx. psi	Blue Dot Grains	Blue Dot Approx. psi
2½	7/8	1,155	Fio. 616	Fed. 20S1			15.0	9,100	17.0	9,100				
				Hornady Versalite			15.5	9,700	18.0	8,300				
				Lage Uniwad			15.5	9,500	17.5	8,600				
				Fed. 209	Fed. 20S1		14.5	11,100	15.5	10,000				
				Rem. 209	Fed. 20S1		14.5	10,000	16.0	9,400				
	Skeet	7/8	1,200	Win. 209	Fed. 20S1		14.5	10,600	16.5	9,000				
				CCI 209M	Fed. 20S1		14.5	10,500	16.0	9,200				
				Fio. 616	Fed. 20S1		14.5	10,400	16.0	9,500				
				Fio. 615	Fed. 20S1		16.0	10,900	18.0	9,700	18.0	9,200		
				Rem. RXP20			16.5	10,300	19.0	8,500	19.0	8,700		
2¾	1	1,220	Fio. 615	Win. WAA20			16.0	10,800	17.5	9,600	18.5	8,700		
				Hornady Versalite			16.0	10,000	16.0	9,000	19.0	8,300		
				Lage Uniwad			17.5	8,200	19.0	8,000				
				Fio. 616	Fed. 20S1		15.5	10,600	17.5	10,000	18.0	9,200		
				Fed. 209	Fed. 20S1		15.5	11,100	17.0	10,800	17.5	10,200		
3	1	1,275	Fio. 616	Win. 209	Fed. 20S1		16.0	10,400	16.0	10,100	18.0	9,900		
				Rem. 209	Fed. 20S1		15.5	10,800			16.5	9,900		
				CCI 209M	Fed. 20S1		15.5	10,700	17.0	10,000	17.0	9,900		
2¾	1 1/8	1,175	Fio. 616	Rem. SP20									24.5	10,300
				Fio. 615	Rem. SP20								27.5	9,200
				Fed. 209	Rem. SP20								23.0	10,300
				Rem. 209	Rem. SP20								22.5	10,600
				CCI 209M	Rem. SP20								24.0	10,700
3	1	1,275	Fio. 616	Rem. SP20									26.0	10,800
				Fed. 209	Rem. SP20								25.0	10,300
				Win. 209	Rem. SP20								26.0	10,600
2¾	1 1/8	1,175	Fio. 616	Rem. SP20									23.5	10,000
				Fed. 209	Rem. SP20								23.5	10,700
				Win. 209	Rem. SP20								23.5	11,400

## 28-Gauge, 2¾-in. Federal Plastic Target Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Red Dot Approx. psi	Green Dot Grains	Green Dot Approx. psi	Unique Grains	Unique Approx. psi	Herco Grains	Herco Approx. psi	Blue Dot Grains	Blue Dot Approx. psi
Skeet	3/4	1,200	Fed. 209	Fed. 28S1A			12.5	11,800	13.5	11,600	14.0	11,700	17.5	9,600
				Rem. SP28					13.0	11,200	13.0	10,100	18.0	9,900
				Win. WAA28			13.0	10,000	13.5	10,500	14.0	10,900	17.5	8,700
				CCI 109	Rem. SP28				14.0	10,400	14.5	10,000	18.5	9,800
2½	3/4	1,295	Fed. 209	Rem. SP28									20.0	10,900



## 28-Gauge, 2¾-in. Remington-Peters Plastic Target Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Approx. psi	Green Dot Grains	Approx. psi	Unique Grains	Approx. psi	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi
Skeet	3/4	1,200	Rem. 209P	Fed. 28S1A Rem. SP28 Win. WAA28			12.0	10,500	13.5	11,300	14.5	11,200	18.0	9,200
			CCI 109	Fed. 28S1A Rem. SP28 Win. WAA28			13.0	11,800	14.0	10,900	14.5	10,700	18.5	10,100
							12.0	10,200	13.0	9,100	14.0	8,900	18.0	7,500
							12.0	10,400	13.0	9,100	14.0	8,300	18.0	7,300
2 1/4	3/4	1,295	Rem. 209P	Rem. SP28					15.0	10,600	16.5	10,300	21.0	9,700

## 28-Gauge, 2¾-in. Winchester-Western Plastic AA-Type Shells

Dram Equiv.	Shot Wt. (ounces)	Velocity (fps)	Primer	Wad	Red Dot Grains	Approx. psi	Green Dot Grains	Approx. psi	Unique Grains	Approx. psi	Herco Grains	Approx. psi	Blue Dot Grains	Approx. psi
Skeet	3/4	1,200	Win. 209	Win. WAA28			12.5	11,900	13.0	9,400	14.0	8,400		
			CCI 109	Win. WAA28			13.0	8,400	14.0	7,900				

## .410 Bore 2½-in. Plastic Shells

Shell	Shot Weight (ounces)	Velocity (fps)	Primer	Wad	2400		
					Grains	Approx. psi	Grains
Federal	1/2	1,200	Fed. 209	Fed. 410SC Rem. SP410 Win. WAA41		13.5	11,900
			Fed. 410	Fed. 410SC		13.0	11,500
	1/2	1,200	Rem. 97★	Rem. SP410 Fed. 410SC Win. WAA41		13.0	11,300
			CCI 209	Rem. SP410 Fed. 410SC Win. WAA41		13.5	12,000
Rem.-Peters	1/2	1,200	Rem. 97★	Rem. SP410 Fed. 410SC Win. WAA41		14.0	11,500
			CCI 209	Rem. SP410 Fed. 410SC Win. WAA41		14.5	10,500
			CCI 209M	Rem. SP410		14.0	10,600
Winchester-Western AA-Type	1/2	1,200	Win. 209	Win. WAA41		14.5	10,300
			CCI 209	Fed. 410SC Rem. SP410		13.5	11,000
				Win. WAA41		13.0	11,700
				Fed. 410SC		13.0	12,100
				Rem. SP410		13.5	12,000

## .410 Bore 3-in. Plastic Shells

Shell	Shot Weight (ounces)	Velocity (fps)	Primer	Wad	2400		
					Grains	Approx. psi	Grains
Rem.-Peters	1 1/16	1,135	Rem. 97★	Rem. SP410 Fed. 410SC Win. WAA41		14.5	13,000
			Fed. 410	Rem. SP410		14.5	12,600
			CCI 209M	Rem. SP410		14.5	12,300
				Rem. SP410		14.0	12,700
				Rem. SP410		14.5	12,200



## 10-Gauge 3½-in. Buckshot Loads

Primer	Shell	No. and Size Buckshot	Velocity (fps)	Wad	Herco		Blue Dot	
					Grains	Approx. psi	Grains	Approx. psi
Fed. 209	Federal Plastic	40-4's 17-0's	1,275 1,300	SP10+.270 in. 20 ga. Card SP10+.135 in. 20 ga. Card			45.0 46.0	10,100 10,000
Rem. 57★	Remington Plastic	40-4's 17-0's	1,275 1,300	SP10+.270 in. 20 ga. Card SP10+.135 in. 20 ga. Card			46.0 48.5	10,100 9,800
Win. 209	Winchester-Western Plastic	40-4's 17-0's	1,275 1,300	SP10+.270 in. 20 ga. Card SP10			47.5 51.0	10,000 9,500

## 12-Gauge 2¾-in. Buckshot Loads

Primer	Shell	No. and Size Buckshot	Velocity (fps)	Wad	Herco		Blue Dot	
					Grains	Approx. psi	Grains	Approx. psi
Fed. 209	Federal Hi Power Plastic	34-4's 9-00's	1,250 1,325	Card .135+¾ Fiber+Card .135 Card .135+¼+¾+½ Fiber	30.0	9,400	37.0	10,700
Win. 209	Winchester-Western AA-Type	34-4's 9-00's	1,250 1,325	Card .135+¾+Card .135 Card .135+¼+¼ Fiber	30.0	10,000	39.0	10,900
Rem. 97★	Rem. RXP Plastic	9-00's	1,325	Card .135+¼+¾ Fiber	29.0	10,100		

## 12-Gauge 3-in. Buckshot Loads

Primer	Shell	No. and Size Buckshot	Velocity (fps)	Wad	Herco		Blue Dot		2400	
					Grains	Approx. psi	Grains	Approx. psi	Grains	Approx. psi
Fed. 209	Fed. Hi Power	33-4's 18-1's 12-0's	1,250 1,225 1,275	Bal. Prod. GS&SC Bal. Prod. GS&SC RP12+.200 in. 20 ga. Card	31.5	9,800	37.0 36.0	10,500 9,700	50.0	8,100
Rem. 97★	Rem. Unibody	33-4's 18-1's 12-0's	1,250 1,225 1,275	Bal. Prod. GS&SC Bal. Prod. GS&SC RP12+.200 in. 20 ga. Card			35.5	9,800	46.0	9,400
Win. 209	Winchester-Western AA-Type	33-4's 33-4's 18-1's 18-1's 12-0's	1,250 1,300 1,225 1,300 1,275	Bal. Prod. GS&SC Bal. Prod. GS&SC Bal. Prod. GS&SC RP12+.200 in. 20 ga. Card	29.5	10,000	34.5	9,900	46.5 49.0	9,000 9,800
							37.5	9,900	50.5	9,200

NOTE: Bal. Prod. = Ballistic Products



## 12-Gauge, 2¾-in. Rifled Slug Loads—Rolled Crimp

Slug Weight, Type	Primer	Shell	Velocity (fps)	Wad	Unique Grains	Herco Grains	Herco Approx. psi.
7/8 oz., Cast	Fed. 209	Federal Hi Power Plastic	1,570	Card .135+3/16+1/4+2 Card .135 Card .135+3/16+2 Card .135	33.0	10,000	35.5 8,000
	Rem. 97★	Rem. RXP Plastic	1,570	Card .135+1/4+1/4+2 Card .135 Card .135+1/4+1/4 Fiber+2 Card .135	34.0	10,800	35.0 9,700
	Win. 209	Winchester-Western AA-Type	1,570	Card .135+1/4+1/4 Fiber+2 Card .135 Card .135+1/4 Fiber+2 Card .135	34.5	9,800	29.0 8,600
1 oz., Brenneke	Fed. 209	Federal Hi Power Plastic	1,570	Card .135+1/4+1/4 Fiber			37.0 10,700
	Win. 209	Winchester-Western AA-Type	1,570	Card .135+3/16 Fiber +3/16			37.0 9,700

## 12-Gauge, 3-in. Rifled Slug Loads—Rolled Crimp

Slug Weight, Type	Primer	Shell	Velocity (fps)	Wad	Herco Grains	Blue Dot Grains	2400 Grains	Herco Approx. psi.	Blue Dot Approx. psi	2400 Approx. psi.
7/8 oz., Cast	Fed. 209	Fed. Hi Power	1,570	.135 Card+1/2+3/8+.135 Card	40.0	10,500				
	Rem. 97★	Rem. Unibody	1,570	.135 Card+1/2+3/8+.135 Card	37.5	10,600				
	Win. 209	Winchester-Western AA-Type	1,570	.135 Card+1/2+.135 Card	37.5	9,700				
1 oz., Brenneke	Fed. 209	Fed. Hi Power	1,525	.135 Cards(2)+3/8 Filler			45.0	10,400		
	Rem. 97★	Rem. Unibody	1,525	.135 Cards(2)+3/8 Filler					56.5	10,000
	Win. 209	Winchester-Western AA-Type	1,525	.135 Cards(2)+3/8 Filler					57.5	9,400

## 20-Gauge, 2¾-in. Buckshot Loads

Primer	Shell	No. and Size Buckshot	Velocity (fps)	Wad	Herco Grains	Blue Dot Grains	Blue Dot Approx. psi
Fed. 209	Federal Hi Power Plastic	18-4's	1,275	Rem. SP20	19.0	11,000	25.0 9,300
		24-3's	1,200	Rem. SP20 Petals Removed			
		12-1's	1,275	Rem. SP20 Petals Removed			
Win. 209	Winchester-Western AA-Type	18-4's	1,275	Rem. SP20		24.0 9,600	25.5 10,100
		12-1's	1,275	Rem. SP20 Petals Removed			

## 20-Gauge, 3-in. Buckshot Loads

Primer	Shell	No. and Size Buckshot	Velocity (fps)	Wad	Herco Grains	Blue Dot Grains	Blue Dot Approx. psi
Fed. 209	Federal Hi Power Plastic	18-3's	1,220	Rem. RXP20	19.5	8,400	26.0 7,800
		21-3's	1,220	Rem. SP20			
Rem. 97★	Rem.-Peters Plastic (Old Style)	18-3's	1,220	Win. WAA20F1	19.5	8,300	26.0 8,500
		21-3's	1,220	Win. WAA20F1			
		1,220		Rem. SP20			
Win. 209	Winchester-Western AA-Type	18-3's	1,220	Win. WAA20F1	19.0	9,500	25.0 9,400
		21-3's	1,200	Rem. RP20			

## 20-Gauge, 2¾-in. Rifled Slug Loads—Rolled Crimp

Slug Weight, Type	Primer	Shell	Velocity (fps)	Wad	Herco Grains	Herco Approx. psi.
7/8 oz., Cast	Fed. 209	Fed. Hi Power	1,570	.125 Card+1/2 in. Fiber+2 Card .125 each	25.5	9,800
	Win. 209	Win. WAA-Type	1,570	.125 Card+1/2 in. Fiber+2 Card .125 each	25.5	10,200

# Pistol and Revolver Loads

Cartridge/Bullet	Primer	Min. OAL (inches)	Bbl Length	Bullseye			Red Dot			American Select			Green Dot			Unique			Power Pistol			Herco			Blue Dot			2400						
				Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi				
.25 Auto																																		
50 FMC	Rem. SP 1½	0.875	2.0	1.3	760	15,000	1.1	740	15,500							1.4	785	15,400	1.7	760	14,800				1.7	735	15,600							
.32 Auto																																		
71 FMC	Rem. SP 1½	0.984	4.0	2.2	835	12,500	2.1	805	12,900							2.3	810	11,900	2.5	820	11,200				3.2	880	13,500							
.32 H&R Magnum																																		
85 JHP	Fed. 100	1.320	5.0	3.4	1,020	18,700	3.4	1,030	19,200							3.5	1,035	19,500	4.1	1,050	18,700				4.6	1,060	18,900	6.6	1,100	19,000				
90 LWC (target)		1.100	5.0	2.2	800	9,500	2.1	800	9,400							2.2	805	9,600	2.5	800	8,400				2.8	805	8,500	3.7	805	7,800				
90 LWC		1.180	5.0	3.3	1,060	19,600	3.1	1,020	20,000							3.3	1,050	20,400	3.7	1,110	20,300				4.0	1,070	20,400	5.1	1,150	20,300				
98 LRN		1.320	5.0	3.4	1,020	19,500	3.1	980	19,700							3.5	1,010	19,600	4.0	1,000	19,000							6.2	1,150	20,400				
9x18mm Makarov																																		
95 JHP	Win. W.S.P.	0.965	4.0	3.6	970	21,200																												
100 FPJ	1½-108	0.965	4.0	3.6	960	21,100	3.1	905	21,300							3.5	925	21,300																
100 LRN		0.965	4.0	3.2	920	21,000	2.7	865	21,300							3.2	910	21,600	4.3	985	20,900	4.2	950	21,600										
9mm Luger																																		
95 FMJ	Win. W.S.P.	1.055	4.0	5.5	1,295	31,400	5.3	1,285	32,100							5.5	1,240	25,500	6.5	1,250	26,400	7.8	1,445	32,900	6.8	1,225	24,400	8.3	1,180	22,000				
115 FMJ	1½-108	1.120	4.0	5.0	1,180	31,000	4.5	1,150	32,600							4.7	1,150	30,000	6.1	1,185	30,100	6.7	1,280	33,500	6.3	1,180	28,700	8.0	1,190	29,200				
125 L		1.150	4.0	4.9	1,165	32,100	4.5	1,145	32,000							5.2	1,165	32,100	6.0	1,165	29,400	6.2	1,165	28,500	8.2	1,190	29,700							
125 FMJ		1.150	4.0	4.9	1,155	32,000	4.6	1,145	33,000							5.2	1,150	32,100	6.2	1,170	31,300	6.6	1,235	34,000	6.5	1,180	32,700	8.2	1,170	29,900				
147 XTP		1.140	4.0	4.2	1,010	32,900	3.4	895	32,400							3.7	930	32,200	4.4	1,010	32,700	5.7	1,095	34,000	4.9	1,010	30,500	6.2	1,050	30,200				
.357 Magnum																																		
110 JHP	Fed. 200	1.560	5.6	9.0	1,690	31,700	7.7	1,560	34,000							10.0	1,660	31,300	10.0	1,735	34,100	9.7	1,690	34,000	13.0	1,885	33,300	16.0	2,040	33,800				
125 JSP		1.570	5.6	8.4	1,550	32,800	7.0	1,410	34,000							7.3	1,415	33,600	9.6	1,585	33,800	9.2	1,555	33,500	9.8	1,590	33,600	14.5	1,795	34,000				
148 LWC (target)		1.330	5.6	2.8	780	10,000	2.7	775	12,400							2.8	780	14,100	3.3	775	10,000													
148 LWC		1.330	5.6	5.7	1,475	34,000	4.6	1,300	33,600							5.1	1,310	34,000	6.4	1,465	33,800													
158 LSWC		1.580	5.6	6.5	1,320	33,900	5.5	1,215	34,000							6.0	1,240	34,000	6.8	1,295	33,900													
158 JSP		1.575	5.6	6.8	1,250	33,100	6.0	1,160	33,400							7.0	1,215	34,000	7.8	1,280	33,200	8.0	1,305	33,800	8.2	1,305	34,000	10.7	1,420	33,300				
170 FMJ		1.585	5.6	6.2	1,175	33,900	5.4	1,025	33,600							6.1	1,090	33,700	6.8	1,175	33,300	8.0	1,195	33,300	7.0	1,175	33,500	9.7	1,310	33,800				
180 JFP		1.580	5.6	6.3	1,135	34,000	5.3	930	33,200							6.0	1,010	34,000	7.0	1,125	33,800	7.0	1,145	33,800	7.2	1,110	34,000	9.7	1,260	33,300				
200 LRN		1.575	5.6	5.3	1,085	33,900	4.6	990	33,600							5.0	1,015	34,000	6.0	1,105	33,900							6.1	1,105	33,900				
.38 Super Auto +P																																		
115 JHP	Rem. SP 1½	1.255	5.0	5.5	1,240	33,900	4.7	1,155	33,500							5.7	1,225	33,800	6.6	1,265	33,800	7.3	1,345	34,400	6.8	1,260	34,000	10.2	1,360	33,000				
130 FMJ		1.260	5.0	5.1	1,170	33,600	4.5	1,095	33,900							5.2	1,135	33,600	6.2	1,200	34,000	6.8	1,255	34,600	6.3	1,180	33,500	9.1	1,265	32,500				
147 XTP		1.275	5.0	5.0	1,095	34,000	4.5	1,035	34,000							4.7	1,045	33,500	5.8	1,105	34,000	6.2	1,155	34,900	6.4	1,135	33,800	8.6	1,220	33,900	10.9	1,215	33,600	
158 L		1.275	5.0	4.6	1,030	33,600	4.0	985	34,000							4.9	1,025	33,900	5.9	1,085	33,800				6.0	1,080	33,100	8.3	1,190	33,900				
.38 Special																																		
110 JHP	Fed. 100	1.430	5.6	4.5	1,085	14,900	4.0	1,000	15,800							4.6	1,050	16,000	5.6	1,090	15,400				5.6	1,090	15,800	7.8	1,170	15,700				
125 JSP		1.440	5.6	4.4	1,000	15,300	3.9	950	15,600							4.3	985	15,900	5.3	1,015	16,000				5.5	1,040	16,000	7.3	1,035	15,600				
148 LWC (target)		1.180	5.6	2.7	785	14,600	2.3	730	14,800							2.7	765	14,600	3.2	775	14,100													
148 LWC		1.180	5.6	2.8	815	15,900	2.5	750	15,500							2.9	800	15,900	3.3	815	15,300													
158 LSWC		1.420	5.6	3.6	910	15,500	3.1	835	15,800							3.5	870	15,600	4.3	920	16,000													
160 JSP		1.435	5.6	3.5	805	15,600	3.2	715	15,700							3.4	750	15,800	4.2	800	15,600													
200 LRN		1.540	5.6	3.0	760	15,100	2.8	725	15,100							3.1	750	15,500	3.6	780	15,700													
.38 Special +P																																		
90 JHP	Fed. 100	1.410	5.6	5.5	1,340	17,000	4.5	1,245	17,000							5.1	1,260	16,900	6.3	1,300	16,800				6.5	1,310	17,100	9.1	1,345	16,900				
110 JHP		1.430	5.6	5.0	1,175	17,400	4.2	1,040	17,500							4.8	1,100	17,400	5.9	1,160	17,500	6.5	1,200	17,100	5.9	1,150	17,500	8.2	1,205	16,800				
125 JSP		1.445	5.6	4.8	1,090	17,500	4.1	965	17,000							4.6	1,015	17,500	5.6	1,070	17,500	6.3	1,165	17,200	5.8	1,050	16,900	7.5	1,065	16,900				
158 LSWC	</td																																	

Cartridge/Bullet	Primer	Min. OAL (inches)	Bbl Length	Bullseye			Red Dot			American Select		Green Dot			Unique			Power Pistol			Herco			Blue Dot			2400									
				Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi						
<b>.380 Auto</b>																																				
88 JHP	Win.	0.960	3.7	3.2	980	14,300	3.1	965	14,600				3.4	940	14,600	4.0	920	13,600				4.1	995	14,900	6.0	1,000	14,700									
90 JHP	1½-108	0.960	3.7	3.0	940	12,900	3.1	940	14,300				3.2	890	12,800	4.0	940	14,000				4.0	960	14,800	6.0	980	14,800									
90 XTP		0.960	3.7																																	
95 FMJ		0.975	3.7	3.2	900	14,700	3.1	885	14,900				3.5	890	14,700	4.2	910	14,600				4.7	1,065	21,000	4.4	910	14,600	6.5	910	14,200						
100 FMJ-RN		0.975	3.7	3.3	985	20,100	2.8	920	19,900				3.1	955	20,000	4.3	1,005	19,500				4.6	1,035	20,600												
<b>.38/40 Win.</b>																																				
150 gr. Sierra JHP	Rem. 2½	1.585	5.6	6.5	960	12,600	6.2	910	12,800				6.8	950	12,700	8.2	990	13,200				9.2	995	13,100	11.8	1,020	13,100	14.1	970	13,100						
180 gr. Sierra JHP		1.585	5.6	5.6	820	12,200	5.1	740	12,500				5.6	745	12,700	6.9	815	13,200				7.3	795	13,100	10.3	875	13,200	13.0	875	13,400						
200 gr. Hornady FMJ/FP		1.585	5.6	5.3	750	12,400	4.8	685	12,400				5.5	730	12,500	6.7	765	13,100				7.3	785	13,300	9.9	840	13,500	12.7	830	13,500						
<b>.357 Sig.</b>																																				
90 JHP	Fed. 100	1.090	4.0	9.3	1,660	37,100	7.1	1,495	35,400				7.8	1,545	36,500	9.2	1,615	37,100	11.4	1,715	37,000	10.1	1,625	34,600	12.8	1,690	35,300									
115 JHP		1.150	4.0	8.0	1,435	36,400	6.4	1,285	37,100				6.9	1,305	37,000	10.0	1,505	36,200	8.7	1,400	36,600	11.3	1,495	37,400												
124 TMJ		1.195	4.0	7.0	1,325	37,000	6.0	1,215	37,200				6.5	1,255	36,800	9.5	1,435	37,200	8.3	1,345	37,600	10.6	1,405	36,900												
147 XTP		1.138	4.0	5.8	1,145	36,800							4.8	1,010	37,100	5.8	1,110	37,200	7.8	1,245	37,000	6.4	1,140	37,600	8.2	1,205	35,800									
<b>.40 S&amp;W Auto</b>																																				
135 JHP	Win.	1.105	4.0	7.6	1,350	33,600	6.7	1,280	33,200				7.5	1,330	33,100	8.5	1,290	26,600	9.3	1,340	34,000	8.2	1,215	33,900	11.5	1,285	34,000									
150 JHP	1½-108	1.105	4.0	6.7	1,225	34,000	5.9	1,155	34,000				6.2	1,175	33,800	8.0	1,245	34,000	8.2	1,215	33,300	8.2	1,215	33,900	9.8	1,170	33,900	12.1	1,110	33,600						
170 XTP		1.124	4.0	5.5	1,015	33,500	5.1	985	34,000				5.6	1,045	33,700	6.7	1,075	33,800	7.3	1,105	33,300	7.4	1,125	34,000	9.8	1,170	33,900									
180 JHP		1.125	4.0	5.5	1,015	33,900	5.0	980	34,000				5.3	1,010	33,600	6.4	1,065	33,800	6.9	1,050	33,700	7.0	1,045	34,000	8.8	1,065	34,000	10.9	1,025	33,900						
190 JHP		1.130	4.0	5.4	955	34,000	4.9	895	33,600				5.1	955	33,600	6.1	1,010	34,000	6.9	1,020	33,100	6.7	1,000	33,800	8.7	1,040	33,800	10.6	975	33,600						
200 FMJ		1.130	4.0	4.6	945	33,600	4.1	890	33,500				4.3	890	33,600	5.3	955	33,900	6.3	960	33,700	5.8	955	34,000	7.9	960	33,800	8.5	925	33,600						
<b>10mm Auto</b>																																				
135 JHP	Fed. 150	1.250	5.5																																	
150 JHP		1.250	5.5																																	
155 HP		1.250	5.5	6.7	1,190	34,000																7.5	1,200	33,800	8.2	1,230	33,800	11.5	1,340	34,100	13.6	1,270	33,600			
155 L		1.250	5.5																			9.5	1,320	33,000												
170 HP		1.250	5.5	6.2	1,135	34,000																6.9	1,135	34,100	7.5	1,145	33,600	10.1	1,180	33,500	12.6	1,190	33,800			
180 JHP		1.250	5.5	6.4	1,125	35,900																7.0	1,125	35,700	8.7	1,240	34,900	7.5	1,140	35,800	10.4	1,220	35,800			
180 L		1.250	5.5																			6.7	1,235	34,700												
190 JFP		1.250	5.5	6.3	1,050	35,500																6.7	1,025	35,500	8.2	1,200	35,900	7.2	1,050	35,800	10.0	1,185	36,000			
200 FMJ		1.260	5.5	5.3	940	33,600																5.8	940	33,700	7.7	1,145	35,600	6.5	965	33,500	8.9	1,110	33,800	11.2	1,115	34,100
<b>.41 Rem. Magnum</b>																																				
200 HP	Rem. 2½	1.580	5.8	8.0	1,235	35,700	7.5	1,200	33,400				8.3	1,170	35,000	10.0	1,280	35,700				10.1	1,320	35,900	14.0	1,470	36,000	17.5	1,420	34,700						
210 JSP		1.575	5.8	8.3	1,245	34,300	8.2	1,225	34,300				8.7	1,165	35,800	10.1	1,265	35,400				10.3	1,320	34,800	13.5	1,425	33,800	17.5	1,425	33,900						
220 JHP		1.575	5.8	7.5	1,150	35,800	7.4	1,125	35,900				7.9	1,140	35,800	9.3	1,215	35,300				9.3	1,220	35,800	12.5	1,365	35,800	16.4	1,365	34,300						
<b>.44 S&amp;W Special</b>																																				
180 JHC	Win. 7-111	1.600	5.6	6.5	910	12,000	6.4	885	12,100				6.7	925	c.u.p.	9.0	985	12,500				9.8	1,000	12,600	13.5	1,020	c.u.p.	16.0	950	c.u.p.						
246 LRN		1.590	5.6	4.5	765	11,700	4.3	740	11,900				5.0	785	11,900	6.0	800	11,700				7.7	805	12,100	9.2	845	12,300	11.3	805	11,500						
<b>.44/40 Win.</b>	Rem. 2½																																			
200 JSP		1.590	24	6.6	1,070	12,300	5.9	920	12,400				6.6	990	c.u.p.	8.0	1,090	12,400				8.5	1,100	12,500	12.0	1,225	12,500	14.5	1,230	c.u.p.						
240 L		1.580	24	5.0	850	12,200	4.7	800	12,300				5.5	850	12,200	6.7	950	12,500				7.1	955	12,400	9.9	1,125	12,500	12.0	1,130	12,500						
<b>.44 Rem. Magnum</b>																																				
180 JHC	Fed. 150	1.585	5.7	11.5	1,520	33,400	10.0	1,410	34,600				11.3	1,470	34,600	13.0	1,550	35,000				13.6	1,560	34,900	19.0	1,725	34,000	23.3	1,760	33,700						
200 JHP		1.575	5.7	11.0	1,420	34,000	9.7	1,320	34,800				10.7	1,370	34,500	13.0	1,475	34,400				13.0	1,455	34,500	17.0	1,565	33,400	23.2	1,665	34,300						
225 JHP		1.575	5.7	9.5	1,270	34,600	8.2	1,185	34,600				9.2	1,220	34,700	10																				

## Pistol and Revolver Loads (continued)

Cartridge/Bullet	Primer	Min. OAL (inches)	Bbl Length	Bullseye			Red Dot			American Select			Green Dot			Unique			Power Pistol			Herco			Blue Dot			2400					
				Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi			
.455 Webley																																	
220 MK IV L	CCI 300	1.000	6.0	3.6	765	c.u.p.	3.4	745	c.u.p.				3.5	755	c.u.p.	4.4	800	c.u.p.				4.8	790	c.u.p.									
265 HB RN L		1.245	6.0	3.8	750	12,600	3.4	685	12,300				3.6	690	12,400	4.3	710	12,600				4.9	735	12,700	6.8	770	c.u.p.						
.45 A.C.P.																																	
155 Cast Lead	Federal 150	1.270	5.0	6.9	1,175	19,400	5.8	1,155	18,800				6.6	1,165	19,300	7.8	1,190	19,200				8.5	1,185	19,100									
180 LWC		1.190	5.0	5.4	985	15,800	4.8	900	14,100				5.3	910	14,500	6.0	875	13,400				6.7	950	15,800	9.0	920	13,600						
185 JHP		1.275	5.0	6.7	995	19,400	5.9	940	19,500				6.8	990	19,300	8.2	1,030	18,900	8.6	1,025	18,800	8.2	990	18,500									
200 LSW (target)		1.190	5.0	4.0	790	9,800	4.0	805	9,400				4.3	805	9,900	5.1	810	9,600															
200 JHP		1.175	5.0	6.0	960	19,400	5.2	890	19,200				5.9	915	18,900	7.1	975	19,500	7.4	965	19,900	7.7	955	19,300	10.6	1,000	19,500						
230 L (target)		1.190	5.0	4.0	810	13,900	4.0	810	12,800				4.3	805	13,200	5.0	790	11,800				5.2	815	13,600									
230 JHP		1.230	5.0	5.4	865	19,200	5.0	820	19,500				5.4	845	19,500	6.4	880	19,400				7.0	875	19,500	9.8	915	19,300						
230 FMC		1.190	5.0	5.0	905	16,200	5.0	910	16,200				5.4	920	15,800	6.0	895	16,000	7.2	895	20,000	6.2	890	16,200	8.5	900	16,200						
240 JHP		1.210	5.0	5.0	810	18,900	4.5	770	19,200				5.0	790	19,300	5.9	820	19,200				6.5	820	19,200	8.3	865	19,300						
260 JHP		1.210	5.0	4.5	725	19,400															5.9	750	18,600	8.3	780	19,000							
240 JHC		1.190	5.0																		6.5	835	19,900										
.45 ACP +P																																	
185 JHP	Fed. 150	1.190	5.0																		9.1	1,075	21,700										
200 JHP		1.190	5.0																		8.2	1,030	22,200										
230 FMC		1.190	5.0																		7.5	930	22,000										
240 JHC		1.190	5.0																		7.1	890	22,200										
.45 Colt																																	
200 JMPH	Win. 7-111	1.550	7.3	6.0	870	c.u.p.	7.0	915	c.u.p.				8.0	940	c.u.p.	9.0	895	c.u.p.				9.5	895	c.u.p.	13.0	925	c.u.p.						
250L		1.550	7.3	5.4	805	11,800	6.0	830	12,000				6.8	855	c.u.p.	8.0	850	c.u.p.				9.0	910	c.u.p.	11.5	890	c.u.p.						
300 HP/XTP		1.580	7.3	5.0	605	12,400	4.8	550	12,200				5.7	645	c.u.p.	6.8	690	c.u.p.				7.2	670	c.u.p.	10.0	730	c.u.p.	12.5	735	c.u.p.			
.45 Win. Magnum																					14.0	1,385	34,500										
200 JHP	Win. 7-111	1.475	5.0																		13.1	1,270	34,900										
230 FMJ		1.475	5.0																		11.5	1,145	34,400										
260 JHP		1.475	5.0																		14.5	1,250	37,400	18.6	1,340	36,900	22.5	1,345	37,100				

NOTES and KEY pertain to Pistol and Revolver tables.

See Special Reloading Precautions on page 56.


### NOTES:

- Do not intermix cases of different manufacture, nor bullets, nor primers.
- Be sure that each case is crackfree and completely empty.
- Unless specifically recommended, use standard primers. Magnum primers are neither needed nor recommended for most calibers.
- Do not exceed the powder weight shown, and guard against accidental multiple charges of powder.
- Start with 10% less powder than shown. Work up gradually, watching for signs of high pressure.
- Be sure that every completed cartridge is not shorter than the length listed.
- Watch for signs of case head separation.

### KEY

BR	=Bench Rest	M	=Match	in.	=inches
FMC	=Full Metal Case	psi	=Chamber pressure, piezo system	gr.	=grains
FMJ	=Full Metal Jacket			Vel.	=velocity
FN	=Flat Nose	PSP	=Pointed Soft Point	fps	=feet per second
FP	=Flat Point	RN	=Round Nose	c.w.	=powder charge weight
FS	=Fail Safe	SB	=Solid Base	c.u.p.	=chamber pressure, in copper units
GC	=Gas Check	SJ	=Semijacketed	Min	=minimum overall
HB	=Hollow Base	SP	=Soft Point	OAL	length, measured from base to tip of bullet
HC	=Hollow Cavity	Sp. Pt.	=Spire Point		
HP	=Hollow Point	WC	=Wad Cutter		
J	=Jacketed	Wt	=weight		
L	=Lead	Bbl	=barrel		

# Silhouette Loads



Cartridge/Bullet	Primer	Min OAL (inches)	Blue Dot			2400			Reloder 7		
			Charge Weight (grains)	Velocity (fps)	Chamber Pressure (copper units)	Charge Weight (grains)	Velocity (fps)	Chamber Pressure (copper units)	Charge Weight (grains)	Velocity (fps)	Chamber Pressure (copper units)
<b>.222 Remington (Rem. case)</b>											
50 gr. Sierra Spitzer	Fed. 205M	2.090				12.9	2,425	43,800	19.3	2,700	43,800
53 g. Sierra BRHP		2.104				12.4	2,345	43,800	18.2	2,575	43,500
55 gr. Sierra Spitzer		2.125				12.0	2,250	43,100	17.6	2,495	43,400
60 gr. Hornady Spire Pt.		2.125				12.0	2,180	43,800	17.0	2,400	43,800
68.0 gr. Hornady BTHP		2.125				11.3	1,990	43,800	16.5	2,230	43,200
<b>.223 Remington (Rem. case)</b>											
55 gr. Sierra Spitzer	Fed. 205M	2.250				15.9	2,430	48,500	22.1	2,670	48,900
60 gr. Hornady Spire Pt.		2.250				15.4	2,320	48,500	21.4	2,550	49,500
70 gr. Hornady Spire Pt.		2.250				13.0	1,965	48,600	17.0	2,180	48,800
<b>7mm BR Rem. (Rem. case)</b>											
120 gr. Sierra Spitzer	Rem. 7½ BR	2.300				20.2	2,160	47,100	27.8	2,425	47,400
145 gr. Speer Spitzer		2.300				17.7	1,800	47,200	24.8	2,130	47,800
<b>7mm/08 (Rem. case)</b>											
120 gr. Sierra Spitzer	Fed. 210 BR	2.750				27.5	2,310	48,100	37.2	2,560	48,900
145 gr. Speer Spitzer		2.750				23.5	1,970	48,300	33.0	2,250	48,300
<b>.30-.30 Winchester (Fed. case)</b>											
152 gr. Cast Lead	Fed. LR #210	2.500	13.0	1,525	29,000	16.0	1,650	33,300	25.0	1,950	34,900
170 gr. Rem. SPCL		2.500				16.0	1,500	34,700	23.5	1,800	34,900
<b>.35 Remington (Rem. case)</b>											
158 gr. Hornady L	Fed. LR #210	2.400	15.5	1,574	25,200	21.0	1,715	25,300	28.5	1,875	26,600
170 gr. Sierra FMJ		2.400	13.0	1,300	22,400	17.0	1,450	23,400			
200 gr. Rem. SPCL		2.510				22.0	1,650	31,700	30.0	1,825	31,700
<b>.357 Magnum (Win. case)</b>											
158 gr. Rem. SP	Fed. 200	1.580	12.0	1,600	42,900	14.6	1,640	42,300			
170 gr. Sierra FMJ		1.580	10.7	1,445	41,700	13.2	1,450	43,000			
180 gr. Speer FMJ		1.580	9.6	1,265	42,300	11.8	1,320	42,900			
180 gr. Sierra FPJ		1.580	9.2	1,250	42,400	12.1	1,350	41,700			
<b>.357 Maximum (Rem. case)</b>											
125 gr. Speer JHP	Rem. 7½ BR	1.900	15.0	1,860	38,200	20.5	2,045	38,200			
158 gr. Hornady HP		1.975				18.0	1,790	40,400	26.0	1,845	33,600
160 gr. Speer SP		1.975	15.3	1,760	40,700	17.4	1,775	41,200	26.0	1,830	32,700
170 gr. Sierra FMJ		1.975	14.5	1,675	41,300	16.5	1,670	40,500	25.5	1,840	40,100
180 gr. Sierra FPJ		1.975	14.9	1,610	39,400	16.8	1,590	39,000	25.0	1,760	39,700
200 gr. Speer FMJ		1.975	11.6	1,275	41,300	14.1	1,340	41,300	22.3	1,650	41,400
<b>.44 Rem. Magnum (Rem. case)</b>											
180 gr. Sierra HC	Fed. 150	1.590	18.8	1,875	37,900	23.0	1,910	37,800			
240 gr. Speer FMJ		1.590	15.5	1,550	37,600	18.8	1,560	36,800			
250 gr. Sierra FPJ		1.590	15.0	1,525	36,800	19.0	1,600	37,800			
265 gr. Hornady FP		1.590	14.1	1,420	36,300	17.4	1,460	37,400			

Test barrels were 14 inches long, except .357 Maximum, which was 12½ inches.

See NOTES and KEY on page 55.

See Special Reloading Precautions on page 56.



## Centerfire Rifle

Cartridge/Bullet	Primer	Min. OAL (inches)	Case	Bbl Length	2400			Reloder 7			Reloder 12			Reloder 15			Reloder 19			Reloder 22			
					Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	
.17 Rem. Hornady 25HP	Rem. 7½	2.140	Rem.	24							21.8	3,750	c.u.p. 50,100	22.8	3,915	c.u.p. 50,200							
.22 Hornet Speer 40SP	Win. 6½-116	1.710	Win.	24	7.5	2,250	c.u.p. 41,000	11.0	2,265	c.u.p. 19,800													
Speer 45 Spitz		1.710		24	7.1	2,065	c.u.p. 41,300	10.6	2,170	c.u.p. 20,300													
Hornady 50SPSX		1.710		24	7.0	1,945	c.u.p. 41,700	10.5	2,115	c.u.p. 21,500													
.22/250 Rem.											35.5	3,760	59,400										
Speer 45 Spitz	Win. 8½-120	2.300	Win.	24							34.3	3,575	58,900										
Hornady 50SPSX		2.350		24							33.3	3,425	59,200	35.3	3,625	59,400							
Hornady 55SPSX		2.350		24							32.5	3,290	58,500	34.7	3,485	59,400	41.0	3,510	57,800				
Hornady 60SP		2.350		24																			
.220 Swift											36.6	3,760	c.u.p. 50,100	39.0	4,010	c.u.p. 50,300							
Speer 45 Spitz	CCI 200	2.645	Horn.	24							36.1	3,675	c.u.p. 50,500	38.6	3,850	c.u.p. 49,800	44.0	3,650	c.u.p. 50,400				
Hornady 50SPSX		2.660		24																			
Hornady 55MJBT		2.630		24																			
Hornady 60 Sp. Pt.		2.680		24																			
.221 Rem. Fireball																							
Speer 40SP	Rem. 7½	1.800	Rem.	10½	15.5	2,700	c.u.p. 46,500																
Sierra 50 Spitz		1.825		10½	13.8	2,410	c.u.p. 43,500																
Sierra 53BRHP		1.825		10½	13.5	2,320	c.u.p. 43,600																
Nosler 60 Spitz		1.825		10½	13.3	2,200	c.u.p. 46,300	18.1	2,250	c.u.p. 34,000													
.222 Rem.																							
Speer 45 Spitz	Rem. 7½ BR	2.090	Rem.	24				19.8	3,225	c.u.p. 47,500	25.0	3,290	46,200										
Sierra 50SMP		2.130		24				20.0	3,115	c.u.p. 47,400	24.0	3,120	44,300										
Sierra 55MJBT		2.130		24							24.0	3,190	c.u.p. 47,900	24.3	3,120	c.u.p. 47,900							
Hornady 60SPPT		2.130		24																			
.222 Rem. Mag.																							
Speer 45 Spitz	Rem. 7½	2.280	Rem.	24				23.0	3,400	c.u.p. 46,500													
Sierra 50 Spitz		2.280		24							22.5	3,250	c.u.p. 45,400										
Sierra 53BRHP		2.280		24							22.0	3,120	c.u.p. 44,500										
Sierra 55 Spitz		2.280		24							22.0	3,100	c.u.p. 46,000										

Cartridge/Bullet/Primer				Min. OAL (inches)	Case	Bbl Length	2400			Reloder 7			Reloder 12			Reloder 15			Reloder 19			Reloder 22		
		Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi		
<b>.223 Rem.</b>																								
Speer 45 Spitz	Fed. 205M	2.210	Fed.	24	14.9	3,030	49,600	21.8	3,375	53,200	28.0	3,470	52,800	28.5	3,635	53,500								
Hornady 50SP		2.250		24	14.5	2,795	48,500	21.5	3,195	53,000	27.0	3,335	52,300											
Sierra 52HPBT		2.250		24				20.9	3,165	53,300	27.5	3,310	52,700	28.3	3,440	53,100								
Hornady 55MJBT		2.215		24	14.0	2,685	49,900	20.5	3,080	52,400	27.5	3,255	52,200	28.0	3,390	53,600								
Hornady 60 Sp. Pt.		2.250		24							25.5	3,070	53,300	26.5	3,240	53,000								
Hornady 68BTHP		2.260		24							24.0	2,935	56,600	25.6	3,030	52,800								
Hornady 75BTHP		2.260	Rem.	24										24.9	2,895	53,400								
Sierra 80HPBT		2.260	Rem.	24										24.0	2,800	53,000								
<b>.225 Win.</b>																								
Win. 50PSP	Win. 8½-120	2.450	Win.	24				22.0	3,130	c.u.p. 44,000														
Win. 55PSP		2.450		24				22.0	3,075	c.u.p. 44,500														
<b>.243 Win.</b>																								
Sierra 60HP	Win. 8½-120	2.550	Win.	24				30.2	3,320	54,800	38.5	3,450	56,400											
Speer 75HP		2.610		24							34.0	3,125	57,500											
Speer 80 Spitz		2.685		24							34.0	3,060	57,000	36.5	3,145	57,500	44.5	3,270	57,500					
Sierra 100 Spitz BT		2.700		24													41.0	2,925	57,100	41.7	2,950	57,500		
<b>6mm Remington</b>																								
Sierra 60HP	Rem. 9½	2.760	Rem.	24							41.8	3,665	62,800	43.6	3,820	62,700								
Speer 75HP		2.790		24							39.0	3,340	62,200	40.6	3,410	62,300								
Speer 80 Spitz		2.790		24							38.0	3,205	62,300	40.5	3,340	63,000	49.5	3,435	61,700	51.5	3,450	60,900		
Sierra 100 Spitz BT		2.800		24													46.0	3,145	62,500	48.0	3,205	62,500		
<b>.25-06 Rem.</b>																								
Sierra 75HP	Fed. 210	3.090	Fed.	24							48.0	3,580	59,900											
Speer 87 Spitz		3.090		24							44.5	3,290	59,500	47.2	3,425	61,000	57.3	3,525	59,800					
Speer 100 Spitz		3.200		24										44.9	3,190	61,000	54.3	3,320	61,000	55.9	3,355	61,100		
Sierra 120HPBT		3.225		24													50.5	3,025	60,400	52.5	3,080	60,400		
<b>.25/20 Win.</b>																								
Rem. 86SP	CCI 400	1.590	Rem.	24	8.0	1,340	c.u.p. 18,300	11.5	1,460	c.u.p. 15,000														
<b>.250 Savage</b>																								
Sierra 75HP	Rem. 9½	2.400	Rem.	24							37.8	3,250	c.u.p. 43,800	38.3	3,350	c.u.p. 43,700								
Speer 87 Spitz		2.450		24													36.0	3,135	c.u.p. 43,800	41.0	2,940	c.u.p. 42,800		
Speer 100 Spitz		2.500		24																40.0	2,855	c.u.p. 43,400		
Sierra 120HPBT		2.510		24																40.0	2,680	c.u.p. 43,600		
<b>.257 Roberts</b>																								
Sierra 75HP	Win. 8½-120	2.775	Win.	24							39.0	3,160	c.u.p. 42,800	41.8	3,340	c.u.p. 42,700								
Speer 87 Spitz		2.775		24							36.5	2,930	c.u.p. 43,300	41.0	3,185	c.u.p. 43,200								
Speer 100 Spitz		2.775		24													44.7	2,930	c.u.p. 43,100					
Sierra 120HPBT		2.775		24																44.0	2,785	c.u.p. 43,000		
<b>.257 Roberts +P</b>																								
Sierra 75HP	Win. 8½-120	2.775	Win.	24							41.0	3,365	c.u.p. 48,000	43.4	3,510	c.u.p. 48,000								
Speer 87 Spitz		2.775		24							39.5	3,165	c.u.p. 48,000	43.5	3,310	c.u.p. 48,000								
Speer 100 Spitz		2.775		24																47.2	3,110	c.u.p. 47,900		
Sierra 120 HPBT		2.775		24																46.5	2,945	c.u.p. 48,000		

See NOTES and KEY on page 55.

continued on next page

## Centerfire Rifle (continued)

Cartridge/Bullet	Primer	Min. OAL (inches)	Case	Bbl Length	Chg Wt	2400 fps	psi	Reloder 7	Chg Wt	fps	psi	Reloder 12	Chg Wt	fps	psi	Reloder 15	Chg Wt	fps	psi	Reloder 19	Chg Wt	fps	psi	Reloder 22	Chg Wt	fps	psi		
<b>.257 Wby. Mag.</b>																													
Sierra 75HP	Fed. 215	3.075	Wby.	26																	73.3	3,895	52,900	77.0	3,900	53,000			
Speer 87 Spitz		3.150		26																68.4	3,650	53,000	73.0	3,675	52,700				
Speer 100 Spitz		3.170		26																64.5	3,420	52,700	69.0	3,460	52,400				
Barnes 115 Spitz		3.170		26																61.3	3,175	53,000	64.5	3,200	52,700				
Nosler 120 SP		3.170		26																59.7	3,100	53,000	62.7	3,140	52,900				
<b>6.5x55 Swedish Mauser</b>																													
Hornady 129SP	CCI 200	2.935	Norma	24				25.8	2,130	c.u.p. 43,600		36.7	2,465	c.u.p. 44,400		38.8	2,620	c.u.p. 44,400		48.0	2,815	c.u.p. 44,500							
Speer 140 Spitz		3.000		24									35.0	2,395	c.u.p. 44,500		36.6	2,480	c.u.p. 44,200		46.0	2,650	c.u.p. 44,000		48.1	2,700	c.u.p. 44,400		
Hornady 160RN		2.975		24				25.0	1,940	c.u.p. 44,000		35.2	2,225	c.u.p. 44,200		35.6	2,325	c.u.p. 44,000		45.0	2,500	c.u.p. 44,300		47.0	2,535	c.u.p. 44,000			
<b>.264 Win. Mag.</b>																													
Hornady 129 Sp. Pt.	Win. 8½-120	3.270	Win.	24																57.0	3,070	c.u.p. 51,800							
Speer 140 Spitz		3.340		24																56.0	2,945	c.u.p. 51,800		57.0	2,960	c.u.p. 51,300			
Hornady 160RN		3.315		24																					57.0	2,780	c.u.p. 51,800		
<b>.270 Win.</b>																													
Speer 100 Spitz	Win. 8½-120	3.150	Win.	24																53.8	3,465	c.u.p. 62,000		64.0	3,510	c.u.p. 61,800			
Speer 130 Spitz		3.250		24															47.3	2,840	c.u.p. 61,600		57.5	3,110	c.u.p. 61,600				
Sierra 140 SBT		3.280		24															47.0	2,770	c.u.p. 61,600		57.0	2,910	c.u.p. 61,500				
Sierra 150 Spitz BT		3.320		24																55.5	2,945	c.u.p. 61,400		58.5	3,010	c.u.p. 61,800			
Nosler 150 Spitz		3.325		24																56.5	2,810	c.u.p. 61,800		59.5	2,845	c.u.p. 60,300			
<b>.270 Wby. Mag.</b>																													
Speer 100 Spitz	Fed. 215	3.160	Wby.	26																76.8	3,755	c.u.p. 53,400		79.0	3,775	c.u.p. 53,000			
Speer 130 Spitz		3.260		26																70.5	3,340	c.u.p. 53,500		73.8	3,400	c.u.p. 53,500			
Sierra 140 SBT		3.275		26																68.1	3,240	c.u.p. 53,500		71.0	3,280	c.u.p. 53,500			
Sierra 150 SBT		3.285		26																64.4	3,075	c.u.p. 53,500		68.8	3,145	c.u.p. 53,500			
Nosler 150 Spitz		3.285		26																64.8	3,090	c.u.p. 53,200		69.7	3,180	c.u.p. 53,500			
<b>7-30 Waters</b>																													
Hornady 120 Sp. Pt.	Fed. 210	2.640	Fed.	24				27.3	2,470	c.u.p. 38,600		36.5	2,645	c.u.p. 38,700		36.3	2,725	c.u.p. 39,000											
Hornady 139 F.P.		2.650		24									33.8	2,405	c.u.p. 39,000		34.7	2,540	c.u.p. 38,800										
<b>7mm-08 Rem.</b>																													
Hornady 120 Sp. Pt.	Rem. 9½	2.750	Rem.	24				35.5	2,775	57,200		45.2	2,950	58,400		45.5	3,070	58,700											
Hornady 139 Sp. Pt.		2.800		24				34.0	2,555	57,300		42.5	2,735	59,000		43.0	2,830	59,000		52.0	2,850	57,900							
Speer 145 Spitz		2.800		24				31.8	2,405	57,500		39.6	2,580	59,000		41.0	2,700	59,000		49.3	2,785	58,900							
Sierra 150 HPBT		2.800		24				32.3	2,410	57,300		40.1	2,590	58,500		40.9	2,685	58,600		49.0	2,760	58,700							
Sierra 160 Spitz BT		2.800		24									40.0	2,535	58,900		40.5	2,620	59,000		48.5	2,675	56,400						

Cartridge/Bullet	Primer	Min. OAL (inches)	Case	Bbl Length	Chg Wt	2400 fps	psi	Chg Wt	Reloder 7 fps	psi	Chg Wt	Reloder 12 fps	psi	Chg Wt	Reloder 15 fps	psi	Chg Wt	Reloder 19 fps	psi	Chg Wt	Reloder 22 fps	psi				
<b>7x57 Mauser</b>																										
Hornady 120 Sp. Pt.	Fed. 210	2.965	Fed.	24					43.0	2,895	48,900	45.0	2,995	48,900	54.0	3,030	48,000									
Hornady 139 Sp. Pt.		3.015		24					40.5	2,660	48,800	41.5	2,700	48,400	51.8	2,835	49,000	53.0	2,790	45,600						
Speer 145 Spitz		3.040		24					37.0	2,520	48,800	38.5	2,550	48,500	47.3	2,680	48,800	48.8	2,720	49,000						
Sierra 160 Spitz BT		3.040		24											49.0	2,665	45,500	50.0	2,690	48,300						
<b>.280 Rem.</b>																										
Hornady 120SP	Rem. 9½	3.310	Rem.	24					47.1	2,985	57,900	48.0	3,065	57,200	58.0	3,115	57,600									
Hornady 139 Sp. Pt.		3.320		24					44.0	2,700	57,100	46.5	2,800	57,700	57.0	2,970	58,000	59.5	3,000	57,500						
Speer 145 Spitz		3.320		24					42.5	2,580	57,600	43.0	2,630	57,100	53.0	2,815	57,800	56.0	2,865	58,000						
Sierra 160 Spitz BT		3.325		24											53.4	2,750	58,100	55.7	2,795	58,000						
<b>.284 Win.</b>																										
Hornady 120 SP	Win. LR	2.800	Win.	24											51.5	3,235	54,300	60.5	3,265	53,600						
Hornady 139SP	8½-120	2.795		24											48.0	2,975	54,700	57.0	3,075	53,500	58.5	3,030	49,000			
Speer 145 Spitz		2.795		24											46.7	2,855	55,100	55.0	2,940	52,400	55.0	2,900	49,200			
Nosler 150 Part.		2.790		24														55.0	2,940	53,500	55.0	2,840	46,300			
Sierra 160 Spitz BT		2.800		24														54.0	2,885	54,600	52.0	2,680	42,700			
<b>7mm Rem. Mag</b>																										
Hornady 120 Sp. Pt.	Rem. 9½	3.275	Fed.	24					54.0	3,110	59,000	55.0	3,200	58,300	69.0	3,465	58,600	73.0	3,490	58,600						
Hornady 139 Sp. Pt.		3.275		24					57.0	3,035	59,000	55.6	3,070	59,000	67.5	3,260	58,100	70.0	3,295	58,000						
Speer 145 Spitz		3.280		24					48.0	2,765	58,900	47.5	2,780	58,700	61.7	3,090	58,400	64.5	3,150	58,600						
Sierra 160 Spitz BT		3.285		24														62.0	3,020	58,500	65.0	3,075	58,600			
Sierra 175 Spitz BT		3.285		24														61.3	2,900	58,400						
<b>7mm Wby. Mag.</b>																										
Hornady 120 Sp. Pt.	Fed. 215	3.200	Wby.	26											61.3	3,370	c.u.p. 52,500	74.0	3,505	52,100						
Hornady 139 Sp. Pt.		3.280		26														70.9	3,315	52,500	74.8	3,355	c.u.p. 52,300			
Speer 145 Spitz		3.240		26														68.0	3,165	52,200	72.4	3,245	c.u.p. 52,500			
Nosler 150 Spitz		3.250		26														67.3	3,145	52,500	72.0	3,220	c.u.p. 52,400			
Sierra 160 Spitz		3.240		26														64.8	3,045	52,300	70.7	3,110	c.u.p. 52,500			
Sierra 175 Spitz		3.245		26														60.5	2,850	52,200	67.4	2,965	c.u.p. 52,500			
<b>.30 Carbine</b>																										
Hornady 100SJ	CCI 400	1.625	Fed.	20	12.3	1,815	c.u.p. 34,500																			
Cast (GC) 112L		1.625		20	10.3	1,590	c.u.p. 35,700																			
<b>.30-06 Springfield</b>																										
Sierra 110JHP	Fed. 210	3.100	Fed.	24	30.9	2,715	55,900	45.0	3,145	56,400	57.0	3,280	58,300	58.6	3,465	58,100	65.5	2,995	47,300							
Sierra 125 Spitz		3.120		24	30.0	2,575	55,100	42.0	2,915	56,600	55.3	3,170	58,300	56.8	3,275	58,500	63.5	2,895	50,900	63.0	2,815	46,000				
Hornady 150 Sp. Pt.		3.210		24	29.4	2,330	56,000	43.8	2,780	57,000	53.6	2,960	58,400	53.6	3,005	58,500	63.0	2,950	56,400	62.0	2,845	50,600				
Barnes X 150		3.220		24														49.8	2,815	58,500	62.1	2,890	58,500	60.0	2,755	51,300
Nosler 165 Part.		3.220		24														48.3	2,660	58,500	60.0	2,750	57,100	60.0	2,675	51,500
Speer 165 Spitz		3.250		24	29.2	2,295	55,400	40.5	2,610	56,800	51.1	2,785	57,900	50.5	2,835	58,500	62.0	2,880	56,100	62.0	2,824	52,500				
Speer 180 Spitz		3.250		24	28.2	2,210	55,400	39.8	2,505	56,900	49.6	2,695	58,500	48.5	2,720	58,200	60.0	2,800	57,000	60.0	2,710	51,000				
Nosler 180 Part.		3.250		24														57.2	2,685	55,300	59.0	2,670	52,000			
Win. 180 F.S.	Win. W.L.R.	3.200	Win.	24					45.3	2,515	56,800	47.0	2,600	56,500	57.2	2,685	55,300	59.0	2,670	52,000						
Sierra 190 MKing	Fed. 210	3.300	Fed.	24	26.0	2,075	55,600	37.4	2,340	57,400	46.0	2,520	58,300	47.3	2,600	58,500	58.0	2,720	58,100	60.0	2,755	56,600				
Sierra 200 Spitz BT		3.300		24					44.8	2,440	58,300	46.0	2,505	58,500	55.8	2,630	58,500	58.4	2,680	58,400						

continued on next page

See NOTES and KEY on page 55.

## Centerfire Rifle (continued)

Cartridge/Bullet	Primer	Min. OAL (inches)	Case	Bbl Length	Chg Wt	2400 fps	psi	Reloder 7	Chg Wt	fps	psi	Reloder 12	Chg Wt	fps	psi	Reloder 15	Chg Wt	fps	psi	Reloder 19	Chg Wt	fps	psi	Reloder 22	Chg Wt	fps	psi			
.30-30 Win. Sierra 125JFP	Win. 8½-120	2.470	Win.	24				30.0	2,630	c.u.p. 34,100		37.0	2,555	39,900																
Sierra 150JFP		2.525		24				27.5	2,190	c.u.p. 33,800		33.5	2,320	40,400		36.0	2,450	40,600												
Hornady 170JFP		2.545		24				24.0	1,910	c.u.p. 34,500		32.0	2,160	40,100		34.1	2,330	40,500												
.300 Savage Sierra 125SPT	Rem. 9½	2.600	Rem.	24							c.u.p. 44,300		46.0	2,920																
Sierra 150SPT		2.600		24							c.u.p. 41,400		43.0	2,635																
Sierra 165SBT		2.600		24							c.u.p. 40,800		41.0	2,485																
.300 H&H Mag. Hornady 150 Sp. Pt. Fed. 210	3.570	Fed.	24													63.8	3,270	c.u.p. 52,500	75.0	3,275	c.u.p. 52,500									
Speer 165 Spitz	3.555		24													60.9	3,065	c.u.p. 52,500	72.7	3,150	c.u.p. 52,500									
Nosler 180 Part.	3.535		24													58.0	2,910	c.u.p. 52,300	70.3	3,040	c.u.p. 52,500	71.0	3,040	c.u.p. 52,100						
Speer 180 Spitz	3.575		24													56.7	2,850	c.u.p. 52,400	69.8	3,055	c.u.p. 52,500	71.5	3,070	c.u.p. 52,000						
Sierra 200 Spitz BT	3.590		24													55.0	2,725	c.u.p. 52,100	67.0	2,910	c.u.p. 52,100	69.0	2,935	c.u.p. 52,200						
.300 Win. Mag. Hornady 150 Sp. Pt. Win. 8½-120	3.340	Win.	24													59.0	3,105	c.u.p. 61,200	65.3	3,180	c.u.p. 61,000	76.7	3,225	c.u.p. 61,000	81.5	3,275	c.u.p. 60,400			
Speer 165 Spitz	3.340		24													62.0	2,935	c.u.p. 60,600	62.6	2,980	c.u.p. 60,100	74.6	3,070	c.u.p. 60,400	79.4	3,135	c.u.p. 60,800			
Speer 180 Spitz	3.340		24																											
Win. 180 F.S. Sierra 200 Spitz BT	Win. W.L.R.	3.340	24	Win. 8½-120	3.340	24																								
.300 Wby. Mag. Hornady 150 Sp. Pt. Fed. 215	3.540	Wby.	26																											
Speer 165 Spitz	3.510		26																											
Speer 180 Spitz	3.515		26																											
Nosler 180 Part.	3.530		26																											
Sierra 200 Spitz	3.550		26																											
.303 British Hornady 123SP	Win. 8½-120	2.860	Win.	24												38.6	2,750	c.u.p. 43,200	48.0	2,915	c.u.p. 43,000	49.8	3,015	c.u.p. 43,200						
Speer 150 Spitz		2.935		24												31.0	2,400	c.u.p. 41,200	45.0	2,700	c.u.p. 42,900	46.2	2,755	c.u.p. 43,200						
Speer 180 RN		2.940		24												30.0	2,050	c.u.p. 39,600	40.0	2,340	c.u.p. 42,600	43.7	2,515	c.u.p. 43,200						

Cartridge/Bullet	Primer	Min. OAL (inches)	Case	Bbl Length	Chg Wt	2400 fps	psi	Chg Wt	Reloder 7 fps	psi	Chg Wt	Reloder 12 fps	psi	Chg Wt	Reloder 15 fps	psi	Chg Wt	Reloder 19 fps	psi	Chg Wt	Reloder 22 fps	psi			
<b>7.62 x 39</b>																									
Speer 100 Plinker	CCI 200	1.830	Fed.	20	16.5	2,240	c.u.p. 44,900																		
Sierra 110HP		2.055		20	16.0	2,115	c.u.p. 44,800	26.5	2,330	c.u.p. 38,300															
Hornady 123SP		2.155		20	15.3	1,915	c.u.p. 44,900	25.5	2,330	c.u.p. 45,000															
Sierra 150JP		2.000		20	14.8	1,800	c.u.p. 45,000	24.8	2,145	c.u.p. 44,600															
<b>.308 Win.</b>																									
Sierra 110JHP	Fed. 210	2.600	Fed.	24				42.5	3,130	c.u.p. 47,200	50.5	3,200	57,400												
Sierra 125 Spitz		2.700		24			c.u.p. 36,700	40.0	2,920	c.u.p. 47,100	49.0	3,040	57,400												
Sierra 150 Spitz		2.600		24	25.0	2,215	c.u.p. 36,700	37.0	2,750	46,900	45.0	2,755	57,100	46.3	2,880	57,300									
Barnes 150X		2.750		24							45.8	2,750	57,400	45.0	2,815	56,800									
Barnes 165X		2.750		24							43.5	2,590	57,200	43.5	2,675	57,000									
Sierra 165 Spitz		2.700		24							44.0	2,650	57,200	45.5	2,780	57,000									
Sierra 168HPBT	Fed. 210M	2.700	Fed.	24							43.0	2,605	57,200	42.8	2,665	56,600									
Speer 180 Spitz	Fed. 210	2.750	Fed.	24										44.0	2,645	57,500									
Win. 180 F.S.	Win. W.L.R.	2.750	Win.	24							36.0	2,290	55,400	41.5	2,500	57,000									
<b>8mm Mauser</b>																									
Hornady 125SP	Win. 8½-120	2.820	Win.	24							45.0	2,720	c.u.p. 35,500	46.8	2,760	c.u.p. 36,000									
Sierra 150 Spitz		2.975		24							43.0	2,455	c.u.p. 34,900	44.0	2,560	c.u.p. 36,000									
Speer 170 Spitz		3.015		24							40.0	2,280	c.u.p. 35,300	41.4	2,400	c.u.p. 36,000									
<b>8mm Rem. Mag.</b>																									
Speer 170S Spitz	Rem. 9½M	3.500	Rem.	24																82.8	3,315	61,700	87.2	3,350	61,700
Speer 200 Spitz		3.525		24															77.7	3,050	61,600	81.0	3,090	61,600	
Hornady 220 Sp. Pt.		3.600		24															75.0	2,885	61,600	77.0	2,910	61,300	
<b>.348 Win.</b>																									
Rem. 150SP	Rem. 9½	2.790	Rem.	24				48.0	2,750	c.u.p. 34,900															
Rem. 200SP		2.790		24				45.0	2,330	c.u.p. 35,800															
<b>.338 Win. Mag.</b>																			65.0	2,935	c.u.p. 51,300	78.0	3,020	c.u.p. 52,400	
Hornady 200 Sp. Pt.	Win. 8½-120	3.340	Win.	24															74.0	2,910	c.u.p. 52,000	78.0	2,875	c.u.p. 43,200	
Nosler 210 Spitz		3.330		24															75.3	2,865	c.u.p. 52,100	76.0	2,840	c.u.p. 46,200	
Hornady 225 Sp. Pt.		3.325		24														61.8	2,705	c.u.p. 51,600	77.0	2,790	c.u.p. 46,200		
Barnes 225X		3.335		24														56.5	2,590	c.u.p. 51,600	72.0	2,765	p.s.i. 50,900		
Win. 230 F.S.	Win. W.L.R.	3.335	Win.	24														72.0	2,790	p.s.i. 60,500	73.0	2,760	p.s.i. 56,400		
Hornady 250RN	Win. 8½-120	3.330		24														73.0	2,735	c.u.p. 52,300	73.0	2,620	c.u.p. 45,300		
<b>.340 Wby. Mag.</b>																		71.8	2,990	c.u.p. 53,100	85.0	3,095	c.u.p. 53,300		
Hornady 200 Sp. Pt.	Fed. 215	3.660	Wby.	26														70.8	2,930	c.u.p. 53,500	89.2	3,135	c.u.p. 53,500		
Nosler 210 Spitz		3.595		26														84.3	3,075	c.u.p. 53,500	88.0	3,035	c.u.p. 53,400		
Hornady 225 Sp. Pt.		3.645		26														83.7	2,995	c.u.p. 53,500	84.7	2,880	c.u.p. 53,300		
Hornady 250RN		3.665		26														80.7	2,865	c.u.p. 53,500					

See NOTES and KEY on page 55.

continued on next page

## Centerfire Rifle (continued)

Cartridge/Bullet	Primer	Min. OAL (inches)	Case	Bbl Length	2400			Reloder 7			Reloder 12			Reloder 15			Reloder 19			Reloder 22		
					Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi
.35 Rem. Rem. 150SPCL	Win. 8½-120	2.485	Win.	24				32.0	2,290	c.u.p. 30,700												
Cast (GC) 158L		2.485		24				28.0	2,200	c.u.p. 29,800												
Rem. 200SPCL		2.485		24				31.0	2,115	c.u.p. 30,700												
.350 Rem. Mag. Rem. 150SPCL	Rem. 9½M	2.800	Rem.	20				55.0	3,075	c.u.p. 47,500												
Rem. 200SPCL		2.800		20				48.0	2,550	c.u.p. 48,500												
Rem. 250PSP		2.800		20				43.0	2,230	c.u.p. 49,300												
.358 Win. Rem. 200PSP	Win. 8½-120	2.780	Win.	24				38.0	2,420	c.u.p. 46,100	50.0	2,455	c.u.p. 44,100									
Win. 250ST		2.780		24				34.5	2,075	c.u.p. 44,700												
.35 Whelen Hornady 200SP	Rem. 9½M	3.125	Rem.	24				51.5	2,630	c.u.p. 50,300	60.0	2,590	c.u.p. 43,200	60.0	2,675	c.u.p. 44,800	c.u.p.					
Hornady 250RN		3.225		24				47.6	2,330	c.u.p. 50,400	60.0	2,505	c.u.p. 49,700	59.5	2,550	c.u.p. 48,400						
.375 Win. Hornady 220FP	Win. 8½-120	2.555	Win.	24	23.5	1,900	c.u.p. 44,000	36.0	2,260	c.u.p. 45,500												
.375 H&H Mag. Hornady 220FP	Rem. 9½M	3.360	Rem.	24							75.0	2,835	c.u.p. 49,500	77.0	2,980	c.u.p. 50,000						
Hornady 270SP		3.545		24							73.5	2,540	c.u.p. 49,700	73.4	2,685	c.u.p. 49,500						
Hornady 300MC		3.550		24										66.5	2,455	c.u.p. 49,600	79.0	2,540	c.u.p. 49,600			
.378 Wby. Mag. Hornady 270SP	Fed. 215	3.620	Wby.	26										90.5	2,940	c.u.p. 53,300	110.8	3,110	c.u.p. 53,100	115.0	3,050	c.u.p. 47,200
Barnes 300 Solid		3.625		26													108.6	2,960	c.u.p. 53,300	114.0	2,965	c.u.p. 51,600
.38/55 Win. IVI 255SP	CCI 200	2.530	IVI	24	18.0	1,410	c.u.p. 23,500	26.5	1,725	c.u.p. 26,000												
.38/40 Win. 150 Sierra JHP	Rem. 2½	1.585	Rem.	24	14.1	1,425	c.u.p. 13,100															
180 Sierra JHP		1.585		24	13.0	1,305	c.u.p. 13,400	25.8	1,745	c.u.p. 13,500												
200 Hornady FMJ/FP		1.585		24	12.7	1,225	c.u.p. 13,500	24.0	1,610	c.u.p. 13,400												
.416 Rem. Mag Barnes 300X	Rem. 9½M	3.600	Rem.	24							90.0	2,790	c.u.p. 52,100	90.5	2,890	c.u.p. 52,400						
Barnes 350X		3.600		24							85.0	2,525	c.u.p. 52,400	85.0	2,610	c.u.p. 52,400						
Hornady 400RN		3.565		24							82.0	2,390	c.u.p. 52,000	82.0	2,445	c.u.p. 51,700	83.0	2,140	c.u.p. 35,600			
A Square 400 Solid		3.600		24							81.0	2,410	c.u.p. 52,400	81.0	2,455	c.u.p. 50,900	82.0	2,130	c.u.p. 35,600			

Cartridge/Bullet	Primer	Min. OAL (inches)	Case	Bbl Length	2400			Reloder 7			Reloder 12			Reloder 15			Reloder 19			Reloder 22			
					Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	Chg Wt	fps	psi	
<b>.416 Rigby</b> Barnes 300X	Fed. 215	3.650	Fed.	24																103.0	2,590	c.u.p.	
Barnes 350X		3.675		24															101.0	2,455	c.u.p.		
Hornady 400RN		3.725		24															96.0	2,355	c.u.p.		
A Square 400 Solid		3.725		24															96.0	2,360	c.u.p.		
<b>.416 Wby. Mag.</b> Barnes 325X	Fed. 215	3.650	Wby.	26															117.0	2,880	c.u.p.		
Barnes 350X		3.650		26														116.9	2,830	c.u.p.			
Hornady 400SP		3.615		26														117.5	2,720	c.u.p.			
A Square 400 Solid		3.680		26														117.0	2,705	50,500			
<b>.44/40 Win.</b> Rem. 200SP	Rem. 2½	1.590	Rem.	24	14.5	1,230	c.u.p. 12,500																
Cast 240L		1.580		24	12.0	1,130	c.u.p. 12,500	23.5	1,290	c.u.p. 12,100													
<b>.444 Marlin</b> Speer 240SP	Rem. 9½	2.500	Rem.	24	25.0	1,730	c.u.p. 21,900	51.0	2,400	c.u.p. 38,100													
Cast (GC) 240L		2.500		24	22.0	1,725	c.u.p. 27,900	42.5	2,080	c.u.p. 28,900													
Hornady 265FP		2.500		24	25.0	1,715	c.u.p. 22,100	47.0	2,215	c.u.p. 35,800													
<b>.45/70 Govt.</b> Hornady 300HP	Rem. 9½	2.475	Rem.	24	30.0	1,650	c.u.p. 23,000	50.0	2,075	c.u.p. 24,700													
Cast (GC) 385L		2.575		24	25.0	1,340	c.u.p. 21,300	45.0	1,810	c.u.p. 25,100													
Speer 400FN		2.700		24	25.0	1,260	c.u.p. 24,000	40.0	1,580	c.u.p. 24,900	54.0	1,710	c.u.p. 26,100										
<b>.458 Win. Mag.</b> Hornady 300HP	Win. 8½-120	2.950	24	Win.	35.0	1,590	c.u.p. 13,500	70.0	2,555	c.u.p. 41,400													
Cast (GC) 385L		3.000		24	30.0	1,290	c.u.p. 14,200	65.0	2,285	c.u.p. 42,100													
Hornady 500FMJ		3.280		24	35.0	1,415	c.u.p. 32,600	64.0	2,000	c.u.p. 47,000													

NOTES and KEY pertain to Silhouette and Centerfire rifle tables.

See Special Reloading Precautions on page 56.

#### NOTES:

1. Do not intermix cases of different manufacture, nor bullets, nor primers.
2. Be sure that each case is crackfree and completely empty.
3. Unless specifically recommended, use standard primers. Magnum primers are neither needed nor recommended for most calibers.
4. Do not exceed the powder weight shown, and guard against accidental multiple charges of powder.
5. Start with 10% less powder than shown. Work up gradually, watching for signs of high pressure.
6. Be sure that every completed cartridge is not shorter than the length listed.
7. Watch for signs of case head separation.

#### KEY

BR	=Bench Rest	M	=Match	in.	=inches
FMC	=Full Metal Case	psi	=Chamber pressure, piezo system	gr.	=grains
FMJ	=Full Metal Jacket	Vel.	=Velocity		
FN	=Flat Nose	PSP	=Pointed Soft Point	fps	=feet per second
FP	=Flat Point	RN	=Round Nose	c.w.	=powder charge weight
FS	=Fail Safe	SB	=Solid Base	c.u.p.	=chamber pressure, in copper units
GC	=Gas Check	SJ	=Semijacketed	Min	=minimum overall
HB	=Hollow Base	SP	=Soft Point	OAL	length, measured from base to tip of bullet
HC	=Hollow Cavity	Sp. Pt.	=Spire Point		
HP	=Hollow Point	WC	=Wad Cutter		
J	=Jacketed	Wt	=weight		
L	=Lead	Bbl	=barrel		



## Pistol and Revolver Cartridges Special Reloading Precautions

Most pistols and revolvers function best when loaded with a quick-burning powder such as Bullseye. Since peak pressure is reached very quickly, the **SEATING DEPTH** of the bullet is very important: the deeper the bullet, the higher the pressure. If the bullet is seated too deeply, dangerous pressures will be generated, which could burst the gun and cause severe personal injury (including death).

Equally critical is the powder charge. Guard AGAINST multiple charges when reloading. Certain cartridges (notably .38 Special) have been reloaded accidentally with double and even triple charges, with catastrophic results when fired in the gun.

### A. Prevent deeply seated bullets.

1. Your assembled cartridges must be as long as, or longer than, the minimum length listed for the combination you are reloading.
2. Set your bullet station accordingly and lock tool securely.
3. Keep bullet station clean of accumulating lead and grease.
4. Inspect all loaded rounds for overall length.
5. Be sure every bullet is held tightly by shell mouth, especially pistol loads (recoil drives magazine against bullet noses of contained cartridges).

### B. Prevent multiple charges.

1. **Handloading:** Keep track of every powder charge, then look inside all shells and compare powder levels.
2. **Progressive reloading:** Be sure every shell is truly empty; don't back up the turret; don't jiggle the handle; don't use a shell to clean out the powder train (use a paper cup or equivalent).

### C. Inspection.

1. Discard cases with split mouths.
2. Discard cases with enlarged primer pockets.
3. Do not use cases that are designed for primer-propelled practice cartridges; such cases may not be designed for full power loads.

## Physical Effect of Gun Recoil (Kick)

The rearward motion of every gun, its recoil, increases when heavier shot or heavier bullets are fired, and when higher velocity loads are fired. This motion must be opposed by the shoulder, or the pistol hand, of the shooter. Whenever the recoil is perceptibly annoying to the shooter, accuracy on succeeding firings undoubtedly diminishes.

When the shooting condition demands heavy loads and high velocity, recoil kick can be reduced by using a heavier gun, and by spreading the force over a larger area of the anatomy, such as by using a wider stock, larger grip, plus shoulder pad or softer grip.

Excellent publications available to the reloader, plus his or her own growing sophistication, have generated a wholesome trend away from maximum loads and toward accuracy of loads no more powerful than needed to accomplish the particular shot. Reducing recoil increases accuracy.

Contributing to increased accuracy as well as the pleasantness of shooting is in two main areas:

1. This *Reloaders' Guide* includes many reduced loads.
2. Our research indicates that the burning rate of powders has a modest effect on recoil. For example, whenever two or more powders are listed for the same load, the slower one usually is chosen by the expert shooter as giving milder felt recoil. An intriguing aspect of reloading at home is the freedom to assemble, for example, trap loads with Red Dot or Green Dot powder, then to shoot them alternately to decide which seems more comfortable.

# Handloading Precautions

---

1. Understand what you are doing and why. Read handbooks and manuals on reloading. Talk to experienced reloaders. Write or call suppliers of components if you have questions or are in doubt.
2. Stay *alert* when reloading. Do not reload when distracted.
3. Establish a loading procedure and follow it. Do not vary your sequence of operations.
4. Examine empty cases (shotshell or metallic) to be sure they are in good condition before reloading. Never force live cartridges into or out of the chamber of a gun.
5. Do not use cases that are designed for primer-propelled practice cartridges; such cases may not be designed for full power loads.
6. Do not *ream out* or *enlarge* flash holes of metallic cartridge cases. This may change the ignition rate and result in dangerous pressures.
7. Do not punch out live primers. Fire the empty primed shells in a gun.
8. Do not mix primers. Primers differ in brisance of ignition, which affects pressure and velocity. Use only the primer listed.
9. The shotshell loading data in the *Reloaders' Guide* are for **LEAD SHOT only. DO NOT USE STEEL SHOT.**
10. One-piece plastic wads for shotshells vary in compressibility and gas-sealing effectiveness. Use only the wad listed.
11. If you "throw," or measure powder charges by volume, check-weigh the charge frequently. Do not mix powders.
12. Do not use powders near a flame, spark-producing machinery, or heating device. Do not expose powders to temperatures above 100°F.
13. Keep out of reach of children.
14. Do not smoke while reloading.

## Crusher/Piezo Pressure Tabulation

---

The following table lists the maximum average pressures, measured by the crusher system (c.u.p.) or piezo system (psi), utilized for the centerfire rifle recommendations in this brochure.

The values listed in the "c.u.p" and "psi" columns are approximately the same pressure. The difference is due to the measuring system used and does not indicate that a pressure change has occurred.

Cartridge	C.U.P.	PSI	Cartridge	C.U.P.	PSI
.22-250 Remington	53,000	62,000	7mm Remington Magnum	52,000	61,000
.222 Remington	46,000	50,000	.280 Remington	50,000	60,000
.223 Remington	52,000	55,000	.30 Carbine	40,000	
6mm Remington	52,000	65,000	.30-06 Springfield	50,000	60,000
.243 Winchester	52,000	60,000	.30-30 Winchester	38,000	42,000
.25-06 Remington	53,000	63,000	.300 Savage	46,000	
.257 Roberts	45,000	54,000	.300 Winchester Magnum	54,000	64,000
.257 Roberts +P	50,000	58,000	.303 British	45,000	49,000
.270 Winchester	52,000	65,000	.308 Winchester	52,000	60,000
7mm-08 Remington	52,000	57,500	8mm Mauser	37,000	
7-30 Waters	40,000	45,000	8mm Remington Magnum	54,000	65,000
7 x 57 Mauser	46,000	51,000	.338 Winchester Magnum	54,000	64,000
			.35 Remington	35,000	
			.45-70 Government	28,000	

## Notes

## **Some Publications on Reloading**

These and other good literature pertinent to reloading usually are stocked at local gun and ammunition retail stores.

<u>Title</u>	<u>Publisher</u>
<i>Basic Rules for Reloading Safety</i>	National Reloading Manufacturers Association 4905 S. W. Griffith Drive Beaverton, OR 97005
<i>Handloading</i>	NRA Bookservice 11250 Waples Mill Road Fairfax, VA 22030
<i>Speer Reloading Manual</i>	Blount Industries Box 856 Lewiston, ID 83501
<i>RCBS Reloading Guide</i>	RCBS Box 1919 Oroville CA 95965
<i>Tips on Better Reloading</i>	Remington Arms Bridgeport, CT 06602
<i>Hornady Handbook of Cartridge Reloading</i> <i>Hornady Reloading Tools and Accessories</i>	Hornady Mfg. Co. Box 1848 Grand Island, NB 68801
<i>Sierra Bullets Reloading Manual</i>	Sierra 10532 Painter Avenue Santa Fe Springs, CA 90670
<i>Lyman Cast Bullet Handbook</i> <i>Lyman Shotshell Handbook</i> <i>Lyman Pistol and Revolver Handbook</i>	Lyman Products Middlefield, CT 06455
<i>Nosler Reloading Manual</i>	Nosler Bullets, Inc. P.O. Box 671 Bend, OR 97709
<i>How to Reload Shotshells and Why</i>	MEC 715 South Street Mayville, WI 53050
<i>Ponsness-Warren Catalog</i>	Ponsness-Warren Box 8 Rathdrum, ID 83858
<i>Handloaders' Digest</i> <i>ABC's of Reloading</i>	DBI Books 540 Frontage Road Northfield, IL 60093
<i>The Handbook of Shotshell Reloading</i>	SKR Industries, Inc. P.O. Box 1382 San Angelo, TX 76092

**ALLIANTTECHSYSTEMS**

Alliant Techsystems  
New River Energetics  
Route 114 P.O. Box 6  
Radford, VA 24141-0096

Visit our web site at  
<http://reloading.ATK.com>