

SCIENTIFIC AMERICAN

[Entered at the Post Office of New York, N. Y., as Second Class Matter. Copyrighted, 1888, by Munn & Co.]

A WEEKLY JOURNAL OF PRACTICAL INFORMATION. ART, SCIENCE. MECHANICS, CHEMISTRY, AND MANUFACTURES.


Vol. LVIII.—No. 11.
[NEW SERIES.]

NEW YORK, MARCH 17, 1888.

[\$3.00 per Year.]

THE LICK OBSERVATORY OF THE UNIVERSITY OF CALIFORNIA.

James Lick, whose name has already acquired a world-wide fame as the establisher of the Lick Observatory, was born in 1798, in Pennsylvania. He led a somewhat adventurous life, and before he was thirty years old had accumulated a few thousand dollars. This he had made principally in South America, where he spent some years. In 1827 he went to California and visited the old mission town of San Francisco. The splendid harbor, the only one on many miles of coast, greatly impressed Mr. Lick, and he began purchasing land. Twenty-one years later, when gold had been discovered, and when the rush to California began, his investments acquired new value, and he ultimately became immensely rich. He was a man of very secluded habits, was a skillful mechanic, and, it is said, was especially fond of astronomy. Toward the end of his life he lived near San



THE LICK OBSERVATORY MOUNT HAMILTON CAL.

Jose, in the Santa Clara Valley. In 1874 he made over by deed to a body of trustees the sum of two millions of dollars for various public and philanthropic uses, and in 1875 made a revised deed to the same general effect. Besides various charitable donations, it included the following gifts: \$150,000 for free public baths in San Francisco; \$100,000 for statuary for the new City Hall of that city; \$60,000 for a monument to Francis Scott Key, the author of "The Star Spangled Banner;" \$540,000 to endow the California School of Mechanic Science in San Francisco; and \$700,000 for procuring for the University of California "a telescope of greater power than any yet made." The total value of the trust fund was estimated at \$5,000,000.

As the site for his observatory he selected Mount Hamilton, near his home in the Santa Clara Valley. He died October 1, 1876, aged 78 years. His body is interred under the base of the great telescope, (Continued on page 162.)



PROF. EDWARD S. HOLDEN, DIRECTOR.



THE LICK OBSERVATORY AND ITS GREAT TELESCOPE.

Scientific American.

ESTABLISHED 1845.

MUNN & CO., Editors and Proprietors.

PUBLISHED WEEKLY AT

No. 361 BROADWAY, NEW YORK.

O. D. MUNN.

A. E. BEACH.

TERMS FOR THE SCIENTIFIC AMERICAN.

One copy, one year, for the U. S. or Canada. \$3 00
One copy, six months, for the U. S. or Canada. 1 50
One copy, one year, to any foreign country belonging to Postal Union, 4 00

The Scientific American Supplement

is a distinct paper from the SCIENTIFIC AMERICAN. THE SUPPLEMENT is issued weekly. Every number contains 16 octavo pages, uniform in size with SCIENTIFIC AMERICAN. Terms of subscription for SUPPLEMENT, \$5.00 a year, for U. S. and Canada. \$6.00 a year to foreign countries belonging to the Postal Union. Single copies, 10 cents. Sold by all newsdealers throughout the country.

NEW YORK, SATURDAY, MARCH 17, 1888.

Contents.

(Illustrated articles are marked with an asterisk.)

Table listing various articles such as 'American trade and enterprise in Venezuela', 'Lick observatory of the University of California', 'Blasted stumps, logs, etc., device for', etc.

TABLE OF CONTENTS OF

SCIENTIFIC AMERICAN SUPPLEMENT

No. 687.

For the Week Ending March 17, 1888.

Price 10 cents. For sale by all newsdealers.

Table listing sections I through XI, including Botany, Chemistry, Civil Engineering, Electricity, Mathematics, Mechanical Engineering, Medicine and Surgery, Miscellaneous, Naval Engineering, Optics, and Technology.

William I., King of Prussia and Emperor of Germany.

On March 9, 1888, the Emperor William I. of Germany breathed his last. His death occurred at about half past eight in the morning. He was born on March 22, 1797.

He was a son of Frederick William III. of Prussia and of Queen Louise. He was named Wilhelm Friedrich Ludwig. In early life he accompanied the army that contended with Napoleon I.

Deplorable Condition of the New York Quarantine Establishment.

The quarantine establishment, port of New York, consists of the landing station at Clifton, Staten Island, where vessels arriving receive the official inspection of the Health Officer.

The quarantine property, land, buildings, and plant generally, owned by the State of New York, is in the custody of a body called the Commissioners of Quarantine, appointed by the State and responsible to it.

In November last the New York Academy of Medicine appointed a committee of seven prominent medical men to visit and report upon the condition and needs of the quarantine establishment.

Of Hoffman Island they say: "The ground is soft, uneven, full of recesses in which water, refuse, etc., will be retained without any chance of their being cleaned."

"The present buildings used for the residence of the people quarantined are badly adapted for their purpose. They should be razed or remodeled."

"There is now almost no adequate separation of ages, sexes, or families. No suspected groups can now be isolated. There is no opportunity at all to separate those who may be amply able and willing to pay.

There are no proper accommodations, bedsteads, bedding, tables, forks, knives, spoons, plates or towels. As an instance of the hardships caused by want of means of isolation, a steamer is at present detained at quarantine, owing to the passengers and crew having been exposed to smallpox.

"The supply of water is insufficient, and warm water is almost entirely wanting."

"For a population now there of more than five hundred persons, there are about four water closets, each closet having three or four hoppers, some of which are not flushed at all, and all of which are old, badly constructed, and out of repair."

"The cleansing and disinfecting plant is entirely inadequate, in extent and efficiency, thus making it impossible to cleanse the persons of the quarantined or disinfect their luggage, either expeditiously or thoroughly."

"The 'sulphur room' should not be where it is and as it is; for, being on the main floor of a building occupied by masses of the quarantined, the latter are constantly exposed to fresh infection from clothing brought in to be disinfected, and to the fumes of sulphurous acid when the door of the sulphur room is opened."

Among the improvements needed, the committee suggests the following:

The surface of the island should be cemented or asphalted, and should be raised sufficiently above the exterior wall to allow of good drainage. It should be smooth and hard to allow of thorough cleansing, and prevent the lodgment of filth or germs.

If the present large buildings are to remain, the roofs should be repaired. Each main floor should be subdivided into two or more portions by solid partitions, to allow the grouping of the inmates according to age, sex, and relationship. Each apartment should have a separate entrance and be thoroughly ventilated.

The present administration building should either be remodeled or a new one erected. Reconstruction will prove costly and unsatisfactory, and a new building would be better. It should contain the medical officer's apartments (who should also be superintendent) and quarters for an engineer, and with private kitchen; also an extension on one of the docks, the disinfecting plant, storage rooms, laundry, etc., together with a furnace suitable for burning actually infected bedding, clothing, food articles brought in by infected passengers, kitchen refuse, etc.

Separated from these apartments there should be a large kitchen, with accommodations for cooking meals for eight hundred or one thousand persons; rooms for the attendants; boiler room, containing at least two boilers for adequate power and security in case of accident to one; engine, pumps, and apparatus for electric lighting. The sleeping and living rooms for the employes, together with three rooms for the resident physician, may be placed in a separate building.

The boilers should be of sufficient capacity to heat all the buildings, and to furnish steam in great abundance for disinfection, cooking, and washing. They should, if possible, be placed in a separate building, or the present one be devoted to their use.

There should be a small isolated building, easy of access to the dock, where persons taken suddenly ill could be at once placed, prior to their removal to Swinburne Island. It should contain at least four rooms, to admit of the separation of the sexes and of diseases, and should be provided with two water closets and two baths. The necessity for this hospital was recently illustrated by the simultaneous presence of measles, mumps, cholera, rheumatism, and pneumonia, and further made necessary by the great difficulty which attends conveying the sick from Hoffman to Swinburne Island in stormy weather, against opposing tide or with heavy sea.

Soil pipes and sewers should be of best construction, with absolutely tight joints, and should empty below low water. There should be a flushing tank of approved model provided for each line of sewer. No sewage should be allowed to pass to the bay without being subjected to chemical treatment.

There ought to be many water closets in semi-detached buildings or small towers. If the latter, there should be nine buildings—eight for detained persons and one for employes—or more than this if the passengers are divided into smaller groups. The floors and walls should be non-absorbent, and the apartments heated. The closets should be of a kind admitting of inspection of evacuations, of subsequent disinfection, and of thorough flushing. They should be flushed with a disinfecting solution pumped into their respective reservoirs by steam pumps in the administration building.

The lavatories should be in semi-detached buildings, properly warmed and ventilated, and should contain stationary bath tubs and a few portable ones, and in sufficient number to bathe five hundred persons in one day. They should also contain fixed basins of the most approved pattern, and in such number as to facilitate rapid use. Slop sinks should be provided in a separate apartment, and sinks for dish washing should be off the dining room.

The laundry should be in a building with accommodations for washing the bedding and clothing of eight hundred or one thousand persons. It should have stationary but not wooden tubs; also boilers, rinsers, wringers, and all the modern appliances, supplied with steam. There should be a capacious dry steam drying room, and all of sufficient capacity to pass through the clothing of eight hundred or one thousand immigrants in as short a time as possible.

Each pavilion or apartment should be provided with iron beds, wire mattresses, bedding, tables, chairs, etc., of the best models, the latter so that detained persons need not be forced to sit or lie upon the floor during the day. Bedding should be simple in quality, abundant in quantity, and kept scrupulously clean, and when not in use carried to a suitable place for airing and storage.

Dishes, spoons, knives, forks, and all such necessary articles should be provided, and should be kept in the custody of the employes, except when in use, and be cleaned by the employes and not by the detained persons.

If the present buildings are to remain, a space could be partitioned off in one corner of each of the large rooms, with accommodation for twenty-five or fifty sitting at a narrow table. They should be accessible from the hallway, not from the main rooms, and should be kept locked except during meals. With separate buildings or pavilions, provision could be made in a central building for serving meals at separate tables to those in the different rooms.

Complete simple suits of clothing should be provided for the temporary use of immigrants during the disinfection of their own clothing and baggage, and such clothing should be carefully cleaned, or, in case of suspected infection, destroyed.

There should be an abundant supply of towels for the wash and bath rooms.

The disinfecting plant should be located in a separate building near the water's edge. The plant should consist of two or more large iron cylinders or chambers. These should be lined with steam pipes connected with a superheater, so that a dry temperature of at least 220° Fah. could be easily obtained. It should be arranged so that moist steam under fifteen or twenty pounds pressure could be introduced.

The sources and collection of water needs careful consideration, as a plentiful and pure supply is of the first importance. It would be wise to fill up the present cisterns and construct new ones, with every safeguard against contamination. The water used for drinking, cooking, washing utensils, dishes, etc., should be above suspicion, and, at stated times, critically examined. All collections of water should be carefully protected from surface drainage. Rain water for storage should be taken from roofs not liable to possible contamination. It would be well to provide for an emergency by having a large reservoir to which water could be brought in case of drought. Water for drinking and cooking might be brought in water boat from the Croton supply.

Some provision should be made to relieve the tedium that must befall a large shipload of passengers who, after encountering the dangers and sufferings of an ocean voyage, are unwillingly detained in full sight of their port for a considerable period of time, or it may be until the fact has been made clear that they are or are not to be victims to a dread disease.

There should be at time of occupation a resident medical officer on the island, who should be superintendent, and also skilled in every detail of modern sanitary science.

The approach to Swinburne Island is defective, owing to a bar between it and Hoffman Island. It is difficult to land the sick, as there is no protection from the wind.

The present pavilions are too low on the ground, and with little or no air space beneath the floors. The floors of all the wards are defective. The ground beams are giving way, and there appears to be no ventilation underneath.

The wards are lacking in ventilation, there being no adequate roof ventilation. At present the air currents are likely to be blown from one ward into another.

The remains of patients who have died of contagious or infectious disease should be subjected to such processes as would render them, before burial, innocuous, and prepare them for a decay which would not imperil the living.

The islands are small. The buildings are all most combustible. A fire occurring on Hoffman Island, crowded as it was last autumn, would have driven panic-stricken men, women, and children into the sea.

This danger is equally great on Swinburne Island,

though it is probable that the crowding there will never be so great. The more helpless condition of the sick, however, in hospital wards would increase their peril. The fire apparatus in both places is entirely insufficient. The limited area of each island would make any fire apparatus insufficient if the buildings happened to be crowded and a high wind were prevailing at the time of the conflagration. All buildings on such islands for similar purposes should be fireproof.

As a related matter we would allude to the possible effect produced upon the business interests of New York and the country at large, if cholera were permitted to invade the dense population of the city. It is estimated that about one hundred thousand dollars a day are received by those hotels in the city of New York from which people would flee if an alarm of cholera existed there. The amount of money received over the counters of shops from those who frequent the city to buy its innumerable wares cannot be estimated. It is millions. Hundreds of millions of dollars are annually produced in values in our various factories. To disturb the peace and industrial interests of the city, by permitting the irruption of cholera through defects in quarantine, would inflict an injury upon business beyond computation.

The time consumed in reaching San Francisco by railroad is about that of the possible maximum period of incubation of cholera. The germs of any of the contagious diseases admitted into the port of New York by inadequate quarantine might be conveyed to any portion of the United States, fructifying as they went. Every citizen in the United States and British provinces has, therefore, a personal interest in the condition of the New York quarantine. The existence of cholera in New York would cause the entire country to quarantine against the city. In this way interstate commerce would be paralyzed or seriously embarrassed. As regards the effect upon the health and death rate of the people we cannot even surmise, as that question would turn on the efficiency of the sanitary police. The law of cholera, its propagation, limitation, and extinction, are so well understood that the disease may be said, without presumption, to be subject to scientific prevention or control.

If there is neglect in this matter, and cholera, which has threatened to invade our port for more than three years, and has recently been brought to quarantine, should appear in the spring, and, favored by warm weather, pass an imperfect quarantine and reach New York City or Brooklyn, or possibly extend beyond to near and remote places, public opinion would seek out the blameworthy and visit them with a condemnation which no seclusion would be deep enough to smother or mitigate.

PHOTOGRAPHIC NOTES.

Making Portraits Indoors.—In a communication received from a correspondent who has experimented in taking photographs indoors, he states that he has succeeded in making excellent portrait negatives, equal in fact to the results usually obtained under a skylight, as follows:

"Select a good sized north window, place the sitter about three feet back from the window, and hang up in the rear of the sitter some gray material for a background, also hang up a white sheet a few feet from the sitter on the dark side to reflect as much light as possible, then arrange the camera and stop down the lens so as to give say from four to eight seconds' exposure. Have a mirror, size about 2 feet by 3 feet, ready within reach, and immediately upon removing the cap from the lens seize the mirror, and with it direct the light upon the dark side of the sitter's face, giving the mirror a swaying motion during the exposure. When sufficient exposure has been given, put down the mirror and cap the lens. The sitter should be cautioned against following the movements of the mirror with the eyes."

Some recent experiments made with the magnesium flash light show that it can be utilized to good advantage in making portraits beside a window as above described, in a much shorter time. The light takes the place of the mirror. By placing the light compound on a table five feet away from the person, in such a position as to equally illuminate the shadow side, it is only necessary in making the exposure to quickly remove the cap from the lens, set off the flash light, and immediately recap the lens. It is advisable that the subject get accustomed to the suddenness of the flash, by making one or two preliminary flashes before exposing the plate. The lighting of the shadow portion of the face is very easily controlled, for if the light is flashed close to the sitter, the shadow will be less, but if flashed quite a distance away the shadow will be greater. Hence any degree of softness or balance between the daylight on the one side and shadow on the other is readily obtained.

Toning of Silver Prints.—In a communication to the Derby Photographic Society, Mr. Edward J. Lovejoy says: I have chosen the "Toning of Silver Prints" as the subject upon which to offer you a few remarks this evening, and trust that what little information you may gain from them may be of use to

some of you. As a preliminary to toning, I may mention that the color of the print is much influenced by the character of the negative, also that unless you get a good negative—that is, one having a wide range of tones—you cannot get a good silver print. Allowing that your negative is all that can be desired, and after printing somewhat deeper than the finished print is required to be, in order to allow for loss in the subsequent operations, the print is removed from the printing frame, trimmed, and put into a dish of water to dissolve out all the free silver, frequently changing the water till it no longer shows signs of milkiness, then place it into another dish of water in which a little common salt has been previously dissolved. This converts any remaining free nitrate of silver into chloride, which is afterward dissolved out of the film in the fixing bath. I believe the salt bath to be very essential, and for this reason: it causes the prints to take a little longer to tone, by which they get a much finer deposit of gold on their surface, which adds to their permanency.

After the print has been in the salt bath a few minutes it is rinsed again in water, and is ready for toning. There are several kinds of toning baths, with nearly all of which excellent results can be obtained. I will here, however, give you the formulæ for two only, both of which I use myself, and get very good results: Chloride of gold, one grain; acetate of soda, twenty grains; water, eight ounces. This should be made at least twelve hours before using. The other is: Chloride of gold, one grain; water, twelve ounces; borax, half an ounce. Sufficient bicarbonate of soda should be put into the gold solution to neutralize any acid that may be in it. This bath may be used as soon as cold, for it is necessary to dissolve the borax in hot water, and, when cold, add the gold to it. This is an important point—the gold must be added to the borax, and not the reverse. The print is now placed in the toning bath, printed side down, and moved about to expel any air bells which may have adhered to the under surface, and it is well to keep the solution in motion till toning is completed, as, where there are a number of prints in the bath, it causes the gold to deposit equally on all.

The print should remain in the bath till of a fine purple tone, which usually takes from twelve to fifteen minutes, and I recommend the bath to be used at a temperature of about 70° Fah. The print is then taken out and placed in a solution composed of methylated spirit four parts, water one part. This will prevent blisters from appearing on the print, which is a source of great trouble, and very prolific with some brands of ready sensitized paper. It is then put into the fixing bath, made of hyposulphite of soda, two ounces; water, twenty ounces; liquor ammonia, fifteen drops. Fixation will be complete in fifteen or twenty minutes, when it should be taken out and washed in repeated changes of water, in each of which it should remain five minutes, and between each change it should be laid upon a piece of plain clean glass, face down, and a squeegee passed over the back—this is a very effectual way of removing the hypo. out of the print—then wash in running water for several hours.—Reported in Br. Jour. of Photography.

Medicinal Qualities of Onions.

The free use of onions for the table has always been considered by most people a healthy and desirable vegetable, and but for their odor, which is objectionable to many, they would be found more generally on our dining tables.

For a cold on the chest there is no better specific, for most persons, than well boiled or roasted onions. They may not agree with every one, but to persons with good digestion they will not only be found to be a most excellent remedy for a cough, and the clogging of the bronchial tubes which is usually the cause of the cough, but if eaten freely at the outset of a cold, they will usually break up what promised, from the severity of the attack, to have been a serious one.

A writer in one of our medical journals recently recommended the giving of young raw onions to children three or four times a week, and when they get too large and strong to be eaten raw, then boil and roast them, but not abandon their free use.

Another writer, advocating their use, says: During unhealthy seasons, when diphtheria and like contagious diseases prevail, onions ought to be eaten in the spring of the year at least once a week. Onions are invigorating and prophylactic beyond description. Further, I challenge the medical fraternity or any mother to point out a place where children have died from diphtheria or scarlatina anginosa, etc., where onions were freely used.

To Perforate Earthenware.

A method which is said to be very satisfactory is recommended by Professor Stuart as follows:

Instead of a drill a soft copper rod or pipe is used in the lathe, it being fed with a mixture of powdered emery and linseed oil. The emery is embedded in the copper by the friction, and cuts right through the hardest material in a very short time.

THE LICK OBSERVATORY.

(Continued from first page.)

which rises above his remains as a fitting monument to one of the world's greatest benefactors and philanthropists.

In administering their trust the custodians met with legal obstacles and suits brought by his relatives. These delayed the carrying out of his plans, but eventually a settlement was reached. On June 30, 1883, the corner stone of the observatory, to which this article is devoted, was laid, and to-day the work is practically complete. When Mount Hamilton was selected as the site for the Lick Observatory, in order to test its atmospheric conditions, Professor S. W. Burnham, the discoverer of many double stars, was invited to observe there in 1879. Owing to the dryness of the air, and its excellent quality for astronomical work, his six inch telescope described many stars, catalogued by Professor Otto Struve as double, into triple stars. Mr. Lick died in 1876, and the original plans for the observatory were determined by Captain Richard S. Floyd, president of the trustees, and Mr. T. E. Fraser, superintendent of construction, acting under the advice of Professor Edward S. Holden, and Professor Simon Newcomb, of the Naval Observatory, in Washington. Many noted astronomers have been interested in the work, and this will probably be the most famous observatory in the world. It owns about 1,550 acres of land, a portion of which will eventually be made into a public park, and the graded road of twenty-six miles leading to the summit of Mount Hamilton from San Jose may, perhaps, become a direct route to the Yosemite Valley. Since 1880, when the work was first begun, 7,000 tons of rock and earth have been removed to level a plateau upon which the buildings stand. They are constructed of solid masonry, and are of simple but effective architecture, and include the main building—287 feet long—containing the directors' and secretary's offices, the library, clock rooms, etc., with the large dome at its southern end for the large telescope, and a smaller dome for the 12 inch equatorial at the northwest corner, the meridian circle house, the transit house, the photographic laboratory, and several temporary wooden workshops. The dwelling house of the astronomers, 63 x 60 feet, stands below the summit and is connected with the plateau by a bridge. The surrounding peaks have been named from several famous astronomers.

In speaking of the outlook from Observatory Peak, which is 4,302 feet in height, Professor Holden says: "It would be difficult to find in the whole world a more magnificent view than can be had from the summit just before sunrise, on one of our August mornings. The eastern sky is saffron and gold, with just a few thin horizontal bars of purple and rosy clouds. The sharp outlines of Copernicus and Kepler are seen in sharp profile against the brilliant background. Orion, Procyon, the Twins, Sirius, are in the morning sky, and Venus is brilliant and steady against the stars. The instant the sunbeams touch the horizon the whole panorama of the Sierra Nevada flashes out, 130 miles distant. Toward the south and west the beautiful valley of Santa Clara lies,

dotted with farms and vineyards, and bordered toward the sea by Loma Prieta and the Santa Cruz Range. The winding road to San Jose, which takes twenty miles of twisting to accomplish the thirteen miles of air line, lies like a dusty snake at your feet. The Bay of San Francisco looks like a piece of a child's dissecting map, and is lost in the fogs near the city. The buildings of the city seem strangely placed in the midst of all the quiet beauty and the wild strength of the mountains. Then you catch a glimpse of the Pacific in the southwest and of countless minor ranges of mountains and hills that are scattered toward


to the eyepiece of the telescope, which at times is far above the base of the dome, was planned by Sir Howard Grubb, of Dublin. This is an elevating floor 61½ feet in diameter, weighing 50,000 pounds, and is moved up and down through a space of 16 feet. It is highly probable that the present system will not be sufficiently powerful to raise the flooring rapidly enough, but in this event the hydraulic system can be altered, or steam or electricity substituted. The actual speed required can only be determined after a series of experiments have been made.

The dome for the 12 inch equatorial is 25 feet wide, weighs 8 tons, and its observing slit, which extends beyond the zenith, is 3 feet wide. The meridian circle house is 43x38 feet. Its walls are double, the outer frame of galvanized iron, the inner one of California redwood. Between these is an air space 24 inches wide, which encircles the buildings. There is also an air space above the ceiling, which communicates with the room and with the air spaces of the walls, and on the west there is a ventilating tower two stories in height, which connects with the room of the meridian transit instrument. By these means the temperature of the building is kept the same as that of the external air. The transit house adjoining the meridian circle house is built of iron, with a wooden lining, and is arched by a curved shutter, which is controlled by levers, planned by Sir Howard Grubb. The photographic observatory, north of the transit house, is a small wooden building, with brick foundation. The tube of the photoheliograph telescope enters this house, and a brick pier supports the photoheliograph. A room in the second floor of the main building is also fitted for photography.

The large telescope, which embodies the expressed object of the \$700,000 donation, was mounted by Warner & Swasey, of Cleveland. The tube is nearly cylindrical, and is 60 feet in length. There are three finders, 6, 4, and 3 inches in aperture, and in addition to these the 12 inch equatorial can be quickly attached, as a pointer, for photographic work if the controlled driving clock does not work satisfactorily. The lens is 36 inch clear aperture, being the largest object glass in the world, and has a 678 inch focus. The flint disk was obtained from Feil, in April, 1882, and after nineteen failures the crown glass disk was cast successfully in September, 1885. The third photographic crown lens was purchased from Feil in 1886, and broke while in the hands of the Clarks. The trustees of Yale University then offered their 27 inch flint glass to the Lick Observa-

tory, but this was too yellow, and in 1887 Mr. Alvan G. Clark bought in Paris, from Feil, the crown glass, which is worked into a third lens. In addition to its magnifying power and its perfect definition, *i. e.*, neatness, accuracy, etc., this telescope has great light-gathering power, and stars may be seen through it which are 30,000 times fainter than the faintest seen by the naked eye, and the moon will appear under the same conditions as if it were seen by the naked eye at about 200 miles from the earth.


It is interesting to compare this telescope with the simple instrument made by Galileo in 1609, consisting of a single leaden tube with a plano-convex lens at one end for an object



LICK OBSERVATORY—THE MERIDIAN INSTRUMENT.

every point of the compass, while, if the atmosphere is especially clear, you can plainly see to the north Mount Shasta, 175 miles distant."

The large dome, built by the Union Iron Works, of San Francisco, is 75 feet in diameter and its moving parts weigh 100 tons. It revolves upon wheels which run on hardened steel balls. A man merely pushing against it can move the entire dome. The usual motive power is obtained from a water engine which can rotate the dome 360° in less than 9 minutes. Its diameter changes ½ inch in the extreme change of temperature, and its track is given a smooth and oiled surface to slide upon. The observing slit is 9½ feet wide, and the pintle of the shutter is placed eccentrically. A practical device for carrying the observer




THE ELEVATING FLOOR—RAISED—AND THE GREAT TELESCOPE PIER.

glass, and a plano-concave lens at the other end for an eyepiece, and magnifying three times. Ever since Galileo's brilliant discoveries with this "optick tube," described by Milton in his visit to Padua, the growth of the telescope has been of steady progress, in spite of the opinion of a cotemporary professor of Galileo in the University of Padua, who argued that "things invisible to the naked eye are useless and do not exist." In tracing its development briefly we find that the difficulties in obtaining good glass led Newton to construct a reflecting telescope in 1688, which magnified 39 times, the speculum or mirror being made of an alloy of copper and tin. Improvements followed which finally resulted in Herschel's finely constructed instruments, in the large six foot reflector in its gigantic frame, made by Lord Rosse, and in the celebrated reflectors of the present time. The reflecting continued to supplant the refracting telescope until about 1753, when Dolland, an English optician, showed that lenses of flint and crown glass could be combined in such a manner that their dispersive powers would neutralize each other, and this is the principle of construction of the achromatic objective now in use, consisting of an outer double convex lens of crown glass and an inner lens nearly plano-concave of flint glass.

The 12 inch refractor, which was originally made for Dr. Henry Draper's private observatory at Hastings, N. Y., by Alvan Clark & Sons, is of the finest construction. The object glass of the 6½ inch equatorial was also made by the Clarks, and is provided with a portable mounting made by Warner & Swasey. The 4 inch comet seeker, made by Alvan Clark & Sons, has a focal length of 33 inches. The rays fall on a reflecting prism, and are bent into a horizontal plane. The eye of the observer moving in azimuth while the telescope is in altitude can cover the whole sky. The motion is effected by turning a crank. This was bought on Prof. Newcomb's recommendation.

The photoheliograph is mounted south of the transit house. The transit instrument determines the axis of the photoheliograph, and this is also used as a collimator for the transit. The 6 inch Repsold meridian circle was delivered in 1884, after having been inspected by Profs. Auwers and Krueger, of Berlin. The declino-graph was made under the supervision of Dr. Johann Palisa, of Vienna, to fit either a 12 inch or 6 inch equatorial. The universal instrument made by Repsold consists of a telescope containing a prism, into which the rays of light are reflected. Its aperture is 2.15 inch. The horizontal circle reads by two microscopes to 2', and the circles are 10 inches in diameter. This is a perfect geodetic instrument, and together with a 6 inch equatorial and a chronometer can be easily packed for astronomical expeditions. There are several chronometers made by Negus, and a thermometric chronometer by C. Frodsham. The most important of the minor instruments are the filar micrometer for the 36 inch telescope by Fauth & Co., the duplex micrometer by Grubb, and a star spectroscope made by Brashear from designs of Mr. Keeler. Plans for a large solar spectroscope are being worked out by Prof. Holden and Prof. Langley. The other instruments are a delicate sphereometer by Fauth & Co.; resistance coils; galvanometers; a disk photometer; spectroscopes; a lever trier of refined construction; and an engine for measuring photographs, scales, etc., made by Stackpole & Bros., from designs of Prof. Harkness.


The meteorological instruments are: Self-registering rain gauges, wind gauges, barometers, and a number of thermometers. There is a complete set of apparatus for registering earthquakes, provided by the Cambridge Scientific Instrument Co., consisting of a horizontal seismograph with clock and driving plate, the clock being started by an electric contact at the beginning of a shock, and the two rectangular components of the horizontal motion then registering on a moving plate; a vertical seismograph to register vertical motions on a dial plate; a duplex pendulum seismograph to give independent records on a dial plate, the pencil being free to move in any azimuth; and a chronograph,



LEAD COHESION BLOCKS—THE MOULD.

which is set in motion at the beginning of an earthquake and records its duration upon a clock. The staff of the observatory consists of Prof. Edward S. Holden, director and chief astronomer; Samuel W. Burnham, James E. Keeler, John M. Schaeberle, and Edward E. Barnard, assistant astronomers; and C. B. Hill, secretary, librarian, and occasional observer.


Early in 1886, Prof. Holden made contracts with the



JAMES LICK.

Southern Pacific and other railroad companies for supplying time from the observatory by automatic electric signals. This regular time service, of which Mr. Keeler has charge, has been in operation since January, 1887. A great part of the apparatus used in this service forms an integral part of the observatory's equipment. The system which has thus been introduced has been of great service to that particular section of the country, as well as to the railroad companies.

Instruments for recording earthquake shocks have been constructed by a company in San Francisco, and are sold at a very low figure. It is designed in this way that records of any seismic movements shall be procured by private individuals in different parts of the



COHESION—BLOCKS SUSTAINING DIRECT STRAIN.

State, and plates upon which the movement has been recorded may be sent to the observatory, where a record will be kept of all such data, and blue prints will be made of the diagrams and copies of this sent to the person from whom the plate has been obtained. Although this is quite independent of the regular work of the observatory, it will doubtless lead to the accumulation of data which will be most important in formulating statistics for future use.

The great telescope has been mounted for several weeks, and several satisfactory tests of its capacity have been made. It was first directed to the sky on the evening of January 3, 1888, and a few observations were then made for the partial adjustment of the object glass, but the observation was abbreviated by the skies becoming cloudy. The next observations made were on the evening of the 7th. On this occasion Saturn was observed, and Mr. Keeler, who conducted the observation, says with rapture that it was "the most glorious telescopic spectacle ever beheld." He exclaims: "Not only was he shining with the brilliancy due to the great size of the objective, but the minutest details of his surface were visible with wonderful distinctness."

The outlines of the rings were very sharply defined. The most curious feature was the structure of the outer ring; at about one-fifth of its width from its outer edge, a fine dark line was discernible, which marked the beginning of the dark shading, diminishing

in intensity up to the black line. The inner ring did not shade off gradually into the gauge ring, as often represented, but the line of separation was distinct. The space between its inner edge and the planet was perfectly black.

Much of the data given in this article was procured from Prof. Holden's report in the *Sidereal Messenger* and Mr. James E. Keeler's notes on his own observations in the same journal. The observatory with its apparatus and appurtenances is to be transferred, upon its completion, to the University of California, and will in future be under the government of the regents of that institution. Prof. Holden resigned the presidency of the University in order to become director of the observatory.

COHESION OF LEAD.

T. O'CONNOR SLOANE, PH.D.

It has long been known that perfectly clean surfaces of lead, when pressed together, would adhere to each other with some force. The experiment ranks as one of the classics in simple science. A very good way to show it is with bullets. Small surfaces, flat and clean, are prepared on two bullets by cutting off a little slice with a knife. When pressed together with a wrenching motion, the two will remain attached. A third bullet may now be fastened to one of the pair, and in this way a string of bullets, six or more in length, can be built up.

As the phenomenon depends on the absolute cleanliness of the surfaces, and as it is a case of adherence of like to like, it is often invoked as an illustration of cohesion. Pure India rubber shows the same tendency, but in a far stronger degree relatively speaking. Whether it is true cohesion or not is uncertain, especially in the case of lead.


The method of obtaining this cohesion by employing mechanically prepared surfaces is a far less attractive method than the one which Faraday used in his lectures. He melted the lead and poured it out in two pieces upon a flat stone. After they had cooled, he pressed together the smooth lower surfaces of the lead, and thus obtained strong attachment. The flat plane on which the lead rested gave the essential true surface, while during the cooling it was perfectly protected from oxidation or dust. When lead is thus treated, even the upper surfaces which have been exposed to the air will answer for the experiment.

To make the phenomenon really impressive, it may be carried out on a larger scale. In the illustrations the necessary apparatus for conveniently doing this is shown. As mould for the face of the lead a polished block of metal is used. All things considered, this appears to work better than marble, which is the most available stone surface. A block of steel answers very well, and with use becomes slightly colored, as if by formation of magnetic oxide, and resists the rusting action of the atmosphere very well.

The metal block is set into a wooden base, so as to lie with its face even with the surface of the wood. Through a second piece of wood an oblong hole is cut. This should be about twice as long as it is wide. Its width should be equal to that of the metal block, or a shade less. When this is placed upon the base piece, so that the metal block lies at one of its ends and within the opening, the body of a mould is formed. Toward one end a round pin of wood is inserted. If lead is poured into the mould, it will assume an oblong form. Near one end will be a hole, and a face more or less smooth will be formed at its other end.


As regards size, a metallic block 1¼ inches square will answer for the face. The cavity of the mould should be about twice this length. A depth of from one-half to three-quarters of an inch is ample. The lead is melted and poured into the mould. As soon as solid the mould may be taken to pieces, the lead placed to one side to cool, and a second piece cast. This gives two corresponding pieces of lead.

Another piece of wood is provided, which contains a



COHESION—RUBBING BLOCKS TOGETHER.

shallow mortise or groove adapted to receive one of the pieces for nearly its full depth. A cross bar, with a piece cut out transversely, so as to form a notch $1\frac{1}{4}$ inches wide in the present case, is also necessary. Within the notch the wood is best rounded off. One of the pieces of lead is placed in the shallow mortise, with the smooth face uppermost. The other is placed upon



BENEDICT'S COLLAR OR CUFF BUTTON OR STUD.

it, but smooth face downward, the two clean surfaces of lead being in contact. By means of the cross bar the upper block of lead is pressed down with the full weight of the experimenter, and at the same time two or three slight twists or wrenches are given. The notch enables this to be done effectively. The latter wrenching movements are quite essential. In extent they may cover an angle of ten degrees.

The two pieces will now cohere or adhere strongly to each other. If all is properly done, they will resist a fair pull of one hundred and fifty pounds. A very slight transverse strain will immediately separate them. When pulled apart a slight roughness characterizes the points of attachment. The object of the holes is to supply places for the insertion of handles or cross bars, with which to pull them. If the experimenter is not too heavy, he can hang with his full weight suspended from them.

The stress here produced is analogous to shearing. To obtain the direct strain, two square blocks are cast upon the same metallic face, a differently shaped upper mould being used. This only requires one extra piece of board. Two square blocks of lead are made by the same process in general, and in each case a wire loop is inserted while the lead is yet soft. By using the notched bar and slotted block these are pressed together. A hole has to be made in the center of the slot for the loop of the bottom piece to pass through, and the cross bar can be passed through the loop of the upper piece.

They are pressed and twisted, as already described, and adhere about as strongly or nearly so as the others. From a pair of such pieces, $1\frac{1}{4}$ inches square, a weight of 103 pounds was suspended.

A DEVICE FOR UNLOADING AND STACKING HAY.

An invention providing means by which hay may be readily unloaded and formed in a stack is represented in the accompanying illustration, and has been patent-



HOYT'S HAY UNLOADER AND STACKER.

ed by Mr. Ovando Hoyt, of Ovando, Deer Lodge County, Montana Ter. The device consists of a novel construction of rack, to be placed near the spot selected for the stack, and used in connection with a pole held in perpendicular position, carrying pulleys and a hoist rope, to be drawn upon by a team of horses. The slings to be used in the wagon consist of lines secured at their outer ends to poles, which hang longi-


tudinally over the basket sides of the wagon as it is being loaded, and the pole next the rack is provided with short chains, which are to be hooked over pins on the opposite side of the rack when the load is to be lifted. This invention is designed to facilitate the handling of a large quantity of hay at one time, without much strain upon the team, as the load is rolled from the wagon upon the slatted table of the rack, and from thence deposited on the ground or stack, the slats on one side of the rack preventing the hay from scattering beneath.

AN IMPROVED COLLAR OR CUFF BUTTON.

A special form of collar or cuff button or stud, designed to facilitate its insertion into and removal from the button hole, has been patented by Mr. Read Benedict, and is shown in the accompanying illustration. The shank is made flat upon two sides, to permit the button hole to close under the head of the button, the flat surfaces being brought parallel with the edges of the button hole, and the lower surfaces of the head of the button are curved or beveled from the flat surfaces of the shank upward to facilitate the passage of the head out of the button hole. For further particulars with reference to this invention address Messrs. Benedict Brothers, 171 Broadway, New York City.

AN IMPROVED GATE SPRING.

A gate or door spring which is easily applied and effective in operation is illustrated herewith, and has been patented by Mr. Theodore Clough, of Dobbs Ferry, N. Y. To the face of the gate is secured a housing in which there is fitted to slide the end of a plate spring, the other end of the spring being rigidly connected to the post by a plate, the arrangement being such that when the gate is swung back the spring will be drawn out of its normal position, its outer end sliding



CLOUGH'S GATE SPRING.

somewhat in the housing, and when the pressure upon the gate is relaxed the spring will act to return it to its normal position, the throw of the gate in closing being limited by a stop secured to one of the gate posts.


Apantlesis.

Having observed that on several occasions the upper part of an alcohol thermometer column, after having slowly risen from a considerable contraction, was colorless, and that no deposit of the coloring matter (probably cochineal) had taken place, Mallet was led to make further experiments in this direction. It seemed as if the colorless alcohol had by its expansion separated itself from a still perfect solution left behind. The solutions used were partly aqueous, partly alcoholic, of several colloid substances, starch, tannin, caramel, albumen, and gelatin. Each solution was placed in a flask of about half a liter capacity, surrounded with ice, the mouth of the flask being closed with a cork carrying a glass tube about 4 mm. in diameter and 15 or 20 cm. long, having a glass tap near its middle point.

The ice being removed, the liquid was allowed to rise in temperature until the column, originally a centimeter or two below the tap, was as much above it. The tap was now closed and the liquid above it submitted to examination in comparison with an equal volume of the original solution. In all cases the liquid above the tap contained a less amount of material in solution, in some cases very notably less; while in two or three cases there was practically none. As all the solutions were carefully filtered at the outset, there could have been no settling of particles. The conditions influencing the result seem to be: First, the proportion of the colloid solid in solution; and second, the time occupied in the rise of temperature. The author has given the name *apantlesis* to this phenomenon, signifying a draining away of some of the molecules of the solvent from those of the colloid while the solution was undergoing expansion.—*Chem. News.*

AN IMPROVED BRAKE BLOCK FOR VEHICLES.

An invention providing means whereby a brake shoe for vehicles can be easily and quickly removed when worn out, and a new one inserted, is illustrated herewith, and has been patented by Mr. George A. Posson, of Angwin, Napa County, Cal. The brake shoe may be of rubber, wood, or other suitable material, and has a metallic back formed with upper side flanges, embracing the sides of the block, and a bottom flange having upward-projecting points entering the lower end of the shoe, bolts projecting from the rear face by which the brake block is secured to the brake bar. For buggies and spring wagons, as well as for farm wagons, a modi-



POSSON'S BRAKE BLOCK.


fied construction is shown in the figure to the right, in which the metallic back is made in two halves, each half having ribs fitted to the brake bar, and with apertures through which passes a bolt for holding the halves on the brake shoe and the brake block on the brake bar, the upper flanges in this case having side projections passing into apertures in the sides of the brake shoe.

An Ingenious Experiment.

Herr J. Puling, of Vienna, has devised an ingenious method of rendering visible the form of a stretched string set in vibration by having one of its extremities attached to one prong of a tuning fork, which was kept in motion electrically, and gave a definite note, the pitch of which was carefully determined. The vibrating string was lighted up by a vacuum tube connected with a Ruhmkorff coil, the rate of discharge through the tube being alterable at will, and when this is made equal to or some aliquot multiple of the number of vibrations made by the string, the latter was only illumined when occupying some one definite position, and owing to the persistence of its image on the retina, appeared as if at rest. In this way the shape of the string and the positions of the nodes and vertical segments were rendered clearly visible.

AN IMPROVED STAND FOR DISPLAYING GOODS.

A frame or open casing containing removable adjustable shelves and an adjustable and folding brace support, making a stand designed to be mounted on a counter or in other suitable position for conveniently displaying goods, is illustrated herewith, and has been patented by Mr. Ralph H. Maxson, of Richburg, N. Y. The frame is adjustably held in open position by a brace bar pivoted to a strip on the back, and having a spring catch at its free end formed with shoulders



MAXSON'S STAND FOR DISPLAYING GOODS.

which engage a bent rod or loop on a cross bar of the frame. The sides of the casing are made with short strips forming grooves and spaces, and the shelves have projections on their ends whereby they may be mounted in the casing by sliding them to place in an inclined position, and sliding the projections in the grooves until a space is reached, when the shelves may be slid back in a horizontal position.

SIMPLE ELECTRIC MOTOR.

BY GEO. M. HOPKINS.

It is generally understood that an efficient electric motor cannot be made without the use of machinery and fine tools. It is also believed that the expense of patterns, castings, and materials of various kinds required in the construction of a good electric motor is considerable. The little motor shown in the engravings was devised and constructed with a view to assisting amateurs and beginners in electricity to make a motor which might be driven to advantage by a current derived from a battery, and which would have sufficient power to operate an ordinary foot lathe or any light machinery requiring not over one man power.

The only machine work required in the construction of the motor illustrated is the turning of the wooden support for the armature ring. The materials cost less than four dollars, and the labor is not great, although some of the operations, such as winding the armature and field magnet, require some time and considerable patience. On the whole, however, it is a very easy machine to make, and if carefully constructed will certainly give satisfaction.

Only such materials as may be procured anywhere are required. No patterns or castings are needed.

Beginning with the armature, a wooden spool, A (Fig. 2), should be made of sufficient size to receive the soft iron wire of which the core of the armature is formed. The wire, before winding, should be varnished with shellac and allowed to dry, and the surface of the spool on which the wire is wound should be covered with paper to prevent the sticking of the varnish when the wire is heated, as will presently be described. The

wire is cut off and the ends (about two inches in length) are twisted together to cause the coil to retain its shape. After the completion of the first section, one of the pieces, C, is moved to a new position




Fig. 3.—WINDING THE ARMATURE.

and the second section is proceeded with, and so on until the twelve sections are wound. The coils of the ring are then varnished with thin shellac varnish, the varnish being allowed to soak into the interior of the coils. Finally the ring is allowed to remain in a warm place until the varnish is thoroughly dry and hard.

Care should be taken to wind all of the coils in the same direction and to have the same number of convolutions in each coil. A convenient way of carrying the wire through and around the


formed integrally with the collar, H. The end of the hub, G, which is provided with a flange, is prolonged to form the commutator, and the terminals, a b, of the ring coils are arranged along the surface of the hub and inserted in radial holes drilled in the hub in pairs. The wires are arranged so that one hole of each pair receives the outer end of one coil and the other hole receives the inner end of the next coil, the extremities of the wire being scraped before insertion in the holes. The distance between the holes of each pair is sufficient to allow a brass wood screw to enter the end of the hub, G, and form an electrical contact with both wires of the pair, as shown in Fig. 4.

There being twelve armature sections and twelve pairs of terminals, there will of course be required a corresponding number of brass screws. These screws are inserted in the end of the hub, G, so as to come exactly even with the end of the hub. This completes the armature and the commutator.

Before proceeding to mount the armature shaft in journal boxes, it will be necessary to construct the field magnet, as the machine must, to some extent at least, be made by "rule of thumb."

The body, E, of the field magnet consists of strips of Russia iron, such as is used in the manufacture of stoves and stove pipe. The strips are 2½ inches wide, their combined length being sufficient to build up a magnet core seven-sixteenths inch thick, of the form shown. The motor illustrated has 15 layers of iron in the magnet, each requiring about 26 inches of iron, approximately 33 feet altogether.

The wooden block, F, on which the magnet is formed



Figs. 7 & 8.—FORMING THE FIELD MAGNET.

size of the iron wire is No. 18 American wire gauge. The spool is 2⅞ inches in diameter in the smaller part and 2 inches in length between the flanges. It is divided at the center and fastened together by screws. Each part is tapered slightly to facilitate its removal from the wire ring. The wire is wound on the spool to a depth of ⅜ inch. It should be wound in even layers, and when the winding is complete the spool and its contents should be placed in a hot oven and allowed to remain until the shellac melts and the convolutions of wire are cemented together. After cooling, the iron wire ring, B, is withdrawn from the spool, and covered with a single thickness of adhesive tape, to insure insulation.

The ring is now spaced off into twelve equal divisions, and lines are drawn around the ring transversely, dividing it into twelve equal segments, as shown in Fig. 3. Two wedge-shaped pieces, C, of hard wood are notched and fitted to the ring so as to inclose a space in which to wind the coil. This coil consists of No. 16 cotton-covered copper magnet wire, four layers deep, each layer having eight convolutions. The end, a, and the beginning, b, of the winding terminate on the same side of the coil. The last layer of wire should be wound over two or three strands of shoe thread, which should be tied after the coil is complete, thus binding the wires together. When the first section of the winding is finished, the

ring is to wind upon a small ordinary spool enough wire for a single section, using the spool as a shuttle.

The ring is mounted upon a wood support or hub, G, and is held in place by the wooden collar, H, both hub and collar being provided with a concave flange for receiving the inner edges of the ring. The collar, H, is fastened to the end of the hub, G, by ordinary brass wood screws. Both hub and collar are mounted on a ⅜ steel shaft formed of Stubs' wire, which needs no turning. A pulley is

is secured to a base board, G, as shown in Fig. 7, and grooves are made in the edges of the block, and corresponding holes are formed in the base to receive wires for temporarily binding the iron strips together. Opposite each angle of the block, F, mortises are made in the base board, G, to receive the keys, d, and wedges, c. Each key, d, is retained in its mortise by a dovetail as shown in Fig. 8. By this arrangement, each layer of the strip of iron may be held in position, as the formation of the magnet proceeds, the several keys, d, and wedges, c, being removed and replaced in succession as the iron strip is carried around the block, F. When the magnet has reached the required thickness, the wedges, c, are forced down so as to hold the iron firmly, then the layers of iron are closely bound together by iron binding wire wound around the magnet through the grooves, e, and holes in the base board, G.

The next step in the construction of the machine is the winding of the field magnet. To insure the insulation of the magnet wire from the iron core of the magnet, the latter is




Fig. 2.—ARMATURE CORE. Fig. 4.—TRANSVERSE SECTION. Fig. 5.—END VIEW OF ARMATURE, SHOWING COMMUTATOR. Fig. 6.—BRUSH-HOLDING DISK.




Fig. 1.—SIMPLE ELECTRIC MOTOR (ABOUT HALF SIZE).

covered upon the parts to be wound by adhesive tape or by cotton cloth attached by means of shellac varnish.

The direction of winding is clearly shown in Fig. 9. Five layers of No. 16 magnet wire are wound upon each section of the magnet, the winding of sections 1 and 2 being oppositely arranged with respect to each other. In like manner the winding sections 3 and 4 are oppositely arranged. The winding of section 1 is also opposite to that of 3, and that of 2 is opposite to that of 4. The winding begins at the outer end of the magnet, and ends at the inner end of the section. When the winding is completed, the temporary binding is removed. The outer ends of 1 and 2 are connected together, and the outer ends of 3 and 4 are connected. The inner ends of 2 and 4 are connected. The inner end of 3 is to be connected with the commutator brush, *f*. The inner end of 1 is to be connected with the binding post *g'*, and the binding post, *g*, is to be connected with the commutator brush, *f*.

The field magnet is now placed upon a base having blocks of suitable height to support it in a horizontal position. A block is placed between the coils to prevent the top of the magnet from drawing down upon the armature, and the magnet is secured in place by brass straps, as shown in Fig. 1.

The armature is wrapped with three or four thicknesses of heavy paper, and inserted in the wider part of the field magnet, the paper serving to center the armature in the magnet. The armature shaft is leveled, and arranged at right angles with the field magnet. The posts in which the armature shaft is journaled are bored transversely larger than the shaft, and a hole is bored from the top downward, so as to communicate with the transverse hole. To prevent the binding of the journal boxes, the exposed ends of armature shaft are covered with a thin wash of pure clay and allowed to dry. The posts are secured to the base, with the ends of the armature shaft received in the transverse holes. Washers of pasteboard are placed upon the shaft on opposite sides of the posts, to confine the melted metal, which is to form the journal boxes. Babbitt metal, or, in its absence, type metal, is melted and

poured into the space around the shaft through the vertical hole in the post. The journal boxes thus formed are each provided with an oil hole, extending from the top of the post downward. If, after cleaning




Fig. 9.—CIRCUIT OF SIMPLE ELECTRIC MOTOR.

and oiling the boxes, the shaft does not turn freely, the boxes should be reamed or scraped until the desired freedom is secured.

All that is now required to complete the motor is the commutator brushes, *f, f'*. They each consist of three or four strips of thin hard rolled copper curved as shown in Fig. 4, to cause them to bear upon the screws in the end of the hub, *G*. The brushes are secured by small bolts to a disk of vulcanized fiber, or vulcanite, at diametrically opposite points, as shown in dotted lines in Fig. 5, and the brushes are arranged in the direction of the rotation of the armature. In the brush-carrying disk is formed a curved slot for receiving a screw, shown in Fig. 6, which passes through the slot into the post and serves to bind the disk in any position. The disk is mounted on a boss projecting from the inner side of the post concentric with the armature shaft. The brushes are connected up by means of flexible cord as shown in Figs. 1 and 9. The most favorable position for the brushes may soon be found after applying the current to the motor. The ends of both brushes will lie approximately in the

same horizontal plane. When the motor is in operation the direction of the current in the conductor of the field magnet is such as to produce consequent poles above and below the armature.

Eight cells of plunging bichromate battery, each having one zinc plate 5 x 7 inches, and two carbon plates of the same size, will develop sufficient power in the motor to run an ordinary foot lathe or two or three sewing machines.

The dimensions of the parts of the motor are tabulated below:

Length of field magnet (inside).....	10 1/4 in.
Internal diameter of polar section of magnet.....	3 3/8 "
Width of magnet core.....	2 1/2 "
No. of layers of wire to each coil of magnet.....	5
No. of convolutions in each layer.....	34
Length of wire in each coil (approximate).....	95 feet.
Size of wire, Am. W. G.....	No. 16
Outside diameter of armature.....	3 1/2 in.
Inside diameter of armature core.....	2 1/8 "
Thickness.....	3/8 "
Width.....	2 "
" " wound.....	2 1/2 "
No. of coils on armature.....	12
No. of layers in each coil.....	4
No. of convolutions in each layer.....	8
Length of wire in each armature coil (approximate).....	30 feet.
Size of wire on armature, Am. W. G.....	No. 16
Length of armature shaft.....	7 1/4 in.
Diameter of armature shaft.....	3/8 "
" " wooden hub.....	1 1/4 "
Distance between standards.....	5 1/2 "
Total weight of wire in armature and field magnet.....	6 lb.

THE LOCKS OF THE PANAMA CANAL.

We illustrate herewith the new system of locks devised by Mr. Eiffel for use on the Panama canal.

The gates (Figs. 1 and 2) consist essentially of a hollow, balanced, movable caisson, capable of sliding above at right angles with the axis of the canal, on a track carried above the canal by a revolving bridge. This track is prolonged above the lateral chamber. The motion is analogous to that of the doors which slide at the top that are generally used in locomotive shops. When the flood gate is placed in the chamber,




Fig. 1. LOCKS OF THE PANAMA CANAL FLOOD GATE OF 11 METERS FALL.

it is only necessary to revolve the bridge 90° to free the passage and allow boats to go through.

The diagram in Fig. 3 shows the maneuver. A vessel, S, is about to pass from lock, B B', to the reach, C. To this effect, at N the gate, P', taken from its chamber, R, bars the canal, and the bridge, A', is closed above it. At M the gate, P, has slid into its chamber, R'. The revolving bridge has pivoted 90°, and opened the passage.

The gate or movable caisson, the sides of which are stiffened from meter to meter by strong, horizontal, T shaped iron beams, which carry all the stress of the water pressure over to the side walls, is arranged beneath like the working chambers of the caissons used in constructing bridge piers. Moreover, above the working chamber, it is divided into nine compartments by three horizontal and three vertical partitions. All these compartments, as well as the bottom chamber, communicate with the external air through chimneys starting from air locks, so that either water or compressed air may be allowed to enter them at will. Owing to this arrangement, it is easy to balance and ballast the gate, and, besides, on exhausting its different parts in succession, to inspect and repair them. The gate is suspended from a carriage provided with rollers, which, on rolling over the track carried partly by the bridge and partly by a framework, carries along the gate.

The suspension rods of the gate are not fixed in an invariable manner to the carriage. They carry rollers at their upper extremities which are capable of revolving to a certain distance upon transverse rails fixed to the carriage. The object of this arrangement is to start the gate before sliding it forward and to prevent its rubbing against the walls of the chamber and its bearing points. The gate remains constantly suspended by parts situated outside of the water, and which can be repaired and kept in order with the utmost ease. This mode of suspension offers the advantage that it assures the complete stability of the gate, even under the influence of winds that might be capable of overturning it. For a lock of 11 meters fall the dimensions are as follows:

TAIL GATE.	
Height.....	21 meters.
Width.....	4 "
Length.....	21'6 "
HEAD GATE.	
Height.....	10 meters.
Width.....	3 "
Length.....	21'6 "

For the lock of 8 meters fall, the height alone varies. The section of the canal left free by the opening of the gate is 18.6 meters at the lower part and 20.6 at the leveling of the talus and works of access. The location for the locks will have to be so

selected that they can be excavated in compact rock. The side walls of the intermediate locks will then consist of the rock itself, with a thin lining in places where there are cracks. As for the side walls of the heads, they will be formed of T-iron caissons lined with cast iron and filled in with beton. Their dimensions vary with those of the locks. For a lock of 11 meters fall they are as follows:

Thickness.....	5.5 meters.
Height.....	24'25 "
Length.....	30 "

The revolving bridges are of iron or steel, and are 5.5 meters in width by 34.2 in length. This length is divided into two sections of 23.8 and 10.4 meters on each side of the axis of revolution.

The gate chambers are 7 meters in width by 30 in length. The maneuvering of the bridges and gates is effected through chains winding around capstans actuated by hydraulic power, through turbines moved by the fall of water occasioned by the reaches.

In order to introduce so great a mass of water in so short a time (40,000 cubic meters in 15 minutes), it has been necessary to adopt peculiar arrangements. The method adopted consists in making the water flow through the entire length of the lock and in vertical jets, so as to prevent the strong eddies and tumultuous motions that would necessarily be produced in this arrangement. To this effect, for the entire length of the lock, and laterally, in channels beneath the flow of the canal, there run two large cast iron pipes, 2.8 meters in diameter, provided at every 2 meters distance with 0.40 meter apertures. These pipes pass beneath the sill of the gates, at each extremity, and are prolonged about 15 meters down stream and about 12 up

stream in the reach that follows the lock (Fig. 4). Here they curve, and, at 9.75 meters above the floor, terminate in a valve contained in a chamber formed in the side wall. There are, then, two valves of this kind to each reach. These valves, due to Engineer Fontaine, are cylindrical, and without lateral pressure, thus rendering the maneuvering of them extremely




Fig. 2.—THE GATE OPEN.

easy. With this system the emptying and filling of the locks will take but a quarter of an hour.

For the illustrations and description of these gates, we are indebted to *Le Genie Civil*.

New Photo-Stereotype Printing Process.

A new process of so-called autostereotypic printing, especially adapted for the reproduction of books and engravings, has lately been invented in Switzerland, and is already used with advantage at the establishment of Orell, Fussli & Co., at Zurich, a printing office of European fame. The process will cheapen the reprinting of the works of foreign authors. By this method the type setting and the copying of engravings is saved and an accurate stereotyped plate is obtained directly from the original. It is a transfer process, and

be taken off, and it will be found to be as smooth as the glass itself.

The paper to be reproduced is next placed, with the side to be copied down, in a dish which contains the following transferring solution: Distilled water, 16 oz.; alcohol, 90°, 5 oz.; acetic acid, 1/4 oz.; phosphate of soda, 1/4 oz. Care should be taken not to get the solution on the back of the paper, which is not to be transferred, as it is then liable to print through when it is drawn through the transferring press. Should the print to be copied have been printed for some time, it is desirable to warm the solution and float the paper longer on it. The sheets should be left on the solution for at least two hours to insure perfect action. In the mean time, the plaster of Paris plate, which was completely dried before, is prepared in a dark room. A solution of 5 oz. of gelatine in 12 oz. of water is prepared by letting the former soak for half an hour and then heating it to about 190°. Care must be taken to prevent the boiling of the solution. To this six drachms of citrate of iron and ammonia and 2 oz. of alcohol are added and well filtered. This is when still warm. Put into a flat dish covered to a depth of about 1/4 in. It is well to put this dish upon a hot metal plate, as it gets hard quickly when getting cold. The plaster of Paris plate, which itself is warmed first, is dipped in the solution on the smooth side for a moment, thus letting it take up some of it, whereupon it is taken out and dried in the dark. When dry, the copy is transferred upon it in the usual way, the plaster having been placed between rubber sheets to prevent it from breaking. Of course, also, this has to be done in the dark room, that is, at lamp or gas light. The plate is then

dried once more and exposed to direct sunlight for fifteen minutes. When taken out, the places where the light has acted will be found to be quite hard, while at the other places the plaster is soft, and will fall off as fine powder as deep as the solution has penetrated, if brushed with a hard brush. After that the plate is ready to be stereotyped.

The Condition of Sulphur in Vegetation.

The conditions under which sulphur appears in coal are to some extent elucidated by recent experiments of MM. Berthelot and Andre upon the forms in which sulphur may be found in plants. These experimentalists state, in a communication to the *Comptes Rendus*, that sulphur occurs in plants as sulphates. In the form of ethereal compounds comparable to the ethyl-sulphates and glyceri-sulphates capable of being split up by hydration under the prolonged action of dilute acids or alkalis, or by oxidation. In the form of mineral compounds, such as sulphides, sulphites, hypo-sulphites, etc., convertible by the moist

way into sulphates by the prolonged action of oxidizing agents. In the shape of organic compounds, such as taurine, cystine, the sulpho-conjugated acid and albumen compounds, the sulphur in which is not convertible into sulphuric acid in the moist way. The sulphur of plants has been determined by the authors, with absolute accuracy, by burning the sample (previously dried at 100° C.) in a column of oxygen, passing the resultant vapors through a long column of pure anhydrous sodium carbonate. The tube is of hard glass, and the temperature is near redness.

When the organic product is entirely burnt, the current of oxygen is still maintained for some time, so as to complete the conversion of any sulphureted salts into sulphates. After this is effected, the tube is allowed to cool, the contents are dissolved in water acidulated with hydrochloric acid; then boiled; and the sulphuric acid precipitated in the ordinary manner. MM. Berthelot and Andre do not appear to have experimented on fossil plants.

Sheep Bugs.

There are many breeders and sheep raisers in Delaware County, N. Y., and in years past they have had to cope with a variety of diseases among their flocks. At the present time sheep are suffering from the ravages of bugs, and there seems to be no potent remedy at hand to kill them. The pests measure from one-half to three-quarters of an inch in length, and look more like the ordinary snapping bug than anything else. The pests burrow their way into the heads and brains of the sheep, and the loss in the aggregate incurred thereby is quite large.




Fig. 3.—DIAGRAM EXPLANATORY OF THE MANEUVERING OF THE GATES.

for the reproduction two newly printed copies of the publication to be reproduced are necessary to insure complete success. It is done in the following manner: Plaster of Paris, best quality, is mixed with water to make it a thin putty without lumps, and to this a little alum or salt is added to make it set quickly. To every 5 lb. of the plaster are then added: Silicate of potash or silicate of soda, 3 oz.; phosphate of lime, 2 oz. The mixture thus obtained is then put upon a perfectly level piece of plate glass of the desired size, around




Fig. 4.—POSITION OF THE PIPES FOR FILLING THE LOCKS.

which iron rods are placed, and left to get hard. The plaster cast ought to be at least type high, to prevent breakage. While the mass is setting, the back ought to be scraped level, and should remain undisturbed until it is perfectly dry and hard. After that it may

Correspondence.

The Panama Canal.

To the Editor of the Scientific American:

As our papers do not often publish anything but unfavorable information regarding the canal, it may surprise your readers to be told that on Washington's birthday there was an opening of the Gatun section, and steamers proceeded from tide water to a point beyond Gatun, a distance of 11 miles; and by the end of this month the canal will be navigable for 15 miles (to Bohio) for vessels of 1,000 tons burden.

The excavating has gone on very rapidly of late, the excavation for first half of February being 384,521 cubic meters, while the usual amount for a whole month has heretofore averaged about 332,000.

The cut for the Chagres River is well under way, some 1,800,000 cubic meters of excavation having been made on this part of the work alone.

The American Contracting and Dredging Company are pushing their part of the work very rapidly, and between January 15 and February 15 contributed over 390,000 cubic meters of excavation to the year's work.

A. P. HOWARD.

Boston, March 7, 1888.

Openings for American Trade and Enterprise in Venezuela.

To the Editor of the Scientific American:

As your valuable paper has a wide circulation among all classes, and as I have noticed that you give some prominence in your columns to what is going on in foreign parts, I have thought it would be a good idea to ask you kindly to insert the following remarks as a general answer to the many letters of inquiry with which this consulate is favored:

Every mail brings me a large correspondence, and there appears, I am glad to say, a tendency on the part of our people to make a peaceable commercial and industrial invasion of this part of South America.

I therefore take the liberty of intruding upon your space in order to explain in what way our countrymen may establish themselves in this section of Venezuela with but little risk of failure and a fair probability of success. It is a great pity that in the early days immediately after the independence of the South American states, we did not take steps to make our commercial influence paramount.

We, however, lost the opportunity, and to-day only are attempting to gain what should have been ours from the beginning.

For this reason it gives me pleasure to point out the various ways in which success may be tolerably assured to any one possessing the requisite capital and energy. For many reasons this part of Venezuela offers more inducements than any other section of the republic.

The progressive spirit of the people, the ready welcome given to foreigners, the eager desire for improvement and development, and the excellent government with which this division of the Venezuelan federation is favored make it a most promising field for enterprising and intelligent industry.

The natural resources are such that within the limits of the State of Zulia, of which Maracaibo is the capital, agriculture, mining, and stock raising can be carried on to exceptional advantage.

Commercially and industrially, Maracaibo is the most important point on the north coast of South America, and with its steady increase in population and the development of its industrial capabilities, it must some day become a busy metropolis.

I beg to give publicity through your columns to the more advantageous opportunities offered by this section, and particularly by the city of Maracaibo; and although this is intended as a general answer to numberless inquiries, yet I will gladly give further details, as far as may be in my power, to any one requesting them.

My attention has been called to the extensive business now being carried on in the United States in the matter of portable wooden houses, and I believe that Maracaibo would be a good field for their introduction.

Concessions of law for building purposes could be easily obtained from the municipal government, and should one of our manufacturing firms run up one or two blocks of the houses referred to, they could no doubt be at once advantageously rented or sold, and the business established on a good basis. This is an industry which, once introduced, would give excellent results, and is worthy of examination.

In connection with the following suggestions, it will be understood that the city would have no hesitation in giving land at a nominal price, sufficient for the necessities of any bona-fide industry, whose development would, moreover, be encouraged by exemption from imposts.

A first class foundry and shop for repair of machinery should pay well if managed intelligently.

A brick yard and tile factory, run by steam, and with all the modern appliances, could do a fine business. There are many kilns here, all, however, on a

small scale, and the demand for their products is large and constant.

The method of manufacture is of the most primitive character, and as excellent material is abundant and close at hand, there is no reason why one of our enterprising brick makers, thoroughly posted in his business, should not make large profits from the beginning.

A manufactory of pottery, from the most ordinary grade to the finer classes of ceramic work, would find an immediate and profitable market for its products. There exist almost within the city limits the finest grades of clay, and it only needs intelligence and capital to turn out work much superior to that now imported from abroad.

A furniture, window, and sash factory would meet with ample patronage.

To me, it is a matter of surprise that no one has ever thought of establishing, on a large scale, a first class tannery in Maracaibo.

From this port are exported large quantities of hides and skins, which are here abundant, cheap, and of excellent quality. The dividivi, which is used both in this country and Europe as a substitute for bark, is found in the immediate vicinity of Maracaibo, and in such quantities as to make it an important article of export. The consumption of leather is large, the importation being great, and I can scarcely imagine a safer line of business, or one with more probability of profit, than a thoroughly first class tannery.

A boot and shoe factory with the modern mechanical appliances would pay well. All shoes are hand made, dear in price, and not of the best workmanship.

The demand is great, and various shops, some on quite a respectable scale, do a good business. Should a manufactory be opened in this city, capable of turning out good machine work at a moderate price, the results could not be other than satisfactory. I may mention incidentally that the import duty on foreign boots and shoes is excessive, amounting to four dollars per kilogramme, primary duty, and about sixty cents secondary, resulting that the entire duty is about two dollars per pound.

This practically prevents foreign competition, and aids greatly the successful prosecution of this industry in Venezuela.

A dairy on a large scale with a vegetable garden attached would be well patronized.

Vegetables are scarce and dear, there being no truckers, and I believe that the business, once started, would give good returns. In connection with this industry, stock raising could be engaged in. Grazing land abounds and is free to all, and breeding has always been one of the most successful pursuits in this section.

On the frontier of the Goajira peninsula, at the extreme northwest of Venezuela, the business of stock raising is being carried on to great advantage, in spite of the proximity of the famous Indians of that section, and it is calculated that with ordinary good luck, the original capital invested may be doubled in four years. In the district of Perija, to the westward of this city, there are unrivaled facilities for the breeding of cattle, as on the extensive savannas there is an abundance of grass of various classes, and no lack of water.

The great wealth of this section consists, however, principally in its mineral deposits. Asphalt, petroleum, and bituminous coal abound, and serious efforts are about to be made to utilize these valuable products. Should a petroleum refinery be established on a sufficiently extensive scale to supply the domestic demand, the profits would be great, as the crude article is practically inexhaustible.

The fisheries of this coast would also richly repay their systematic development. Many persons now make a good living at the business, and were it taken in hand in a careful and intelligent manner, its importance would be vastly increased.

The sounds of the "curbina" are largely exported for the manufacture of gelatine, and command excellent prices abroad.

A first class hotel would receive good patronage in Maracaibo, as would probably also a good restaurant a la carte.

With the present rapid growth of the city, and its increase in population, an additional market has become a necessity, and it may be suggested to the manufacturers of portable wooden houses, that a contract for its erection, with favorable concessions, might possibly be obtained.

The foregoing remarks are intended to point out the more prominent industrial opportunities of this district, and, as I have already stated, it will give me pleasure to answer in detail any inquiries.

You will kindly excuse this intrusion upon your space, and accept my thanks for your courtesy.

E. H. PLUMACHER, U. S. Consul.


United States Consulate, Maracaibo,

February 14, 1888.

LIEUT. HUNTER.—A correspondent writes us that Lieut. Hunter, one of the "fathers of the American steam navy," is still living in New Orleans, La., 85 years of age.

A DEVICE TO FACILITATE BLASTING STUMPS, LOGS, ETC.

A blasting plug intended especially for use in blasting wood, by which the ordinary tamping of rocks, etc., in the drilled blasting hole may be avoided, and in which no fuse will be necessary, is shown in the accompanying illustration, and has been patented by Mr. Alfred Winder, of Washington, D. C. The plug is exteriorly threaded, to facilitate securing it in the blasting hole, and has a central bore provided at its lower end with a threaded extension to receive the cap support. In this support, shown in one of the small figures, is a cap nipple or seat, from which a vent leads to permit the passage of the flash to the powder. The




WINDER'S BLASTING PLUG.

hammer rod, extending through the bore, may be made sufficiently heavy to fire the cap by gravity, but in order to render the operation more certain, and to permit the device to be operated in a horizontal as well as a vertical plane, a spring is employed, bearing between shoulders on the hammer rod and within the bore. A detent or latch pivoted to the body of the plug serves to hold up the hammer rod, the latch being released by the operator, at a safe distance, pulling on a cord attached thereto, when the descending hammer rod fires the cap and explodes the charge.

A MACHINE FOR TRUING VALVE PLUGS, ETC.

A device for centering a valve stem or valve casing, etc., providing also means for grinding or burring the plug or seat of the centered valve-stem or casing, has been patented by Mr. Daniel F. Dunn, and is shown in the accompanying illustration. Upon the end of an exteriorly screw-threaded stationary tubular spindle, suitably supported, are formed ear pieces to which are pivotally hung the ends of clamp arms having inward bends near their outer ends, with clamping jaws to embrace a valve stem. The clamp arms also have rear lugs pivotally connected by links with a sleeve fitting loosely upon the screw-threaded tubular spindle, there being an internally screw-threaded hand wheel to the rear of the sliding sleeve, by turning which the jaws of the clamp arms are firmly fixed upon the stem of the valve plug to be centered, which is thus brought in axial line with the spindle. The crank arm on the end of the burr shaft can then be forced inwardly for its conical burred opening to lie upon and around the end and edge of the valve plug, when, by rotating the shaft by means of the crank handle, the valve plug is ground perfectly true and concentric with the axial line of its stem. The mechanism permits the substitution of burr shafts having heads with grinding sur-



DUNN'S MACHINE FOR TRUING VALVE PLUGS, ETC.

faces of different characters or forms, suitable for use upon other articles clamped by the jaws, in which a valve casing or body may likewise be clamped and centered, with the axial line of its seat coincident with the axial line of the burr shaft, which is then provided with a conical shaped cutting or grinding head.

For further particulars with reference to this invention address Messrs. B. F. Dunn & Co., P. O. box 705, Columbus, Ohio.

IN Nebraska, where glandered horses are exterminated by order of the authorities, the State pays the owner for the value of the animal. It is said quite a profitable business is carried on by parties who take over the State line lots of diseased horses from Dakota, Iowa, and other localities for the purpose of receiving the bounty.

THE HORNED LIZARD.

The Museum of Natural History at Paris has now in its possession a curious reptile that came from Saint Domingo. It bears the name of horned lizard, which was given it by Lacepede. Mr. Wagler has since put it into the genus *Metopoceros*.

In brief, it is a saurian of the family Iguanidæ, distinguished from the iguanas, properly so called, by having teeth like those of the cycluras, and by two rows of hairs that are to be seen under the thighs. The only species known is the *M. cornuta*, which is remarkable for its forehead being surmounted by a large horn-like tubercle.

This lizard, in form, reminds us of those enormous fossil dinosaurs known as iguanodons, the remains of which have been found in the Wealden cretaceous formation, and very recently at Bernissart, Belgium.

The horned lizard is about twenty-eight inches in length. Its body is gross and squat, of a brown color, and the line of the back is covered with spines that point backward, from the back of the head to the beginning of the tail, where there is a small space destitute of them. The tail is not cylindrical like that of our lizards, but is compressed laterally, and is provided with strong muscles that allow the animal to switch it abruptly and powerfully in either direction in order to defend itself when any one tries to touch it.

Back of the head, which possesses remarkable peculiarities, the back is provided with a sort of hump. The head, which is surmounted in front with a dermic horn, is large and inflated on each side at the back. Under the lower jaw, we observe a fold in the skin, flanked on each side by large pockets that give the animal, in a face view, a most curious aspect.

The collection of the museum contains but few examples of this saurian, and this is the first time that a living specimen has reached the menagerie. So its habits are not known. However, since its arrival it has been observed to be slow of gait, and to make certain vertical motions of the head. When it is approached, it seems to like to give itself as wicked an air as possible. It is fed upon lettuce leaves and a little meat; but it has not much appetite. The horned lizard is a near relative of the cycluras, anolises and amblyrhynchuses. These latter were studied by the celebrated Darwin in the Galapagos Archipelago. It is probable that their habits resemble those of the *Metopoceros*. There are two species of them, one aquatic (*A. cristatus*), and the other terrestrial (*A. Demarllii*). In speaking of the last named species, Darwin tells us that the animals eat during the day and wander but a short distance from their burrows, and, when frightened, run back to the latter in the most comical manner. They cannot run very swiftly except when they are descending sloping ground. This is evidently due to the lateral position of their legs. They are not timid. When they are looking at some one attentively they lift their tail, and, rising upon their fore legs, they keep moving their head up and down and try to put on as vicious an air as possible. But, as a fact, they are not vicious; and if one stamps his foot, their tail at once comes down, and they scamper away as quickly as possible. Darwin observed that the young, which eat flies, give their head exactly this same up and down motion when they observe anything.

This same species excavates burrows just beneath the surface, and when a person is walking in a place inhabited by these animals, he keeps constantly sinking. They dig with the feet of one side of the body at a time, and when these are tired they use the feet of the other side, and so on alternately.

It may be conceded that the amblyrhynchuses, as regards habits, have resemblances with the horned lizard, which, like them, belongs to the Iguanidæ.—*La Nature*.

Progress of Our Southern Neighbors.

A bill has been introduced in the House of Representatives to authorize the President to invite the several governments of the republics of Mexico, Central and South America, and the empire of Brazil to join the United States in a conference to be held at Washington, for the purpose of discussing and recommending for adoption to their respective governments some plan of arbitration for the settlement of disagreements and disputes that may hereafter arise between them, and for considering questions relating to the improvement of business intercourse between said countries, and to encourage such reciprocal commercial relations as will be beneficial to all and secure more extensive markets for the products of each of said countries.

In the course of the discussion an able and brilliant speech in support of the bill was made by the Hon. Mr. McCreary, of Kentucky, from which we take the following:

There are south of our republic fifteen republics and the empire of Brazil, and they cover an area ten times the size of France, Spain, Prussia, and Italy. They are as large as the United States and the whole of Europe

combined. The population of those countries amounts to about 50,000,000 of people. They are connected to us by land, and most of them are nearer to New York than is the State of California, and yet to many of the people of the United States the republics of Central and South America are almost unknown.

In 1887 our exports were valued at \$752,180,902. Of this amount we exported but \$64,719,000 to Mexico and South and Central America.

Our annual mechanical and agricultural products are valued at about eleven thousand millions of dollars, while we seldom have sold more than \$75,000,000 worth of these products to our nearest neighbors, who buy in Europe at least three times as much as they get here.

The total commerce of the countries named in 1885 was as follows:

Imports	\$331,100,599
Exports	391,294,781

Of the \$331,100,599 of merchandise sold to those countries, the share of the United States was only \$42,598,469. Yet we are their closest neighbor.

The report of the commissioners sent by our government to Central and South America shows that the development of the southern half of South America is nearly as rapid as that of the United States. Immigration is flooding in, internal improvements are opening new and fertile fields, and wealth is increasing in a ratio not exceeded by any other section of the globe.

Chili, Uruguay, and the Argentine Republic, almost a *terra incognita* to many, are booming like our Western States and Territories. In 1876 the imports of the Argentine Republic were valued at \$36,000,000. In 1884 they had reached \$80,000,000. In 1876 the merchandise brought to that country from England, France, and Germany was valued at only \$18,000,000,

and Switzerland sells Chili more sewing machines than she buys of us.

Bolivia has a foreign trade of over \$16,000,000 a year, yet the name of that country does not appear in the tables of our Bureau of Statistics. The chief imports of Bolivia are cotton and woolen goods, agricultural implements, mining machinery, hardware, cutlery, clocks, watches, canned goods, and provisions, a list which could be filled in any commercial city of the United States as cheaply as in Europe, and yet the annual reports of the Treasury Department of the United States do not show a dollar's worth of commerce between the United States and that country.

The most absurd spectacle in the commercial world is our trade with Brazil. We buy nearly all her raw products, while she spends the money we pay for them in England and France. In 1884, of the exports of Brazil, \$50,266,000 went to the United States, \$29,000,000 to England, and \$24,000,000 to France. Of the imports of Brazil in the same year, \$35,000,000 came from England, \$15,000,000 from France, and only \$8,000,000 from the United States.

The climate in those countries is warm, and the people use for clothing large quantities of cotton goods. Yet, although we produced last year in this country between five and six millions of bales of cotton, it is a remarkable fact that of the \$65,000,000 expended by Central and South America for cotton goods last year, over \$50,000,000 went to the merchants and manufacturers of England.

The countries of Central and South America need the products of our furnaces, of our factories, and of our farms. They need nearly everything we produce, and we need nearly everything they produce. They need American watches, American machinery, American mowers and reapers, American sewing machines, telephones, scythes, saws, shovels, hoes, axes, indeed nearly everything of which we have a surplus in this country. The map of the world does not show a region that has greater resources or greater possibilities than have North America, Central America, and South America.


I believe in less than twenty years there will be railroad communication between the city of New York and the capital of the Argentine Republic, Buenos Ayres. A few years ago, before the Central and Union Pacific Railroads were constructed, by which New York and San Francisco were connected by rail, the obstacles in the way of that work were greater than those which now exist in the way of connecting New York by rail with the capital of the Argentine Republic. Already the grand movement has commenced. To-day there is railroad connection between New York and the capital of Mexico, and arrangements have been made between the Mexican Republic and the Republic of Guatemala for the construction of a railroad from the city of Mexico to the capital of Guatemala.

That has been done on this end of the line. If you go to the other end, you find that the Argentine Republic is now engaged in building a railroad from Buenos Ayres, its capital, to its northern boundary line; and when the railroad gets to that northern line, there will come into operation a contract already made by Bolivia, giving \$40,000 per mile and 11 square leagues of land to an English company that has agreed to build the railroad from the line between the Argentine Republic and Bolivia to the capital of Bolivia. What is left? But little over 3,000 miles between the capital of Bolivia and the capital of Guatemala; and I assert that the probability of the construction of that railroad is stronger to-day than was the probability of the construction of the Central Pacific and Union Pacific ten years before they were built.

The Sand Freezing Process.

A recent number of the *Annales Industrielles* states that a mine shaft is being successfully sunk by M. Alexandre, of the Houssu Company, in Belgium, through a stratum of moist sand 12 m. thick, met with at 70 m. depth, by the Poetsch method, which consists in freezing the sand, then excavating it like rock. In the present case ten iron tubes, with cutting crown, are inserted in the sand at about 1 m. interval, penetrating the coal below. Into these are put other tubes, through which is passed a very cold liquid, to return by the larger tubes—generally chloride of magnesium cooled by expansion of ammonia. The sand is frozen more than 3 m. round the tubes. It has the appearance of a rock harder than the compact chalk of the English Channel tunnel. It is sparkling and speckled with particles of coal. The chloride of magnesium, injected at -14° C., returns at -12°. A thermometer inserted 10 cm. in the stratum read -8°. M. Poetsch's method was some time ago applied to making a tunnel at a small depth under part of the city of Stockholm, as described and illustrated in our pages.

M. HIGNETTE makes a white artificial stone from sand which has been used for polishing plate glass.



THE HORNED LIZARD.

while in 1884 it was more than \$53,000,000. The entire imports from the United States for twenty years were \$6,000,000 less than those from the three commercial nations of Europe just named for the year 1884.

In the last two years the government of the Argentine Republic has made contracts for \$59,000,000 worth of railway improvements, including a line of road northward into Bolivia and two lines in the direction of Chili and Peru, so as to bring the commerce of the Pacific slope into the harbor of Buenos Ayres, instead of taking it around the Straits of Magellan.

In 1874 the foreign commerce of Chili amounted to \$42,000,000. In 1884 it reached \$132,000,000. From \$50,000,000 to \$60,000,000 in merchandise is imported into Chili every year, of which England furnishes over \$25,000,000, France over \$12,000,000, Germany over \$8,000,000, and the United States \$3,000,000.

Adding the imports of Brazil to those of Uruguay, Chili, and the Argentine Republic, it will be found that the aggregate value of manufactured products introduced into those four countries annually reaches the enormous sum of \$250,000,000, of which England furnishes about one-half, France about \$50,000,000, Germany about \$35,000,000, and the United States about \$17,000,000.

We have no adequate conception of the present magnitude of these markets, nor of their prospective value. The manufacturers of the United States can supply almost every article represented in that \$250,000,000. From the report of the commissioners to South America I have gathered some remarkable facts.

We have more trade with either Belgium, Italy, the Netherlands, Spain, Switzerland, Russia, China, Japan, and Australia than we have with all the Central American States combined. We have nearly as much trade with Greece as we have with Chili. We sell more sewing machines in Switzerland than we sell in Chili,

ENGINEERING INVENTION.

An automatic railroad switch has been patented by Mr. William H. Stowell, of Eureka, Nevada. A heavy central rail is curved to the deflection required and permanently secured to the cross ties, while a deeply flanged wheel is secured beneath the engine, adapted to be raised or lowered to the level of the central rail, to engage therewith, by which means the direction of the train is controlled.

AGRICULTURAL INVENTIONS.

A corn harvester has been patented by Mr. Jesse L. Lamont, of Atkinson, Ill. The machine is designed to simultaneously remove the ear from the stalk and husk it, the husked ears being pushed rearward and delivered to an elevator or conveyor mechanism which will deliver the ears to a wagon or other suitable receptacle.

An attachment for corn planters has been patented by Mr. William H. Bowman, of South Solon, Ohio. It is a check attachment applicable to any style of corn planter, and may also be used for drilling the corn, the construction also providing means whereby in irregularly shaped fields the checking may be accomplished as regularly as in rectangular fields.

A harrow for listed crops has been patented by Mr. Hugh A. Murphy, of Elk City, Kansas. It consists of a number of narrow harrow sections yielding supported by elevated connecting rods, the harrow sections being made adjustable, the invention providing an implement by which ground that has become hard baked may be broken up and pulverized.

MISCELLANEOUS INVENTIONS.

A nut lock has been patented by Messrs. Frank and John Rennie, of Dayton, Ohio. It consists of a rod formed with a bolt-receiving loop, one of the ends of the rod being bent over upon itself toward the loop to form a nut-locking arm.

A combination lock and alarm has been patented by Mr. Robert Baumann, of St. Louis, Mo. The invention covers a novel construction and arrangement of parts and combinations of the same, making an improved alarm lock for doors, money drawers, etc.

A mop holder has been patented by Mr. Benjamin F. Gilbert, Jr., of Fair Haven, Vt. The bail is pivotally secured to the handle, to which also is pivotally secured a clamp jaw, the bail forming a guide for the ends of the clamp jaw, the handle in no way interfering with the insertion and removal of the mop.

A basket bottom has been patented by Mr. Albert W. Beckett, of St. Catharines, Ont., Canada. It is stamped up from sheet metal or paper or other suitable material, and provided with base corrugations to give the required strength, and with other corrugations and perforations to receive the side standards.

A tension device for the warp beam of looms has been patented by Mr. Chester Bailey, of Janesville, Wis. The tension is increased or diminished according to the locality of a weight upon a lever, the weight being automatically and continuously moved toward the fulcrum as the diameter of the roll of warp diminishes, thus maintaining a uniform tension.

A bottle has been patented by Mr. Henry Ader, of Somerset, Ind. It is a cylindrical body with threaded ends and a cross partition dividing it into two compartments, in which two substances may be carried and kept separate, the upper compartment being available for fluids, while the lower one may be used for pills, powders, etc.

An earth scraper has been patented by Mr. Julius D. Brainard, of Highmore, Dakota Ter. It has a scoop-locking device, a rotary handle bar, and connections between them for operating the locking device, with other novel features, whereby the scraper can be brought back after each dumping action exactly to the point where the previous scraping ended.

A folding stand for camp stools has been patented by Mr. Albert Cooper, of Brooklyn, N. Y. Rods constitute the legs, hinged at their upper ends in a cup or frame, other seat or top rods supporting the seat, hinged at their lower ends in a lower cup or frame, the upper and lower cups or frames being apertured to receive, brace, and guide the seat rods and the legs.

An apparatus for treating cereals has been patented by Mr. Henry R. Robbins, Jr., of Baltimore, Md. The invention relates to a means of cooking cereals by steam in accordance with a former patented invention of the same inventor, for more conveniently and expeditiously charging and discharging the receptacle and economically and uniformly treating the materials.

A felting roll for hat sizing machines has been patented by Mr. Aaron T. Clark, of Newburg, N. Y. It is of a novel yielding construction on its acting surface and throughout the main portion of its body, to have a continuous yielding spiral pressure-like action upon the hat bodies, thereby making the quality of work more even and more closely resembling such work done by hand.

An air pump governor has been patented by Mr. Edward G. Moore, of Wilmington, Del. It is a novel construction especially adapted for the air pumps of locomotives, to prevent an excess of pressure in the train pipes, and to cause an accumulation of air in the air reservoir while the brakes are applied, thus permitting an instantaneous release of the brakes when desired.

A stove for burning light fuel has been patented by Mr. Raymond O. Peyton, of Terre Haute, Ind. It has a cylindrical body of sheet iron, adapted to rest unattached upon the stove legs, one head of the cylinder being permanently attached while the other head is detachable and constitutes the door, with other novel features, making a cheap portable stove.

A flour bolting reel has been patented by Mr. Washington Gilleland, of Land, Ga. The sections of bolting cloth are secured to the reel frame in a novel and improved manner, the construction being such that the reel will work faster and the flour be bolted cleaner, while the sections of bolting cloth may be removed separately from the reel for repair or replacement without disturbing the other sections.

A soot collector for gasoline stoves has been patented by Margaret M. Joslyn, of Grand Meadow, Minn. It consists of an inverted funnel placed over the burner while the gasoline is being burned, with its wider end opening downward and its narrower end closed by a perforated sheet metal disk, the smoke passing through the apertures of the disk being received on a moistened cloth thrown over the funnel.

A cotton press has been patented by Messrs. Peter L. and William Brady, of Hearne, Texas. It has two series of rollers arranged in a circle, one series journaled in a movable carriage, and both series receiving motion from drive wheels on opposite sides of the machine, the cotton being compressed by a continuous operation as received from the gin, and the bale cover wrapped around and fastened by ties when the bale is wholly inclosed by the press.

A road machine and road digger and scraper form the subject of two patents issued to Mr. Alberto Finks, of New Berlin, N. Y. The invention covers a carriage or main frame, a digger bar and scraper bar, and elevating devices, the invention consisting particularly in the novel constructions for elevating the bars and adjusting the angle of the scraper bar, while the scraper, being concaved in front and under edge, gives better results than a straight scraper, covering more surface in its travel, and the machine is simple and strong.

SCIENTIFIC AMERICAN
BUILDING EDITION.

MARCH NUMBER.—(No. 29.)

TABLE OF CONTENTS.

- Elegant plate in colors, showing perspective elevations and floor plans of a cottage of moderate cost, together with full specifications, sheet of details, etc., etc.
- Plate in colors of a handsome suburban residence, costing about Twelve Thousand Five Hundred Dollars, with floor plans, specifications, sheet of details, etc.
- Elevations and floor plans of two dwellings of moderate cost.
- Perspective view and floor plans of a house for Six Thousand Dollars.
- Floor plans and elevations of a substantial residence at Tuxedo Park.—James Brown Lord, architect.
- Perspective and two plans of a Cape Cod cottage of moderate cost.
- Plans and perspective of a double house, costing about Six Thousand Five Hundred Dollars.
- Elevation and plans of an alteration of a dwelling on Long Island.
- Sketch of a one story residence erected at Birmingham, Ala., at a cost of Four Thousand Five Hundred Dollars.
- Floor plans and perspective view of a neat cottage for Seventeen Hundred and Fifty Dollars.
- Plans of an English country house.
- Sketch of a handsome double house at Cleveland, Ohio. Cost, complete, Six Thousand Dollars.
- Illustration of a house costing Three Thousand Dollars.
- Designs of two substantial churches, costing about Four Thousand Dollars each.
- Elevation and floor plans of a brick residence at Newark, N. J. Cost, complete, Seven Thousand Six Hundred and Seventy-five Dollars.
- Sketch of the hall and stairway of a luxurious English dwelling.
- Design for a carriage house and stable. Cost, Fifteen Hundred Dollars.
- Plan of an old plaster ceiling, South Quay, Yarmouth.
- Architectural Suggestions.—A Stairway in the Hotel Cluny.—A Stairway in Rouen.
- Miscellaneous Contents: Ancient Water Works.—Making the House Water-Tight.—Mahogany.—Vibration of Buildings.—Building Accidents.—The Column Vendome, Paris.—Learning to Design Buildings.—Non-Inflammable Wood.—Large Redwood Boards.—An Experiment on the Expansion of Iron in Buildings.—Ornamental Hedges.—The Acoustics of Buildings.—Suggestions on House Painting.—Right and Left in Landscape Painting. Furniture Woods.—Range Boiler Explosion, with illustrations.—Plastering of Walls, Westminster Hall.—Notes on Bricks.—Mineral Wool.—The Jackson Ventilating Grate, illustrated.—The Spencer Hot Water Heater, illustrated.—The Alsop Furnace, illustrated.

The Scientific American Architects and Builders Edition is issued monthly. \$2.50 a year. Single copies, 25 cents. Forty large quarto pages; equal to about two hundred ordinary book pages; forming, practically, a large and splendid MAGAZINE OF ARCHITECTURE richly adorned with elegant plates in colors and with fine engravings, illustrating the most interesting examples of Modern Architectural Construction and allied subjects.

The Fullness, Richness, Cheapness, and Convenience of this work have won for it the LARGEST CIRCULATION of any Architectural publication in the world. Sold by all newsdealers.

MUNN & CO., PUBLISHERS,
361 Broadway, New York.

Business and Personal.

The charge for insertion under this head is One Dollar a line for each insertion; about eight words to a line. Advertisements must be received at publication office as early as Thursday morning to appear in next issue.

Wanted—Active, influential men, capable of dealing with principals, who can introduce the Edison recording steam gauge to the notice of steam users in their vicinity. For particulars address Jarvis B. Edson, 91 Liberty St., New York.

U. S. and Canada patent rights for sale—No. 365,181 and 27,410, issued in 1887. Witter's improved bevel. For terms, address F. E. Witter, Brooklyn, Ct.

Patent foot power scroll and circular saw, mortisers, lathes. Seneca Falls Mfg. Co., 606 Water St., Seneca Falls, N. Y.

Finished wood boxes of all kinds made by F. D. Martin & Co., N. Springfield, Vt. Correspondence solicited.

Portable grinding mills. Chas. Kaestner & Co., Chicago, Ill.

Burnham's turbine wheel is sold at net price to mill owners. Catalogue free. Address York, Pa.

The Dieble Manufg. Co., Philadelphia, Pa., manufacturers of the Challenge Emery Grinding and Polishing Machinery, invite correspondence with all needing this class of machinery. Catalogues and prices on application.

The Diamond Prospecting Co., 22 W. Lake St., Chicago, Ill., general agents for the Sullivan diamond prospecting drills.

Foree Bain, 76 Market St., Chicago, designer and constructor. Electrical apparatus, fine and special machinery, etc.

Nickel Plating.—Manufacturers of pure nickel anodes, pure nickel salts, polishing compositions, etc. \$100 "Little Wonder." A perfect Electro Plating Machine. Agents of the new Dip Lacquer Kristaline. Complete outfit for plating, etc. Hanson, Van Winkle & Co., Newark, N. J., and 92 and 94 Liberty St., New York.

Perforated metals of all kinds for all purposes. The Robert Aitchison Perforated Metal Co., Chicago, Ill.

The Railroad Gazette, handsomely illustrated, published weekly, at 73 Broadway, New York. Specimen copies free. Send for catalogue of railroad books.

The Knowles Steam Pump Works, 113 Federal St., Boston, and 93 Liberty St., New York, have just issued a new catalogue, in which are many new and improved forms of Pumping Machinery of the single and duplex, steam and power type. This catalogue will be mailed free of charge on application.

Feed grinders. Chas. Kaestner & Co., Chicago, Ill.

Link Belting and Wheels. Link Belt M. Co., Chicago.

Iron Planer, Lathe, Drill, and other machine tools of modern design. New Haven Mfg. Co., New Haven, Conn.

Supplement Catalogue.—Persons in pursuit of information of any special engineering, mechanical, or scientific subject, can have catalogue of contents of the SCIENTIFIC AMERICAN SUPPLEMENT sent to them free. The SUPPLEMENT contains lengthy articles embracing the whole range of engineering, mechanics, and physical sciences. Address Munn & Co., Publishers, New York.

Presses & Dies. Ferracute Mach. Co., Bridgeton, N. J.

The Holly Manufacturing Co., of Lockport, N. Y., will send their pamphlet, describing water works machinery, and containing reports of tests, on application.

Lathes for cutting irregular forms a specialty. See ad. p. 62.

Curtis Pressure Regulator and Steam Trap. See p. 77.

Billings' Drop Forged Steel C Clamps. Drop Forgings, all kinds. Billings & Spencer Co., Hartford, Conn.

Steam Hammers, Improved Hydraulic Jacks, and Tube Expanders. R. Dudgeon, 24 Columbia St., New York.

Gang drills for light work, 3/8 and under. Automatic or lever feed. Dwight Slate Machine Co., Hartford, Conn.

60,000 Emerson's 1887 Book of superior saws, with Supplement, sent free to all Sawyers and Lumbermen. Address Emerson, Smith & Co., Limited, Beaver Falls, Pa., U. S. A.

Friction Clutch Pulleys. D. Frisbie & Co., N.Y. city.

Paint mills. Chas. Kaestner & Co., Chicago, Ill.

Practical working drawings of machinery made by A. K. Mansfield & Co., 290 Broadway, N. Y. Correspondence invited.

"The Improved Greene Engine." Flat slide valves, both steam and exhaust. Providence, R. I., Steam Engine Co., sole builders.

Pedestal tenoner. All kinds woodworking machinery. C. B. Rogers & Co., Norwich, Conn.

"How to Keep Boilers Clean." Send your address for free 88 page book. Jas. C. Hotchkiss, 120 Liberty St., N. Y.

Split Pulleys at low prices, and of same strength and appearance as Whole Pulleys. Yocom & Son's Shafting Works, Drinker St., Philadelphia, Pa.

Engines and boilers. Chas. Kaestner & Co., Chicago, Ill.

Send for new and complete catalogue of Scientific Books for sale by Munn & Co., 361 Broadway, N. Y. Free on application.

NEW BOOKS AND PUBLICATIONS.

ANIMAL LOCOMOTION. By Eadweard Muybridge. 1872-1885. Plates. University of Pennsylvania.

Mr. Eadweard Muybridge may justly claim a title to the remembrance of posterity as being a systematic worker in photographic studies of animal movements. His first work was done in California, and at once attracted the attention of the world. Recently he has carried on his investigations under the auspices of the University of Pennsylvania, and as a result has secured many hundred plates of human beings and of animals in motion. He has selected representatives of both sexes, of average and of abnormal sizes and of different ages, and has studied the movements of each. He has photographed successive phases of running, jumping, dancing, and every form of motion. A child creeping on hands and knees is reproduced, showing the same succession of steps that are found in the regular progression of animals. In an elaborate analytical table the different plates are classified, in order that any given selection can be made. For

artists especially the work is invaluable. With its results to study there should be no excuse in painting for the constrained positions often servilely copied from a tired model. The complete series comprises over 100 large photographs from instantaneous plates, each plate showing from 12 to 36 figures in different positions. It is a remarkable work, and its realization has involved a vast amount of labor and perseverance.

THE GEOLOGICAL EVIDENCES OF EVOLUTION. By Angelo Heilprin. Philadelphia: Published by the author. 1888. Pp. 99.

This little work, elegant in its printing and illustrations, is an amplification of a lecture delivered by Prof. Heilprin, at the Academy of Natural Sciences, Philadelphia. It is an earnest argument in favor of Darwinism, which the author regards as conclusively proved. He ends by saying that if the geological facts cited are not conclusive in favor of evolution, then "science is a delusion and a snare, and we will be compelled to begin anew our conception of the universe." The history of science in the past is a history of errors, and the assertion, while meant to be very broad, can hardly be so regarded in the light of the small extent of modern knowledge. Until some few of the primary facts in nature are accounted for, until gravitation, light, electricity, and molecular and atomic forces are put upon an intelligible basis, it is too soon to consider any purely theoretical conception as proved. The well known clearness and precision of the author's style are discernible throughout the work and make it most agreeable reading, whether we consider that the Darwinian theory is proved or not by the facts brought forward in less than one hundred small pages. The elegant plates which represent fossil remains with photographic accuracy form one of the pleasing features of this admirable book. Prof. Heilprin's work is every day acquiring more recognition, and this treatise will be no detriment to it.

HARVARD REMINISCENCES. By Andrew P. Peabody, D.D., LL.D. Ticknor & Co. Cloth. Price \$1.25.

This little work contains a number of sketches of the prominent men whose names appeared as college officers at Harvard nearly sixty years ago. Among them may be mentioned Josiah Quincy, Edward Everett, Henry Ware, John G. Palfrey, Charles Follen, John Langdon Sibley, C. C. Felton, Benj. Peirce, etc. The memoirs consist of personal reminiscences of the authors. The work concludes with a picture of college life at Harvard when the author was a student there, in the twenties, and a more striking illustration of the change that has taken place in our customs can hardly be found. Morning prayers at six in the morning, evening prayers at six o'clock, a recitation immediately after morning prayers, and then breakfast, which consisted simply of coffee and hot rolls. Dinner at half-past twelve, and in the evening tea and rolls for supper. The rooms were furnished with plain pine furniture, a bed and washstand and table or desk and a few chairs being the full complement of a well equipped room. A carpet was a luxury only indulged in by the very rich, and even then only during the latter part of one's course. The book will be of interest to Harvard graduates.

DES EMPLOIS CHIMIQUES DU BOIS DANS LES ARTS ET L'INDUSTRIE. Par Othon Petit. Ingenieur Librairie Polytechnique. Baudry et Cie., Paris, France. 1 vol. 8vo, paper. 1888. Price \$5.

The author treats of the subject of wood and the various processes by which the composition of the wood is destroyed or altered in such a way as to liberate certain of its elements, such as carbon, methyl alcohol, acetic acid, cellulose, tannic acid, etc. Combustion produces a complete chemical transformation of the elements of which the wood is composed. The manufacture of tannin and paper pulp alone have brought on a perfect avalanche of patents, many of which are based upon principles that are faulty or incomplete. The object of the present work is to furnish such data as may be of future use in the treatment of wood by chemical processes, and also a description of the apparatus employed in carrying out these processes. The treatise comprises papers on the composition of vegetable tissues, upon wood considered as combustible, on the extraction of carbonate of potash, on the manufacture of charcoal, tar, turpentine, on distillation of various spirits, on the manufacture of tannin and paper pulp, and the transformation of wood into glucose. There is also a list of French patents relative to the extraction of tannin and the manufacture of paper pulp from January 1, 1870, to January 1, 1887.

WIDE AWAKE. An illustrated magazine. We have received copies of this eminently "Wide Awake" monthly magazine, published at \$2.40 a year by the D. Lothrop Co., of Boston, Mass. In its elegance of illustration and typography it leaves nothing to be desired, while its wide range of topics should please every taste. Many of the articles are accompanied by fac-similes of the author's signature, which to many is a feature of interest. The cover, a floral design in subdued tints of the crushed strawberry type, is extremely delicate and attractive.

Received.

PRACTICAL PHYSICS FOR SCHOOLS AND THE JUNIOR STUDENTS OF COLLEGES. ELECTRICITY AND MAGNETISM. By Balfour Stewart, F.R.S., and W. W. Haldane Gee, B.Sc. London and New York: Macmillan & Co. Pp. 221. Price 60 cents.

HOT WATER SUPPLY. A Practical Treatise upon the Fitting of Hot Water Apparatus for Domestic and General Purposes. By F. Dye. London and New York: E. & F. N. Spon. Pp. 82. Price \$1.

HOME SANITATION. A Manual for Housekeepers. By the Sanitary Science Club of the Association of Collegiate Alumnae. Boston: Ticknor & Co. Pp. 80. Price 50 cents.

HANDBOOK FOR STEAM USERS. Being Rules for Engine Drivers and Boiler Attendants, with notes on Steam Engine and Boiler Management. By M. Powis Bale. London and New York: Longmans, Green & Co. Pp. 95. Price 75 cents.

Any of the above books may be purchased through this office. Send for new catalogue just published. Address MUNN & CO., 361 Broadway, New York.

Notes & Queries

HINTS TO CORRESPONDENTS.

Names and Address must accompany all letters, or no attention will be paid thereto. This is for our information, and not for publication. References to former articles or answers should give date of paper and page or number of question. Inquiries not answered in reasonable time should be repeated; correspondents will bear in mind that some answers require not a little research, and, though we endeavor to reply to all, either by letter or in this department, each must take his turn. Special Written Information on matters of personal rather than general interest cannot be expected without remuneration. Scientific American Supplements referred to may be had at the office. Price 10 cents each. Books referred to promptly supplied on receipt of price. Minerals sent for examination should be distinctly marked or labeled.

(1) E. D. and many others.—Any body, as a sphere of metal, that is impervious to water, and hollow, so as to be but little more than the specific gravity of water at the surface, will find its equilibrium at considerable depths in the sea. Water is but slightly compressible, and although there is immense pressure at great depths, the specific gravity is but slightly raised; hence all objects that are slightly heavier than water sink to the bottom of the sea at great depths. Aluminum, one of the lightest metals, will quickly find the bottom of the deepest seas.

(2) D. M. G. asks for a preparation to be used as the hand grenades, to extinguish fires. Wish to use ordinary quart glass flasks, and would like the solution not to freeze in ordinary temperatures in our State (Michigan). A solution of common salt or sulphate of soda in water, making a strong brine, forms a good home-made fire extinguisher, and such solutions do not freeze easily. By adding lime dust and sulphuric acid, and corking tightly, carbonic acid is generated under pressure, but this gas easily escapes if not most securely sealed. We cannot specify the composition of the various patented solutions, for which reference must be made to the patents. See SCIENTIFIC AMERICAN SUPPLEMENT, Nos. 358 and 535, for valuable articles on this subject.

(3) G. K. writes: I have a pair of buck horns I wish to mount; what should I use to whiten and polish the skull connecting the horns, also what is the best polish for the horns themselves? A. You can bleach the shell by dipping into a solution of hydrogen peroxide or a solution of chloride of lime. To polish the horns, first scrape with a glass or steel scraper to take off any roughness, then grind some pumice stone to powder and with a piece of cloth wetted and dipped in the powder rub them until a smooth face is obtained. Next polish with rotten stone and linseed oil, and finish with dry flour and a piece of clean linen rag.

(4) E. H. D. desires (1) recipes for making purple, green, and black type writer copying inks. A. Use any desired aniline color. Dissolve in 15 parts alcohol, and add 15 parts glycerine. 2. What photographic preparation is most sensitive to artificial light, and how is it compounded? A. Gelatino-bromide of silver is the most sensitive. See SCIENTIFIC AMERICAN SUPPLEMENT, No. 541.

(5) E. E. S. asks how photographs can be mounted on ordinary writing paper, so they will not wrinkle and curl. A. Roll the damp prints up in little bundles with the albumen face outward and allow them to dry spontaneously; each bundle is rolled in a sheet of note or foolscap paper. When the prints are dry they are flattened and placed in a book or portfolio, and are then ready to be trimmed. Make a solution of bleached shellac in alcohol, so that it will be somewhat thick. The print is laid face downward and its back covered with the shellac solution; it is then mounted in the usual way upon the card mount or other thin paper support. Allow no shellac to get on the face of the print, as it cannot be removed without injuring it.

(6) G. A. D. asks: What is a good receipt for making a pure baking powder, and how should it be used? A. One of the simplest and best receipts for a baking powder is the following: Take of powdered cream tartar 30 ounces, bicarbonate of soda 15 ounces, flour 5 ounces. All of the ingredients must be well dried. Mix thoroughly and keep dry.

(7) E. D. F. asks the best stain for red, blue, and wine color, by dipping, for cheap chairs. A. For red boil 1 pound Brazil wood and 1 ounce pearl ash in a gallon of water, and while hot brush over the work until of a proper color. Dissolve 2 ounces alum in 1 quart of water and brush the solution over the work until it dries. For blue, boil 2 ounces of indigo, 2 lb. of wood, and 1 ounce alum in 1 gallon water, brush well over until thoroughly stained. For wine color, ground Brazil wood 1 pound, water 3 quarts, cochineal 1/2 ounce; boil the Brazil wood with the water for an hour, strain, add the cochineal, boil gently for half an hour, and it will be read for use.

(8) C. R. asks how to remove black heads, better known perhaps as comedones. A. Water in which ammonia has been dissolved frequently will entirely remove the cause of your complaint. The following paste is also largely used. Take of kaolin 4 parts, glycerine 3 parts, acetic acid 2 parts; make into a pomade with the addition of a little ethereal oil. See SUPPLEMENT, No. 542.

(9) J. R. writes: In carbonate potash solution recommended to preserve iron or steel tools from rust, what strength should solution be made? A. One-quarter pound carbonate potassa dissolved in one gallon of boiling water. Dip the work in the hot solution.

(10) F. K. asks (1) how to prepare bird lime. A. Boil the middle bark of the holly 7 or 8 hours in water, drain it, and lay it in heaps in the ground covered with stones for 2 or 3 weeks, till reduced to a mullage. Beat this in a mortar, wash it in rain water,

and knead until free from extraneous matters. Put it into earthen pots, and in a few days it will be ready for use. An inferior variety is made by boiling linseed oil for some hours until it becomes a viscid paste. 2. Is there any way to make wood elastic? A. No.

(11) E. M. P. asks how he could make a good stain for brick that would be permanent and not wash off with the rain. A. Dissolve 1 ounce of glue in a gallon of water, and when hot put in a piece of alum the size of an egg, 1/2 pound Venetian red, and 1 pound Spanish brown. Try a little on the bricks; if too light, add more red and brown; if too dark, put in more water.

(12) J. P. H. H. desires a receipt for removing discolorations from granite caused by overhanging trees, something that will restore it to original color, without damaging the stone. A. Try a weak solution of hydrochloric acid or a solution of caustic potash.

(13) G. Z. asks what the difference is between Epsom, Rochelle, and arlsbad salts, also tests for crystalline corrosive sublimate or mercuric chloride and sulphate of iron. A. Epsom salts are magnesium sulphate, Rochelle salts are the tartrate potash and soda, and Carlsbad salts are the solid residue obtained by evaporating the water of that celebrated spring in Austria. Corrosive sublimate should be perfectly soluble in sufficient water and in ether, and should be perfectly volatile. It gives a black precipitate with hydrosulphuric acid insoluble in dilute warm nitric acid. Sulphate of iron gives a pale blue precipitate with ferrocyanide of potash that darkens on exposure to the air. Many other tests could be given.

TO INVENTORS.

An experience of forty years, and the preparation of more than one hundred thousand applications for patents at home and abroad, enable us to understand the laws and practice on both continents, and to possess unequalled facilities for procuring patents everywhere. A synopsis of the patent laws of the United States and all foreign countries may be had on application, and persons contemplating the securing of patents, either at home or abroad, are invited to write to this office for prices, which are low, in accordance with the times and our extensive facilities for conducting the business. Address MUNN & CO., office SCIENTIFIC AMERICAN, 361 Broadway, New York.

INDEX OF INVENTIONS

For which Letters Patent of the United States were Granted

February 28, 1888,

AND EACH BEARING THAT DATE.

[See note at end of list about copies of these patents.]

Table listing inventions with names and patent numbers. Includes items like Acid apparatus for making sulphurous, C. E. Getchell, 378,673; Air brake, automatic, R. Solano, 378,628; Amalgamating gold and silver, W. W. Wheeler, 378,750; Animal trap, Cattell & Summers, 378,767; Animal trap, E. Herrington, 378,789; Animal trap, live bait, E. Herrington, 378,790; Ant trap, M. C. Miller, 378,709; Arc light, L. N. P. Poland, 378,616; Axle box, car, J. Stephenson, 378,477; Axle truss, wagon, O. J. Williams, 378,585; Bag, See Paper bag; Bags, frame for traveling, W. Roemer, 378,620; Bags, frame for traveling, F. C. Schmidt, 378,623; Baling press, Frey & Schwarzburg, 378,581; Barrels and other vessels, composition for filling up cracks in, Klein & Schattels, 378,586; Basket, L. A. Brown, 378,492; Basket bottom, A. W. Beckett, 378,757; Bath, See Blotter bath; Battery, See Secondary battery; Battery vessels, J. Wiest, 378,484; Batteries, automatic switch for secondary, J. S. Sellon, 378,527; Bed, couch, J. P. Miller, 378,708; Bedstead, adjustable crib, C. Morse, 378,455; Belt, chain, C. W. Hunt, 378,686; Bicycle support, J. F. Conley, 378,496; Bin, See Feeding bin; Blast furnace, E. A. Wheeler, 378,749; Blast furnace bosh plate, J. Kennedy, 378,550; Blasting plug, A. Winder, 378,820; Bleaching by electrolysis, apparatus for, Hermite & Cooper, 378,651; Block, See Pulley block. Stove block; Blotter and pen wiper, combined, E. Promis, 378,719; Blotter bath, H. F. Arnold, 378,641; Board, See Mould board; Boat detaching apparatus, R. M. G. Brown, 378,768; Boats, construction of, A. Olsen, 378,613; Bolt, W. W. Woodford, 378,857; Boots and shoes, lasting, J. W. Hatch, 378,444; Boots and shoes, manufacturing, J. W. Hatch, 378,445; Bottle, H. Ader, 378,752; Bottle stopper, F. P. Morhous, 378,800; Bottle stopper, W. H. Underwood, 378,743; Bottles, combined spreader and stopper for mullage and other, W. H. Underwood, 378,744; Box, See Axle box; Box, A. T. Linderman, 378,601; Brick machine, J. C. Anderson, 378,538; Bridge cables, suspender connection for, G. Lindenthal, 378,697; Bridges, cable for suspension, G. Lindenthal, 378,696; Brake, See Air brake; Brush, Foster & Kennedy, 378,784; Buckle, J. England, 378,667; Buckle, A. Prym, 378,555; Buckle, D. L. Smith, 378,730 to 378,734; Buckle, turn, C. H. Williams, 378,534; Buggy top, G. Wiggins, 378,485; Buildings, construction of, A. Smith, 378,627; Burner, See Gas burner. Hydrocarbon burner. Vapor burner; Burnisher, W. H. Boles, 378,760; Bustle, J. Galvin, 378,489; Camera tripod, W. H. Carpenter, 378,480; Case shaving machines, gauge attachment for, L. Janson, 378,591; Canelstripper, R. P. Sorrels, 378,735; Car, aisle, J. Stephenson, 378,480; Car bumper, A. W. Van Dorston, 378,532; Car coupling, J. Haish, 378,676; Car coupling, McCray & Shade, 378,702; Car coupling, W. T. Van Dorn, 378,813; Car, freight, H. V. Lucas, 378,602; Car dash trap, tram, J. Stephenson, 378,476; Car door hanger, tram, J. Stephenson, 378,474; Car door hanging, tram, J. Stephenson, 378,472; Car door operator, tram, J. Stephenson, 378,472; Car lamp house, tram, J. Stephenson, 378,469; Car, railway, J. A. Brill, 378,428; Car, railway, H. C. Gross, 378,675; Car roof, tram, J. Stephenson, 378,470; Car sash rail, tram, J. Stephenson, 378,471; Car, seal, Brown & Ketchum, 378,655; Car seat, F. H. Henry, 378,546; Car spring plates, die for making, N. H. Davis, 378,773; Car wheel, G. G. Lobdell, 378,844; Car window, tram, J. Stephenson, 378,473; Cars, draw bar for tram, J. Stephenson, 378,479; Cars, draw head hook for tram, J. Stephenson, 378,478; Cars, sliding door for freight, C. H. Dunham, 378,579; Cards, playing, F. Couch, 378,497; Carriage door lock, W. P. Fest, 378,582; Carriage maker's grooving and boxing tool, J. A. Traut, 378,554; Carriage tops, adjustable form for setting and building, C. C. Oakes, 378,457; Carrier, See Store service apparatus carrier; Case, See Pencil or pin case. Show case; Cash carrier apparatus, pneumatic, G. B. Kelly, 378,792; Cash carrier apparatus, pneumatic, W. A. Webber, 378,533; Caster, furniture, Berkey & Fox, 378,649; Caster socket, W. P. Tracy, 378,740; Catarh remedy, T. S. Greene, 378,504; Cereals, apparatus for treating, H. R. Robbins, Jr., 378,806; Chain, drive, B. A. Legz, 378,589; Chair, See Dental chair. Rail chair; Check hook, F. C. Kimball, 378,795; Chopper, See Cotton chopper; Churn, J. Ahrends, 378,753; Churn, R. F. Collins, 378,770; Churn, Gibbs & Harper, 378,501; Clamp, See Flask clamp; Clasp, See Corset clasp; Clip, See Trace attachment clip; Clock, advertising, G. Hoisholt, 378,589; Clothes pounder, M. A. Nelson, 378,711; Clutch, friction, Jones & Rogers, 378,448; Clutch, friction, W. Oesterlein, 378,803; Coal hod die, E. Barrath, 378,755; Coal hods, die press for forming, E. Barrath, 378,754; Combination lock and alarm, R. Baumann, 378,568; Compasses, correcting device for ships', L. Sirleix, 378,528; Cord or rope, machine for making, C. E. Brainard, 378,491; Corn dropper, automatic, J. H. Stiggleman, 378,808; Corn holder, hot, P. J. Godfrey, 378,503; Corset and bustle, combined, P. Parmenter, 378,518; Corset clasp, P. Lafin, 378,691; Corset steel protector, E. Cushing, 378,576; Cotton chopper, W. H. Harper et al., 378,443; Cotton picker, J. W. Wallis, 378,635; Cotton press, P. L. & W. Brady, 378,570; Coupling, See Car coupling. Hose coupling. Thill coupling. Vehicle coupling; Cranberries, device for picking, A. J. Disbrow, 378,775; Culinary vessel, J. P. King, 378,690; Culinary vessel, H. A. Manning, 378,700; Cultivator, J. P. Black, 378,651; Cultivator, N. Roggy, 378,463; Cuspidor, D. H. Murphy, 378,610; Dampers, adjusting device for, F. A. Garrett, 378,671; Dental chair, J. W. Cooper, 378,433; Die, See Coal hod die; Digger, See Patato digger. Road digger; Dish holder, C. H. Latham, 378,692; Door check, Shaw & Gillilan, 378,728; Door closer, G. W. Rodecap, 378,807; Draught shackle, vehicle, Botsford & Church, 378,589; Drill, See Mining drill. Multiple drill; Drilling machine, W. Wattie, 378,747; Dropper, See Corn dropper; Eaves trough hanger, H. B. Todd, 378,530; Egg tester, R. Stuckwisch, 378,853; Electric distribution, system of, T. Spencer, 378,737, 378,738; Electric generator regulator, W. S. Hill, 378,547; Electric generator, self-exciting, alternate current, O. A. Moses, 378,456; Electric wires or cables, conduit for, R. S. Waring, 378,561; Electric wires or cables, test box for underground, R. S. Waring, 378,560; Electrical conductors, underground conduit for, M. R. Muckle, Jr., 378,801; Electrical conduits, manhole chamber for underground, M. R. Muckle, Jr., 378,802; Electrical distribution, system of, Conant & Lathshaw, 378,432; Electrotpe types, bending, Miller & Dale, 378,707; Elevator, See Hydraulic or other elevator. Tide water elevator; Engine, See Steam engine. Traction engine; Engines, electrical stop motion for steam, R. Exle, 378,668; Envelope, Potter & Upham, 378,849; Erasers, cleaner for blackboard, J. S. McClung, 378,608; Etching on one or both sides, J. Baynes, 378,423; Evaporating apparatus, P. Laberie, 378,598; Evaporating liquids, vacuum apparatus for, S. M. Lillie, 378,843; Evaporator, See Fruit evaporator; Excavator, B. K. Reed, 378,720; Extractor, See Stump extractor; Fabric, See Woven pile fabric; Fabrics, apparatus for guiding, straightening and evening, S. Arnold, 378,822; Fan power, J. Carr, 378,659; Fan, rotary, W. J. Mingle, 378,710; Fanning mill, J. S. Constant, 378,772; Fastening device, C. H. Pratt, 378,461; Feed trough, A. N. Main, 378,608; Feed water purifier, E. G. T. Colles, 378,495; Feeding bin and trough, J. T. Woods, 378,536; Fence, J. F. Bazill, 378,425; Fence, W. A. Frushour, 378,832; Fence, W. Kelly, 378,798; Fence machine, wire and picket, W. Dixon, 378,777; Fertilizer, P. C. Jensen, 378,688; Filter, Clarke & Conroy, 378,431; Firearm, magazine, A. W. Savage, 378,525; Fire escape, D. H. Sweeney, 378,529; Fire escape, portable, G. Gavin et al., 378,833; Fishing reel, P. H. Yauman, 378,565; Flask clamp, adjustable, A. C. Allbee, 378,640; Flies, device for poisoning, J. B. Kibler, 378,509; Flour bolting reel, W. Gilleland, 378,785; Fluid discharge device, C. N. Tyler, 378,812; Fluid pressure, machine to be driven by, W. P. Canning, 378,541; Fruit evaporator, E. White, 378,483; Fur blower, T. J. Sayre, 378,622; Furnace, See Blast furnace. Hydrocarbon furnace; Furnace, Huidekoper & Houze, 378,539; Gauge, See Weather baroding gauge; Garment stretcher, F. Cadmus, 378,764; Gas burner, incandescent, J. Mactear, 378,699; Gas enriching apparatus, J. H. Amies, 378,418; Gas from gas mains, means for carrying off escaping, J. W. Ellis, 378,544; Gas lighting apparatus, electric, C. W. Holtzer, 378,577; Gas, manufacturing water, R. Boeklen, 378,490; Gate, See Railway gate; Gate, C. Wilson, 378,564; Generator, See Electric generator; Glass, machinery for beveling the edges of plates of, O. C. Hawkes, 378,680; Glove, D. B. Gunn, 378,534; Grain binder, F. A. Murdock, 378,845; Grain binders, knotting device for, W. N. Whiteley, 378,815; Gravel, etc., box for washing, T. W. Carrio, 378,765; Groats, separating machine for cleaning, E. Weiss, 378,562; Gum, machine for manufacturing chewing, W. J. White, 378,637; Gun, magazine, R. F. Cook, 378,661; Gun, magazine, E. E. Redfield, 378,556; Gunpowder press and grainer, P. A. Oliver, 378,516; Hammer, nail, D. P. Bigelow, 378,650; Hammer, steam pile driving, J. N. Warrington, 378,745; Handle attachment, F. Brough, 378,540; Hanger, See Car door hanger. Eaves trough hanger. Tobacco hanger; Harrow for listed crops, H. A. Murphy, 378,611; Harrow, sulky, M. S. & W. A. Doolittle, 378,573; Harvester and binder, combined, Whiteley & Bayley, 378,814; Harvester and thrasher, combined, M. P. Farnham, 378,581; Harvester, corn, J. L. Lamont, 378,551; Harvester, corn, D. T. Phillips, 378,521; Harvester, grain binding, W. N. Whiteley, 378,817; Hat sizing machines, felting roll for, A. T. Clark, 378,573; Hay rake and loader, C. P. Slaght, 378,466; Heater, See Hot water heater. Water or liquid heater; Heel nailing machine, F. F. Raymond, 2d, 378,417; Hide lifter and carrier for tanneries, A. M. Fletcher, 378,670; Hinge, butt, Prescott & Locke, 378,718; Hoe, R. S. Rinker, 378,723; Hog trough, S. Corderman, 378,434; Holdback, H. Hansberger, 378,505; Holder, See Corn holder. Dish holder. Mop holder. Sandpaper holder. Slate pencil holder; Hook, See Check hook. Trolling spoon hook; Hoop dressing machine, J. J. Moger, 378,454; Horse head protector, H. Zeffert, 378,858; Hose coupling, Atherton & Bentley, 378,566; Hot water heater, J. M. Thayer, 378,633; Hub, wheel, C. A. Kinney, 378,842; Hydraulic motor, G. W. Mason, 378,761; Hydraulic or other elevator, W. P. Gibson, 378,674; Hydrocarbon burner, H. L. Howse, 378,890; Hydrocarbon furnace, W. B. Smith, 378,852; Incubators, temperature regulator for, C. A. Corman, 378,435; Indicator, See Railway station indicator. Speed indicator; Ink pot or holder, A. Kempson, 378,595; Insect powder gun, J. Jaeger, 378,687; Insect trap, E. Herrington, 378,788; Insecticide, F. Feustell, 378,583; Ironing table, T. B. Porter, 378,553; Jar fastener, T. B. Howe, 378,685; Jars, etc., means for hermetically closing, C. H. P. Le Vilmorin, 378,498; Jersey stay, Kramer & Levy, 378,597; Joint, See Rail joint; Knitted undergarment, J. A. Scriven, 378,465; Ladder, step, A. M. Whiteley, 378,468; Lamp, carbureting, O. W. Bennett, 378,647; Lamp, double arc, Wightman & Rasmussen, 378,818; Lantern, tubular, C. Bergener, 378,648; Lasting machine, J. W. Hatch, 378,446; Lasting machine, Hatch & Pitcher, 378,506; Lifter, See Hide lifter; Light, See Arc light; Liquid receptacles, distributing tip for, W. H. Underwood, 378,742; Lock, See Carriage door lock. Combination lock. Nut lock. Oar lock; Lock, V. Jeannot, 378,593; Locomotive smokestack, P. J. Brown, 378,762; Looms, tension device for the warp beam of, C. Bailey, 378,567; Lumber trimming and assorting machine, A. T. Linderman, 378,796; Magnet, relay, E. L. Orcutt, 378,552; Mallet, C. A. Svensson, 378,632; Match for moulding with gated patterns, J. Wachalac, 378,634; Matrices, apparatus for fitting up, G. Mohr, 378,799; Mechanical movement, L. H. Nash, 378,847; Metal, decorating, J. Baynes, 378,420; Metal, ornamenting, J. Baynes, 378,421; Metallic plate, embossed, A. C. Hafely, 378,442; Metallic surfaces, decorating, J. Baynes, 378,422; Mill, See Fanning mill; Milling machine, A. H. Brainard, 378,427; Mining drill, coal, W. A. J. Thompson, 378,481; Mould board, R. Jones, 378,841; Mop attachment, C. Mansbarger, 378,605; Mop holder, B. F. Gilbert, Jr., 378,586; Motor, See Hydraulic motor. Steam motor; Mowing machine, Whiteley & Bayley, 378,816; Multiple drill, F. C. Weir et al., 378,748; Nail making machine, F. Bryant, 378,856; Nails, machine for making upholsterers', F. J. Bergmann, 378,824; Needle grooving machine, P. M. Beers, 378,489; Nozzle, C. L. Travis, 378,531; Nut lock, J. Edgar, 378,779; Nut lock, F. & J. Rennie, 378,618; Nut lock, H. O. Whyman, 378,563; Nut tapping machine, L. Wilkinson, 378,468; Oar lock, W. H. Rice, 378,722; Ordnance, breech-loading, Driggs & Schroeder, 378,828; Ore crusher, S. Kendall, 378,450; Ore, treatment of, Hersey & Conley, 378,588; Ore washer, T. Sharp, 378,626; Padlock, combination, Spencer & Sanders, 378,736; Paging machine, J. McAdams, 378,607; Paint, H. Burnett, 378,826; Paper bag, D. Appel, 378,487; Paper bags, machine for the manufacture of, C. F. Schmidt, 378,851; Paper bags, manufacture of, C. F. Schmidt, 378,52

Paper, manufacture of, Pearce & Beardsley..... 378,580
Pencil holder, slate, J. P. Podrea..... 378,738
Pencil or pin case, A. B. Chase..... 378,768
Pens or tubes, filling device for fountain, Rutherford & Bartram..... 378,524
Photographing apparatus, automatic electric, Bliss & Middleton..... 378,426
Pianos, music rack attachment for upright, H. Ziegler..... 378,496
Pipe. See Sheet metal pipe.
Pipes, apparatus for treating metal, H. G. Bealey..... 378,756
Plane, bench, H. M. Clark..... 378,494
Plane, bench, Mead & Traut..... 378,704
Planter attaching, corn, W. H. Bowman..... 378,569
Planters, regulating attachment for corn, W. M. Robinson..... 378,724
Plastering machine, D. W. Miles..... 378,453
Pocket attachment, J. T. Simpson..... 378,729
Posts, etc., preserving, C. W. Parker..... 378,459
Pot. See Ink pot.
Potato digger, C. Babcock..... 378,646
Press. See Baling press. Cotton press. Gunpowder press. Seal press.
Printer's galley, F. H. Boynton..... 378,654
Printing machines, ink distributing device for, J. Hackett..... 378,441
Printing transfer process, J. Baynes..... 378,419
Propeller, W. N. Chandler..... 378,600
Protector. See Corset steel protector.
Pulley block, S. H. M. & F. G. Leib..... 378,625
Pump, J. C. Carter..... 378,706
Pump, air, H. J. Doerr..... 378,686
Pump, crank, J. J. De Rycke..... 378,685
Pump governor, air, E. G. Moore..... 378,609
Pump piston and check valve, combined, J. M. Normand..... 378,848
Pump valve, M. W. Murphy..... 378,846
Pumps, pressure regulator for, P. Schuff..... 378,726
Punch, spring, W. C. Jones..... 378,549
Punching press feeding mechanism, F. H. Richards..... 378,806
Rack. See Wagon rack.
Rail chair, I. Wolfe..... 378,856
Rail joint, H. F. Cox..... 378,575
Rail splice or fish plate, H. F. Cox..... 378,543
Rails and rail joints, means for preventing the creeping of, J. J. Reilly..... 378,721
Railway brakes, valve for electro-pneumatic, J. F. Carpenter..... 378,658
Railway crossing, Crowell & Weir..... 378,827
Railway gate, J. Bolt..... 378,761
Railway signal, T. C. Lewis..... 378,451
Railway signaling device, T. P. Rodges..... 378,550
Railway station indicator, electric, G. Guntz..... 378,440
Railway switch, automatic, W. H. Stowell..... 378,809
Railways, rail connection for electric, E. L. Orcutt..... 378,517
Rake. See Hay rake.
Ratchet drill stock, C. H. Wilmoth..... 378,639
Reel. See Fishing reel. Flour bolting reel.
Regulator. See Electric generator regulator. Temperature regulator.
Riddle or sieve, E. Oliver..... 378,458
Road digger and grader, A. Finks..... 378,782
Road machine, A. Finks..... 378,781
Rolling mills, bloom manipulator for, R. Nay-smith..... 378,612
Rolls, mechanism for cleaning toothed feed, H. Tindell..... 378,759
Roof, sheet metal, F. E. Sagendorph..... 378,725
Rubber, lining hollow articles with hard, M. Dittenhoefer..... 378,776
Salt, apparatus for manufacturing, Hogel & Browne..... 378,684
Sandpaper holder, T. L. Prevost..... 378,522
Sash balances, manufacture of, S. Palmer..... 378,712
Sash fastener, O. K. Ketring..... 378,794
Sash fastener, H. J. Murphy..... 378,515
Sawmill carriage, G. M. Hinkley..... 378,683
Sawmill carriages, offset mechanism for, D. C. Prescott..... 378,717
Saw, wood, A. G. Langlot..... 378,510
Saws, guide for circular, J. S. Marshall..... 378,513
Scale, recording weighing, W. E. Selleck..... 378,557
Scale, weighing, M. B. Lloyd..... 378,698
Scraper, earth, J. D. Brainard..... 378,571
Screen. See Window screen.
Screw, L. H. Palmer..... 378,614
Screw stock, Engels & Wesselmann..... 378,880
Seal press, A. B. Schofield..... 378,624
Seat. See Car seat.
Seat corner fastening, J. W. Marcy..... 378,606
Secondary battery, M. Stecher..... 378,629
Seeding machine, G. W. W. Billings..... 378,758
Sewing machine, S. Arnold..... 378,645
Sewing machine, A. A. Bouton..... 378,653
Sewing machine, J. W. Post..... 378,504
Sewing machine, Stewart & Weiss..... 378,630
Sewing machine, book, J. R. Reynolds..... 378,461
Sewing machine, book, D. M. Smyth..... 378,467
Sewing machine shuttle, L. Williams..... 378,855
Sewing machine table, J. Wertheim..... 378,636
Sewing machines, clamp for loopers for, J. R. Reynolds..... 378,462
Sewing machines, device for straightening and evening fabrics for, S. Arnold..... 378,823
Sewing machines, hemstitching attachment for, T. L. Melone..... 378,706
Sewing machines, moistening attachment for shoe, G. Blakeney..... 378,759
Sewing machines, ruffling attachment for, T. L. Melone..... 378,705
Sewing, uniting fabrics by, S. Arnold..... 378,644
Sheet metal pipe, A. J. & C. Lindemann..... 378,601
Show case, J. J. Kelly..... 378,504
Signal. See Railway signal.
Siphon, C. N. Tyler..... 378,811
Skate, E. H. Barney..... 378,424
Skate runner blank, E. H. Barney..... 378,488
Sleigh, D. S. Anderson..... 378,821
Spark arrester, Henderson & Martin..... 378,507
Speed indicator, G. S. Heath..... 378,536
Sprinkler. See Street sprinkler.
Squeezer, G. Lindenthal..... 378,895
Staging, E. E. Strout..... 378,810
Statuette, F. J. Herrick..... 378,682
Steam engine, F. Arrington..... 378,643
Steam motor, O. E. Davidson..... 378,663
Steam trap, J. R. Wade..... 378,482
Stocking, F. Wilcomb..... 378,819
Stone blocks, manufacture of artificial, J. S. Peirce..... 378,715
Stone blocks or tiles for paving and other purposes, means for moulding artificial, J. S. Peirce..... 378,716
Stools, folding stand for camp, A. Cooper..... 378,574
Stopper. See Bottle stopper.
Store service apparatus, J. T. Cowley..... 378,542
Store service apparatus, G. R. Elliott..... 378,499
Store service apparatus, T. P. Farmer..... 378,545
Store service apparatus, carrier for, M. F. Adams..... 378,587

Store service apparatus, switch for, H. L. Lovejoy..... 378,511
Store service railways, track for, R. A. McCarty..... 378,514
Stove, A. L. Kendall..... 378,449
Stove block, Carroll & Hill..... 378,572
Stove for burning light fuel, R. O. Peyton..... 378,615
Stove hood ventilator, A. S. Fisk..... 378,669
Stove, straw burning, F. Girtanner..... 378,786
Stoves, soot collector for gasoline, M. M. Joslyn..... 378,508
Street sprinkler, railway, J. R. Gathright..... 378,672
Stump extractor, O. L. Gallup..... 378,500
Switch. See Railway switch.
Table. See Ironing table. Sewing machine table.
Telegraph, printing, P. B. Delany..... 378,437
Telegraph, repeater, L. Russell..... 378,464
Telegraphy, printing, P. B. Delany..... 378,436
Telephone, L. Ehrlich et al..... 378,780
Telephone exchanges, lock-out box and shunt circuit for, C. H. Haskins..... 378,679
Temperature regulator, Gurney & Peniston..... 378,835
Thill coupling, Hyatt & Dick..... 378,540
Three-way safety switch, Pascoe & Raub..... 378,519
Tide water elevator or system of utilizing the rise and fall of the tides, E. P. Lorch..... 378,452
Tile, illuminating, T. Sharts..... 378,558
Tile, paving, F. Brannigan..... 378,825
Tobacco hanger, W. J. Sculthorp..... 378,727
Trace attachment clip, C. J. King..... 378,689
Traction engine, A. K. Gibson..... 378,502
Trap. See Animal trap. Ant trap. Insect trap. Steam trap.
Trolling spoon hook, J. R. Harlow..... 378,678
Trough. See Feed trough. Hog trough.
Tubes, manufacture of sheet metal, E. K. Coas..... 378,769
Tubs, adjustable frame for laundry, C. J. Everett..... 378,580
Tumbler or bottle washer, L. L. Rowe..... 378,621
Type bars, machine for forming, O. Mergenthaler..... 378,797
Type bars, machine for producing, O. Mergenthaler..... 378,796
Valve, balanced slide, L. Adams..... 378,751
Valve, cut-off piston, P. Arrington..... 378,642
Valve mechanism for blowing engines, pumps, and similar apparatus, Forsyth & Potter..... 378,438
Valve, reversing, P. Maltby..... 378,604
Valve, sewer, P. F. Lenhart..... 378,600
Vapor burner, W. R. Park..... 378,718
Vehicle coupling, C. M. Parker..... 378,714
Vehicle, horse breaking, E. Herrington..... 378,837
Vehicle, two-wheeled, W. N. Bryan..... 378,493
Vehicle, two-wheeled, B. J. Healy..... 378,447
Vehicle, two-wheeled, C. W. & G. H. Jewett..... 378,791
Vehicles, sun shade attachment for, E. E. Dutton..... 378,829
Velocipede, E. G. Latta..... 378,693
Velocipede, A. M. Stoner..... 378,631
Veneer machine, J. W. Trout..... 378,741
Ventilator. See Stove hood ventilator.
Vessels, sheet ring detacher for, A. D. Post..... 378,554
Wagon, dumping, Rodgers & Hatten..... 378,523
Wagon rack, J. W. McMaster..... 378,703
Walls, building, E. E. Hiatt..... 378,838
Washer. See Ore washer. Tumbler or bottle washer.
Watch, stop, V. Jeannot..... 378,592
Water closet cistern, J. Demarest..... 378,664
Water or liquid heater, C. G. Marshall..... 378,512
Weather-boarding gauge, E. Hotchkiss..... 378,548
Weather strip, G. P. Dodge..... 378,778
Wells, system of bailing, S. C. Rhodes..... 378,619
Wheel. See Car wheel.
Whip stock core, H. S. Cushman..... 378,662
Wind instrument, C. G. Conn..... 378,771
Windmill, W. Burrows..... 378,429
Window screen and fixture, G. H. Gould..... 378,587
Wire, apparatus for tempering, E. J. Watson..... 378,746
Wood turning and moulding machine, C. I. Goehring..... 378,787
Woven pile fabric, J. Dobson..... 378,577
Wrench, Gavin & Crome..... 378,564
Wrench, W. L. Gibson..... 378,585

DESIGNS.

Carpet, E. H. Hill..... 18,118
Carpet, T. E. Meagher..... 18,115
Carpet, O. Righter..... 18,116 to 18,121
Check or counter, W. M. Welling..... 18,122
Desk, cabinet, F. A. Coffin..... 18,112
Desk, writing, F. A. Coffin..... 18,111
Furnace front, F. A. Williams..... 18,123
Stove, heating, Keep & Wipfler..... 18,114

TRADE MARKS.

Atomizers, A. P. Lighthill..... 15,232
Bleaching bluing, G. F. Soter..... 15,237
Cement, H. Fleming..... 15,230
Cough cure and certain proprietary medicines in the form of tablets, F. Hiller, Jr..... 15,245
Crackers, biscuits, and kindred articles, C. D. Boss & Son..... 15,227
Flour, E. Steinbrugge..... 15,238
Herb compound for certain diseases, a liniment, and a worm medicine, A. S. Palmer..... 15,247
Injection of milkweed, Roy Drug Co..... 15,248
Medicinal lotion for the skin, J. A. & D. F. Davenport..... 15,244
Medicinal remedies, certain, Standard Medicine Company..... 15,251
Medicine for female diseases, J. H. Schaaf..... 15,250
Medicine for the cure of headache, sea-sickness, epilepsy, and nervous debility, F. Newbery & Sons..... 15,246
Pantaloon, coats, and vests, Marx & Haas..... 15,238
Pills, G. Higgins..... 15,231
Pills, C. W. Palmer..... 15,235
Printing, gauge pins, feed guides, and other registering apparatus, tools, and machinery used in, E. L. Megill..... 15,234
Socks, Western Knitting Company..... 15,239
Tracing cloth, A. Winterbottom & Sons..... 15,240 to 15,243
Venereal diseases, cure for and preventive of, Sackett & Neat..... 15,249
Washing machines, C. E. Ross..... 15,236
Whisky, Dublin Whisky Distillery Company..... 15,229
Yarns, worsted and woolen, A. J. Cameron & Co..... 15,228

A printed copy of the specification and drawing of any patent in the foregoing list will be furnished from this office for 25 cents. In ordering please state the name and number of the patent desired, and remit to Munn & Co., 361 Broadway, New York.

Canadian Patents may now be obtained by the inventors for any of the inventions named in the foregoing list, provided they are simple, at a cost of \$40 each. If complicated the cost will be a little more. For full instructions address Munn & Co., 361 Broadway, New York. Other foreign patents may also be obtained.

Advertisements.

Inside Page, each insertion - - - 75 cents a line.
Back Page, each insertion - - - \$1.00 a line.
The above are charges per agate line—about eight words per line. This notice shows the width of the line, and is set in agate type. Engravings may head advertisements at the same rate per agate line, by measurement, as the letter press. Advertisements must be received at publication office as early as Thursday morning to appear in next issue.

EDISON ELECTRIC LIGHT

FOR
Mills, Factories, Stores, Hotels, Theatres, Steamboats, etc.
CENTRAL STATIONS FOR TOWNS AND VILLAGES.

The EDISON SYSTEM is the best and ONLY COMPLETE SYSTEM of incandescent electric lighting.
Over one thousand plants in successful operation. More than one million (1,000,000) Edison Lamps in use in the United States.

GUARANTEE: Twelve sixteen-candle power lamps to the mechanical Horse-Power. Estimates furnished for plants of 25 lights and upwards.
THE EDISON UNITED MANUFACTURING CO.,
65 Fifth Avenue, New York.


1885, D'1 Davis, Jr. 1849, Palmer & Hall. 1856, Thos. Hall.

THOMAS HALL, Manufactu'g Electrician & Optician

MANUFACTURER AND IMPORTER OF
Telegraphic, Electric, Magnetic, Galvanic, Optical, and Meteorological Instruments.
Chemicals, Chemical and Philosophical Apparatus of all descriptions.
Illustrated Catalogues of each department.
Hall's Patent Medical Batteries.
19 BROMFIELD ST., BOSTON, MASS.

IRRIGATING MACHINERY ON THE Pacific Coast.—By John Richards. An elaborate discussion of the modifications that have had to be made in irrigating machinery to meet the requirements of local conditions in California. Contained in SCIENTIFIC AMERICAN SUPPLEMENT Nos. 624 and 625. Price 10 cents each. To be had at this office and from all newsdealers.

PREPARE for the PRESIDENTIAL CAMPAIGN.




Ray's Patent Folding Transparency. Something entirely new for Political Clubs, Street Parades, etc. State, County, and City Rights for Sale. Apply to King Novelty Mfg. Co., Kansas City, Mo.

NATURAL GAS INDUSTRY AT PITTSBURG, Pa.—A brief history of the Chartiers Valley Gas Company. With 5 illustrations. Contained in SCIENTIFIC AMERICAN SUPPLEMENT No. 627. Price 10 cents. To be had at this office and from all newsdealers.

To Capitalists and Manufacturers

The undersigned wishes to arrange for the manufacture on royalty, or would sell outright, two simple inventions for which there is a large demand.
CURTAIN HOLDER, made of wire, which is simple, ornamented, inexpensive, and can be applied readily to any window casing, and which holds the curtain in graceful folds.
TOWEL RACK and WHISK BROOM HOLDER, made from wire, which may be attached to any window casing or other convenient support without the use of screws or nails. For further particulars apply to ANTON AHLQUIST, Ishpeming, Mich.



Improved Bench Centering Chuck. Will perfectly center round square, and octagonal pieces from 1/4 in. to 1 1/2 in. One of the most useful, durable, and labor saving tools ever made for centering purposes, and is being universally used. Price \$12. Manufactured by THE CUSHMAN CHUCK CO., Hartford, Conn.

THE GENERATION OF STEAM.—A lecture by Geo. H. Babcock delivered in the Sibley College Course. I. The production of Heat. Furnaces for burning bituminous and anthracite coal, wood, sawdust, waste gas, natural gas, etc., described. II. The Generation of Steam. General principles to be observed in the construction of boilers. With 14 figures. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, Nos. 624 and 625. Price 10 cents. To be had at this office and from all newsdealers.



STEEL WIRE OF EVERY DESCRIPTION & STEEL SPRINGS. NEW YORK CITY.
234 W. 29. ST.

BIT Square, Oval, or Round Smooth Holes. For carpenter, cabinet, and pattern work, 1/2 in. 50c., set \$4.00, mailed free. Bridgeport Gun Implement Co., 17 Maiden Lane, N. Y.



Shepard's New \$60 Screw-Cutting Foot Lathe. Foot and Power Lathes, Drill Presses, Scroll Saw Attachments, Chucks, Mandrels, Twist Drills, Dogs, Callipers, etc. Lathes on trial. Lathes on payment. Send for catalogue of Outfits for Amateurs or Artisans. Address H. L. SHEPARD, AGENT, 134 East 2d Street, Cincinnati, Ohio.



REMINGTON STANDARD TYPEWRITER
WYCKOFF, SEAMANS & BENEDICT, 327 Broadway, N. Y.

STORAGE BATTERIES FOR ELECTRIC LOCOMOTION.—A paper by A. Reckenzaun, offering a few facts and figures relating to the present state of the subject of the application of storage batteries to locomotive purposes. Contained in SCIENTIFIC AMERICAN SUPPLEMENT No. 625. Price 10 cents. To be had at this office and from all newsdealers.



SEBASTIAN, MAY & CO'S Improved Screw Cutting LATHES Power Foot & \$60.
Drill Presses, Chucks, Drills, Dogs, and machinists' and amateurs' outfits. Lathes on trial. Catalogues mailed on application. 165 W. 2d St., Cincinnati, O.

THE MIND CURE.—BY MARY J. FINLEY, M.D. A review of the theory of metaphysical healing in its relation to physiology and pathology. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 627. Price 10 cents. To be had at this office and from all newsdealers.



ARTESIAN Wells, Oil and Gas Wells, drilled by contract to any depth, from 60 to 3000 feet. We also manufacture and furnish everything required to drill and complete same. Portable Horse Power and Mounted Steam Drilling Machines for 100 to 600 ft. Send 6 cents for illustrated catalogue. Pierce Well Excavator Co. New York.

ICE-BOATS—THEIR CONSTRUCTION and management. With working drawings, details and directions in full. Four engravings, showing mode of construction. Views of the two fastest ice-boats used on the Hudson river in winter. By H. A. Horsfall, M.E. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 1. The same number also contains the rules and regulations for the formation of ice-boat clubs, the sailing and management of ice-boats. Price 10 cents.



BEST SHORT LINE TELEPHONES PRICES REDUCED.
Ellsworth's "Ei Eco" Telephones For short lines and speaking tube purposes. \$7.50 per pair. Send two 2-cent stamps for illustrated catalogue and circulars.
KNUDSON & ELLSWORTH, 39 Nassau St., N. Y. City.

200 Cute, Curious, Catchy Pictures 10c. P. O. BOX 2653, New York

SCIENTIFIC BOOK CATALOGUE, RECENTLY PUBLISHED.

Our new catalogue containing over 100 pages, including works on more than fifty different subjects. Will be mailed free to any address on application.
MUNN & CO., Publishers Scientific American, 361 Broadway, New York.

FIFTY YEARS' PROGRESS IN TELEGRAPHY.—By W. H. Preece, F.R.S. An interesting historical paper. Improvements in apparatus. Telephones, Pneumatic telegraphs, Cables, Railway telegraphs. Capital invested in telegraphs. Contained in SCIENTIFIC AMERICAN SUPPLEMENT No. 607. Price 10 cents. To be had at this office, and from all newsdealers.

8 LIGHT DYNAMO and MOTOR. As illustrated in SCI. AM. of April 23 and 30, '87, March 17, '88, and in SCI. AM. SUPPLEMENT, July 2, '87.



COMPLETE MACHINES OR CASTINGS AND MATERIAL FURNISHED ALSO WIRE FOR THE SAME.
Address W.S. BISHOP, 95 GRAND AV., NEW HAVEN, CT.

\$10.00 to \$50.00 per night. A light and profitable business. Magic Lanterns and Views of popular subjects. Catalogues on application. Part 1 Optical, 2 Mathematical, 3 Meteorological, 4 Magic Lanterns, etc. L. MANASSE, 88 Madison Street, Chicago, Ill.


COMPRESSION OF AIR.—DESCRIPTION of Messrs. Dubois & Francois' improved air compressing machine, devised for the use of the larger industries and for mining purposes. With 5 figures, illustrating the apparatus in plan, elevation and detail. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 435. Price 10 cents. To be had at this office and from all newsdealers.

New Catalogue of Valuable Papers contained in SCIENTIFIC AMERICAN SUPPLEMENT, sent free of charge to any address.
MUNN & CO., 361 Broadway, N. Y.

PLAYS

Dialogues, Tableaux, Speakers, for School, Club & Parlor. Bestout Catalogue free. T.S. DENISON, Chicago, Ill.

QUARANTINE SYSTEM OF LOUISIANA.—By Joseph Holt, M.D. Description of the methods of disinfection practiced. With 4 figures. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 627. Price 10 cents. To be had at this office and from all newsdealers.



THE ONLY PRACTICAL ELECTRIC MOTORS

ARCHITECTURAL BOOKS.

Useful, Beautiful, and Cheap.

To any person about to erect a dwelling house or stable, either in the country or city, or any builder wishing to examine the latest and best plans for a church, school house, club house, or any other public building of high or low cost, should procure a complete set of the ARCHITECTS' AND BUILDERS' EDITION of the SCIENTIFIC AMERICAN.

The information these volumes contain renders the work almost indispensable to the architect and builder, and to persons about to build for themselves they will find the work suggestive and most useful. They contain colored plates of the elevation, plan, and detail drawings of almost every class of building, with specifications and approximate cost.

Four bound volumes are now ready and may be obtained, by mail, direct from the publishers or from any newsdealer. Price, \$2.00 a volume. Stitched in paper covers. Subscription price, per annum, \$2.50. Address and remit to

MUNN & CO., Publishers, 361 Broadway, New York.

New and Valuable Books

GARDENING FOR PLEASURE.—By Peter Henderson. New and greatly enlarged edition. A guide to the amateur in the Fruit, Vegetable, and Flower Garden. Fully illustrated, cloth, 12mo. Price, postpaid, \$2.00

OUR HOMES.—How to beautify them. Full of suggestions for making the home attractive, and profusely illustrated. Cloth, 12mo. Price, postpaid, \$1.00

A B C OF AGRICULTURE.—By Mason C. Weld and other writers. A valuable and practical manual. Cloth, 12mo. Price, postpaid, 50 cents

HOME FISHING AND HOME WATERS.—By Seth Green. A practical treatise on Fish Culture. Cloth, 12mo. Price, postpaid, 50 cents

Illustrated Catalogue sent free on application.

O. JUDD CO., 751 Broadway, New York.



TIGHT & SLACK BARREL MACHINERY A SPECIALTY JOHN GREENWOOD & CO. ROCHESTER, N.Y.

ASPHALT AND CONCRETE FOOT Pavements.—A paper by G. R. Strachan, M.I.C.E., giving the experience of the writer and others on asphalt and concrete, as materials for foot pavements. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 626. Price 10 cents. To be had at this office and from all newsdealers.

DELAFIELD'S PAT. SAW CLAMP



With saw for cutting metals. Saves all the broken hack-saw blades. In use over two years in all parts of the country. The new clamps have the edges beveled that hold the saw—a great convenience. Price by mail for 50 cents. Discount to dealers. Extra blades 1/2-inch wide, 7 cents each, 70 cents per dozen, by mail. NOROTON MFG. WORKS, Noroton, Conn.

The Draper Recording Thermometer.



This thermometer gives a permanent and continuous record in ink of the temperature. The chart indicating hours of the day and days of the week gives the degrees of temperature from 20° below zero to 110° above. All instruments are accurately adjusted and warranted. The record is easily read and absolutely correct. Sold by the leading instrument dealers and opticians throughout the United States and Canada, and by THE DRAPER MANUFACTURING CO. Owners of the United States and foreign patents, 152 Front Street, New York Size 1 1/2x20 in. Patented. Copyrighted.

LEAD SMELTING.—A FULL DESCRIPTION of the Lewis Bartlett process, by William Ramsay; illustrated with 9 engravings. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 593. Price 10 cents. To be had at this office and from all newsdealers.

MODEL and EXPERIMENTAL WORK.—A SPECIALTY. Send for Circulars. C. E. Jones & Bro. CINCINNATI, O. (Mention this Paper.)

VOLNEY W. MASON & CO., FRICTION PULLEYS CLUTCHES and ELEVATORS PROVIDENCE, R. I.

THE FORTH RIDGE.—A PAPER BY A. S. Biggart, describing the method employed in the erection of this great engineering work. With 8 figures. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 626. Price 10 cents. To be had at this office and from all newsdealers.

PERFECT NEWSPAPER FILE


The Koch Patent File, for preserving newspapers, magazines, and pamphlets, has been recently improved and price reduced. Subscribers to the SCIENTIFIC AMERICAN and SCIENTIFIC AMERICAN SUPPLEMENT can be supplied for the low price of \$1.50 by mail, or \$1.25 at the office of this paper. Heavy board sides; inscription "SCIENTIFIC AMERICAN" in gilt. Necessary for every one who wishes to preserve the paper. Address

MUNN & CO., Publishers SCIENTIFIC AMERICAN.

ON 30 DAYS' TRIAL; THIS NEW ELASTIC TRUSS

Has a Pad different from all others, is cup shape, with Self-adjusting Ball in center, adapts itself to all positions of the body, while the ball in the cup presses back the intestines just as a person does with the finger. With light pressure the Hernia is kept in its position and a cure is certain. It is easy, durable and cheap. Sent by mail Circulars free. EGGLESTON TRUSS CO., Chicago, Ill.

THE DUNNING PATENT WROUGHT IRON BOILER. (Over 13,500 in use.)




THE Dunning Boiler, Self-Feeding, is the best for Low Pressure Steam Heating, and insures a warm house night and day. Free from Carbonic Acid Gas and Smoke. Made in eleven sizes, suitable to heat the Smallest Cottage to the Largest Business Block, in five different styles: As a Magazine Boiler, which requires attention but once in twenty-four hours. As a Surface Burning Boiler, which will burn Hard or Soft Coal, Wood, Coke or Gas. As a Hot Water Boiler, for Green House and hot water heating. As a Portable Boiler, to be set without brickwork. Also in Two Sections, to pass through any door or window, where whole one cannot enter. Steam Engines and Boilers of all kinds and machinery generally. Manufactured at the New York Central Iron Works, Geneva, N. Y., U.S.A. Lock Box 40. Send for New Illustrated Catalogue.



Trade Mark.

Steel Brick Machines, Driers & Kilns

Gregg's Steel Brick Machines, Front and Ornamental; Gregg's Clay Crusher Roller Mills; Gregg's Disintegrating Mills; Gregg's Steam Driers for Bricks, Tile, Lumber, Paper, Fabrics, etc.; Gregg's Brick Kilns, Direct, Down Draft, and Compartment; also, Hydro-Carbon Furnaces. Plans and Specifications by competent engineers for complete works. GREGG MANUFACTURING CO., 423 Walnut St., Philadelphia, Pa., U.S.



HARMON'S IMPROVED Leveling Instrument. With or without Compass. The boss for Engineers, Machinists, and all others requiring a low price Leveling Instrument for grading, measuring heights, squaring, or getting any desired angle. Illustrated circular sent on receipt of stamp. JOHN W. HARMON, 65 Haverhill Street, Boston, Mass.

Notice to Engine Builders.

The National Cash Register Co. of Dayton, O., will receive bids until March 15th for one first-class 100 horse power engine, boiler, heater, pump, and purifier, all set up and ready to run. Proposals are invited from all first-class builders.

AMERICAN Leather Link Belt Co. A new article in Belting which is made of small Leather Links joined together with steel bolts. They have been remarkably successful for hard working machinery and belts run half crossed. For prices and particulars write to CHAS. A. SCHILBEN & CO. 47 Ferry St., New York; 416 Arch St., Phila.; 86 Federal St., Boston.

GUILD & GARRISON

BROOKLYN, N. Y., U.S.A. Builders of Steam Pumps for Water and every description of Liquids or Semi-liquids. Vacuum Pumps of the highest efficiency. Filter Press Pumps, Air, Gas, and Acid Blowers. Air Compressors. Boiler Feed Pumps, etc.

ASBESTOS

BRAIDED PACKING, MILL BOARD, SHEATHING, CEMENT, FIBRE and SPECIALTIES. CHALMERS-SPENCE CO., FOOT B. 8TH ST., N. Y. BRANCHES: Phila, 32 S. 2d St. Chicago, 144-146 E. Lake St. Pittsburg, 37 Lewis Block.

OTTO GAS ENGINES.

Over 25,000 Sold. Horizontal.....Otto....Gas Engines. Vertical.....Otto....Gas Engines. Twin Cylinder.....Otto....Gas Engines. Combined.....Otto....Gas Engines and Pumps. Combined.....Otto....Gas Engines and Dynamos. OTTO GAS ENGINE WORKS, CHICAGO, PHILADELPHIA. New York Agency, 18 Vesey Street.

FOREIGN TRADE. JOHN G. ROLLINS & Co., Limited, London, England, an old established and reliable House, are well situated to represent American Manufacturers in the sale of their products in Foreign Countries. Satisfactory American and English reference if required. Address direct, or American Office, 4 Stone Street, New York City.

CLARK'S NOISELESS RUBBER WHEELS. No more Splintered Floors. Different Styles. Catalogue Free. GEO. P. CLARK, Windsor Locks, Ct. Box L.

ICE-HOUSE AND COLD ROOM.—BY R. G. Hatfield. With directions for construction. Four engravings. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 59. Price 10 cents. To be had at this office and from all newsdealers.

OIL ENGINES. For Printers, Steam Yachts, pumping water, sawing wood, making ice-cream, Carpenters, Mechanics, to 5 H.P. Fuel, Kerosene. No dust. Automatic in fuel and water supply. Illustrated Catalogue free. Mention SCIENTIFIC AMERICAN. SHIPMAN ENGINE CO. 92 Pearl St., Boston, Mass.

\$1,000 REWARD! We offer \$1000.00 Reward for a cough or throat trouble (last stages of disease excepted), which can not be relieved by a proper use of Dr. X. Stone's Bronchial Waters. Sample free. Address STONE MEDICINE CO., Quincy, Ill.

RUBBER BELTING, PACKING, HOSE.

Oldest and Largest Manufacturers in the United States. VULCANIZED RUBBER FABRICS For Mechanical Purposes. Air Brake Hose A SPECIALTY. RUBBER MATS, RUBBER MATTING, AND STAIR TREADS. NEW YORK BELTING & PACKING CO., 15 PARK ROW, N. Y. JOHN H. CHEEVER, Treas., Branches: 167 Lake St., Chicago; 308 Chestnut St., Phila.; 52 Summer St., Boston; J. D. CHEEVER, Dep'y Treas. Post & Co., Cin., O. Europe'n Br'ch, Pickhuben 5 Hamburg (Freihafengebiet), Ger.

ICE & REFRIGERATING

Machines. York Patent. YORK MFG. CO., York, Pa.

Blake's Belt Stud.

The Strongest, Cheapest, and Best Fastening for Leather and Rubber Belting. Beware of fraudulent and poor imitations. None genuine without this trade mark and picture on the package. Greene, Tweed & Co. Manufacturers, 83 Chambers Street, New York. PATENTED JULY 31, 1883.

PATENT RIGHTS FOR SALE.

APPARATUS FOR BUILDING CONCRETE BUILDINGS AND WALLS. County Rights, \$50. State Rights, \$500. See descriptive notice in SCI. AMERICAN, May 22, 1886. Send for circulars. Ransome, 402 Montgomery St., S.F. Cal.

SHIELDS & BROWN CO.

Manufacturers of Sectional Insulated Air Coverings. FOR Steam, Gas and Water Pipes, Drums, Heaters, etc. The Best Non-Conductor of Heat & Cold in the World. Send for illustrated descriptive Circular, and name this paper. 143 7th Street, NEW YORK. 78 and 80 Lake St., CHICAGO.

SYRACUSE WATER MOTOR.

With Automatic Governor shutting off all surplus water. The amount of power developed by these motors is only limited by the amount of pressure available and quantity of water used. We guarantee something which is safer than a high rated horse power, and that is, that these motors will perform the work satisfactorily which they are sold for. Are adapted for all kinds of light machinery, electric light dynamos, dairy work, elevators, church organs. Manuf'd by TUERK WATER METER CO., Syracuse, N.Y.

PIPE COVERINGS

Made entirely of ASBESTOS. Absolutely Fire Proof. BRAIDED PACKING, MILL BOARD, SHEATHING, CEMENT, FIBRE and SPECIALTIES. CHALMERS-SPENCE CO., FOOT B. 8TH ST., N. Y. BRANCHES: Phila, 32 S. 2d St. Chicago, 144-146 E. Lake St. Pittsburg, 37 Lewis Block.

ASK YOUR STATIONER FOR THE JOHANN FABER LEAD PENCILS THE BEST NOW MADE

THE COPYING PAD.—HOW TO MAKE

and how to use; with an engraving. Practical directions how to prepare the gelatine pad, and also the aniline ink by which the copies are made; how to apply the written letter to the pad; how to take off copies of the letter. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 438. Price 10 cents. For sale at this office and by all newsdealers in all parts of the country.

SUPERIOR Stationary Engines with Plain and Automatic Cut-off. Vertical and Horizontal. Penna. Diamond Drill Co., Birdsboro, Pa.

2000 Fine Black copies of Writing, Drawing, Music. FAST AUTOMATIC Works automatically with wonderful precision and rapidity. FAST AUTOMATIC CO., 2 New Chambers St., N. Y.

2nd MACHINERY

Encyclopedia of 700 Engravings of WELLS TOOLS. Diamond Drills and Lighting Hydraulic Wells Machines. Book free, 25c. for mailing it. American Well Works, Aurora, Ill.

HODGE'S Universal Angle Union

PATENTED. Combining an elbow and union, and can be set at any angle at which it is desired to run the pipe. Manufacturers & Wholesale Agents, BOLLSTONE MACHINE CO., 48 Water St., FITCHBURG MASS.

To Manufacturers!

The North St. Paul Land Company, of St. Paul, Minn., are desirous of locating on their land twenty more large manufacturing establishments. There is no place in the United States better adapted for manufacturing some lines of goods than St. Paul. To any one wishing to engage in this business, we are prepared to offer liberal inducements in land and cash. Correspondence solicited. We mean business.

The North St. Paul Land Co., ST. PAUL, MINN.

CAMERA BELLOWS.—FULL DESCRIPTION. With 12 figures, by means of which any amateur can easily make a camera bellows for himself. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 625. Price 10 cents. To be had at this office and from all newsdealers.

Well Drills

FOR EVERY PURPOSE SOLD ON TRIAL. Investment small, profits large. Send 20c. for mailing large illustrated Catalogue with full particulars. Manufactured by GOULDS & AUSTIN, 167 & 169 LAKE ST. CHICAGO, ILLINOIS

CITY OF LONDON AND SOUTHWARK SUBWAY.—Description of a new underground railway now in course of construction in London. With 7 figures. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 626. Price 10 cents each. To be had at this office and from all newsdealers.

IT PAYS to sell our Rubber Stamps. Free Catalogue to agents. Chandler & Fisher, Cleveland, O.

FOR SALE. "Novel Rope Clamp" Patent. Simple, durable, and serviceable device to secure rope any thickness without requiring knot. Most available device of the kind ever patented. Write for terms. WM. B. DENTHORNE, Patentee, Phoenixville, Pa.

FOR SALE.

A Water Power Plant suitable for manufacturing of any kind, situated in Northern Illinois. Solid, well built stone building, floor space of 14,000 square feet. A never failing water power of 150 horse power. Good shipping facilities by two railroads, C. & N.W., and C. B. & Q. R.R. Part payment in cash, balance on any reasonable length of time. Address E. C. CHURCH, Sterling, Illinois.

\$5 COUNTY RIGHTS. P. O. Box 304, Sandusky, O.

FOR SALE. An interest in Patent for a Gas Regulator, or State Right thereunder. PHELPS, 120 West 9th Street, New York.

TAKE THE MONON ROUTE BETWEEN Chicago and Louisville, Indianapolis, Cincinnati, and all winter cities of the South. E. O. McCormick, Gen. Pass. Agent, Chicago.

To Business Men.

The value of the SCIENTIFIC AMERICAN as an advertising medium cannot be overestimated. Its circulation is many times greater than that of any similar journal now published. It goes into all the States and Territories, and is read in all the principal libraries and reading rooms of the world. A business man wants something more than to see his advertisement in a printed newspaper. He wants circulation. This he has when he advertises in the SCIENTIFIC AMERICAN. And do not let the advertising agent influence you to substitute some other paper for the SCIENTIFIC AMERICAN, when selecting a list of publications in which you decide it is for your interest to advertise. This is frequently done, for the reason that the agent gets a larger commission from the papers having a small circulation than is allowed on the SCIENTIFIC AMERICAN. For rates see top of first column of this page, or address

MUNN & CO., Publishers, 361 Broadway, New York.

CASTING METALS UPON COMBUSTIBLE MATERIALS.—A paper by A. E. Outerbridge Jr., describing a process of casting iron and other metals upon lace, embroideries, fern fronds, and other combustible materials. With 4 illustrations. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 601. Price 10 cents. To be had at this office and from all newsdealers.

The Scientific American PUBLICATIONS FOR 1888.

The prices of the different publications are as follows: RATES BY MAIL. The Scientific American (weekly), one year \$3.00 The Scientific American Supplement (weekly), one year 5.00 The Scientific American, Export Edition (monthly) one year 5.00 The Scientific American, Architects and Builders Edition (monthly), one year 2.50

COMBINED RATES. The Scientific American and Supplement, \$7.00 The Scientific American and Architects and Builders Edition, 5.00 The Scientific American, Supplement, and Architects and Builders Edition, 9.00 Proportionate Rates for Six Months. This includes postage, which we pay. Remits by postal or express money order, or draft to order of MUNN & CO., 361 Broadway, New York.

CURE FOR THE DEAF

PECK'S PATENT IMPROVED CURSIONED EAR DRUMS Perfectly Restore the Hearing, whether deafness is caused by colds, fevers or injuries to the natural drums. Invisible, comfortable, always in position. Music, conversation, whistles heard distinctly. Write to F. HISCOCK, 853 Broadway, cor. 14th St., New York, for illustrated book of proofs FREE.

Advertisements.

Inside Page, each insertion ... 25 cents a line. Back Page, each insertion ... \$1.00 a line.

IMPROVED SCREW PITCH GAUGE.

SENT BY MAIL FOR \$1.00. This Gauge has TWENTY PITCHES, viz: 9, 10, 11, 12, 13, 14, 15, 16, 18, 20, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40.

BUFFALO FORGE CO. MAKE BEST LINE FORGES BLOWERS EXHAUSTERS DRILLS

New Gas Engine "The Baldwin"

Exhibited at the late American Institute Fair, New York. A four horse-power engine in connection with storage battery, running 34 incandescent electric lights.

Otis Brothers & Co., Elevators and Hoisting Machinery, 38 PARK ROW, NEW YORK.

COPPER TUBES SHEET BRASS BRASS WIRE

DISEASES OF DYNAMOS.—A PAPER by S. P. Thompson, D. Sc., discussing the maladies to which dynamo machines are liable, and their treatment, cure and prevention.

HARTFORD STEAM BOILER INSPECTION AND INSURANCE CO. HARTFORD, CONN.

THE MODERN ICE YACHT.—BY Geo. W. Polk. A new and valuable paper, containing full practical directions and specifications for the construction of the fastest and best kinds of Ice Yachts.

PATENT JACKET KETTLES, Plain or Porcelain Lined. Tested to 100 lb. pressure. Send for Lists. HAND, BURR & CO.

Barnes' Foot-Power Machinery. Complete outfits for Actual Workshop Business. Read what a customer says: "Considering its capacity and the accuracy of your No. 4 Lathe, I do not see how it can be produced at such low cost."

PATENTS.

MESSRS. MUNN & CO., in connection with the publication of the SCIENTIFIC AMERICAN, continue to examine improvements, and to act as Solicitors of Patents for Inventors.

"THE STANDARD." H.W. JOHNS ASBESTOS BOILER COVERINGS. ASBESTOS CEMENT FELTING. AIR-CHAMBER COVERING. SECTIONAL PIPE COVERING. ASBESTOS LINING FELT. PATENTED.

WATCHMAKERS

Before buying, send for Price List of Whitcomb Lathe, Webster Foot-Wheel and our Table of Equivalents. American Watch Tool Co., Waltham, Mass.

STEAM YACHTS AND PLEASURE BOATS.



Hulls, 19 to 40 ft. Strongest and best obtainable models. Stationary and Marine Engines and Boilers, Petroleum Fuel. Simple, Safe, Compact, Durable, Cheap.



Row and Sail Boats. Paddling and Sailing Canoes. All Styles, Sizes and Prices. Send Stamp for Catalogues. THOMAS KANE & COMPANY, 137 and 139 Wabash Avenue, Chicago, Ill., U. S. A.

IF YOU USE VALVES JENKINS BROS. 71 John St., New York. 105 Milk St., Boston. 13 S. Fourth St., Phila. 54 Dearborn St., Chicago.

"UNIQUE" Screw Holding Screw Driver. Wallen's Patent. The ALFORD & BERKELEY COMPANY, Sole Agents, 77 Chambers St., New York P. O. Box 2002.

HARRISON CONVEYOR! For Handling Grain, Coal, Sand, Clay, Tan Bark, Cinders, Ores, Seeds, &c. BORDEN, SELLECK & CO., Sole Mfrs., Chicago, Ill.

COLUMBIA BICYCLES. TRICYCLES. TANDEM. GUARANTEED HIGHEST GRADE ILLUSTRATED CATALOGUE—FREE. POPE MFG. CO. 79 FRANKLIN ST. BOSTON BRANCH 112 WARREN ST. NEW YORK HOUSES 221 WABASH AVE. CHICAGO.

THE CHEAPEST AND BEST PHOTO ENGRAVING CO. 67 PARK PLACE NEW YORK ENGRAVING FOR ALL ILLUSTRATIVE AND ADVERTISING PURPOSES

USEFUL BOOKS.

Manufacturers, Agriculturists, Chemists, Engineers, Mechanics, Builders, men of leisure, and professional men, of all classes, need good books in the line of their respective callings.

Shafting and Gearing, Textile Machinery, ELEVATORS, ETC.

We are prepared to furnish the finest quality of THROUGH PUNCHES and DIES for METAL WORK, for the manufacture of which we have unequalled facilities.

SYRACUSE MALLEABLE IRON WORKS W. B. BURNS PROP.

THE IMPROVED ECONOMY Combination Steam & Warm Air Heater. An apparatus in which one fire generates both Warm Air and Steam. Send for Catalogue illustrating these Heaters, and also the ECONOMY WARM AIR FURNACES.

J. F. Pease & Co. Syracuse, N. Y. Toronto, Ont. 206 Water Street, New York. 75 Union Street, Boston. 177 East Randolph Street, Chicago.

THE Scientific American

ESTABLISHED 1846. The Most Popular Scientific Paper in the World. Only \$3.00 a Year, including Postage. Weekly. 52 Numbers a Year.

This widely circulated and splendidly illustrated paper is published weekly. Every number contains sixteen pages of useful information and a large number of original engravings of new inventions and discoveries.

Terms of Subscription.—One copy of the SCIENTIFIC AMERICAN will be sent for one year—52 numbers—postage prepaid, to any subscriber in the United States or Canada, on receipt of three dollars by the publishers; six months, \$1.50; three months, \$1.00.

The safest way to remit is by Postal Order, Draft, or Express Money Order. Money carefully placed inside of envelopes, securely sealed, and correctly addressed, seldom goes astray, but is at the sender's risk.

MUNN & CO., 361 Broadway, New York.

THE Scientific American Supplement.

This is a separate and distinct publication from THE SCIENTIFIC AMERICAN, but is uniform therewith in size, every number containing sixteen large pages full of engravings, many of which are taken from foreign papers, and accompanied with translated descriptions.

The most important Engineering Works, Mechanisms, and Manufactures at home and abroad are illustrated and described in the SUPPLEMENT.

Price for the SUPPLEMENT for the United States and Canada, \$5.00 a year, or one copy of the SCIENTIFIC AMERICAN and one copy of the SUPPLEMENT, both mailed for one year for \$7.00. Single copies 10 cents.

MUNN & Co., 361 Broadway, N. Y., Publishers SCIENTIFIC AMERICAN.

Builders Edition.

THE SCIENTIFIC AMERICAN ARCHITECTS' AND BUILDERS' EDITION is issued monthly. \$2.50 a year. Single copies, 25 cents. Forty large quarto pages, equal to about two hundred ordinary book pages; forming a large and splendid Magazine of Architecture, richly adorned with elegant plates in colors, and with other fine engravings; illustrating the most interesting examples of modern Architectural Construction and allied subjects.

A special feature is the presentation in each number of a variety of the latest and best plans for private residences, city and country, including those of very moderate cost as well as the more expensive. Drawings in perspective and in color are given, together with full Plans, Specifications, Sheets of Details, Estimates, etc.

The elegance and cheapness of this magnificent work have won for it the Largest Circulation of any Architectural publication in the world. Sold by all newsdealers. \$2.50 a year. Remit to

MUNN & CO., Publishers, 361 Broadway, New York.

PRINTING INKS.

THE "Scientific American" is printed with CHAS. ENEU JOHNSON & CO.'S INK. Tenth and Lombard Sts., Phila., and 47 Rose St., opp. Duane St., N. Y.